

ARKANSAS STATE HIGHWAY & TRANSPORTATION DEPARTMENT
EQUIPMENT AND PROCUREMENT OFFICE
LITTLE ROCK, ARKANSAS

April 16, 2014


NOTICE TO BIDDERS

ADDENDUM

Bid Number: H-14-320R

Opening Date: May 6, 2014

Bid Specifications were inadvertently left out of bid.



Danny Keene
Division Head
Equipment and Procurement

ARKANSAS STATE HIGHWAY AND TRANSPORTATION DEPARTMENT

SPECIFICATION 14-276-007

FOR

COMPACT PASSENGER VAN

1. GVWR: No less than 5,600 pounds.
2. Wheelbase: Minimum of 120".
3. Overall Length: No less than 200".
4. Engine: Flex Fuel capable "V" configuration with a minimum piston displacement of 3.3 liters equipped with full flow oil filter, air cleaner, maintenance free battery with a minimum rating of 600 cold cranking amps at 0° F and not less than 130 amp alternator.
5. Cooling: Anti-freeze protection to -20° F, or lower.
6. Transmission/Transaxle: Automatic, with a minimum of four (4) forward speeds.
7. Steering: Hydraulic actuated power steering as regularly offered by manufacturer.
8. Suspension: Capacity of front and rear suspension shall be as recommended by manufacturer for vehicle to meet or exceed GVWR specified above.
9. Brakes: Power front and rear disc with 4 wheel anti-lock and mechanical parking brake as regularly furnished by manufacturer.
10. Body: Passenger body style with complete body glass all around, including side doors and rear door(s)/liftgate. All glass shall be tinted (standard tint). Interior shall be fully insulated and include full length headliner, side trim panels in passenger and cargo area and full door trim panels (headliner and trim panels may be dealer installed if equivalent in quality to standard type offered by vehicle manufacturer).

Interior floor shall be fully covered with fitted rubber floor mat or color keyed factory carpeting. Shall have dome lights, factory installed electronic AM/FM radio, factory installed fresh air heater-defroster unit, right and left sun visors, key locks on door/s, inside rear view mirror, dual door mounted below eye level exterior mirrors and all standard equipment and appointments, both exterior and interior, as listed in manufacturer's data book.
11. Doors: Two (2) front doors and two (2) side sliding type doors. Rear entry shall consist of either a liftgate or swing-out type door(s).
12. Seating: Minimum seven (7) passenger seating complete with seat belts for all seating positions. Front driver and passenger seats shall be bucket type. Remaining seats shall be removable and may be either bucket or bench type.
13. Upholstery: All seats to be upholstered in cloth.
14. Air Conditioning: Front, mounted in instrument panel.
15. Tilt Steering Column: Factory installed.
16. Speed Control: Automatic speed control (may be dealer installed, but of same manufacturer as vehicle).
17. Windshield Wipers: Dual electric intermittent windshield wipers with washers.
18. Tires and Wheels: Four (4) manufacturer's factory standard for vehicle and one (1) spare as regularly furnished by manufacturer.
19. Fuel Tank: Minimum capacity of 20 gallons.
20. Lights: Dual beam headlights, parking lights, self canceling directional turn signals with hazard flasher switch, back up lights and side marker lights. Rear lights to consist of stop and tail lights in addition to directional signals.
21. Equipment: Front and rear bumpers, rear license plate bracket, hub caps, jack and lug wrench.
22. Keys: Minimum of four (4) ignition/door keys per vehicle.
23. Color: Sherwin Williams F8W2030 Frost White Acrylic Enamel, or equal. Front and rear bumpers, grill, mirrors, wheels and hub caps as regularly furnished by manufacturer.