



## STANDARD BID CONDITIONS

## H-17-277H

1. **ACCEPTANCE AND REJECTION:** The Arkansas State Highway and Transportation Department (AHTD) reserves the right to reject any or all bids, to accept bids in whole or in part (unless otherwise indicated by bidder), to waive any informalities in bids received, to accept bids on materials or equipment with variations from specifications where efficiency of operation will not be impaired, and to award bids to best serve the interest of the State.
2. **PRICES:** Unless otherwise stated in the Bid Invitation, the following will apply: (1) unit prices shall be bid, (2) prices should be stated in units of quantity specified (feet, each, lbs., etc.), (3) prices must be F.O.B. destination specified in bid, (4) prices must be firm and not subject to escalation, (5) bid must be firm for acceptance for 30 days from bid opening date. In case of errors in extension, unit prices shall govern. Discounts from bid price will not be considered in making awards.
3. **BID BONDS AND PERFORMANCE BONDS:** If required, a **Bid Bond** in the form of a cashier's check, certified check, or surety bond issued by a surety company, in an amount stated in the Bid Invitation, must accompany bid. **Personal and company checks are not acceptable as Bid Bonds.** Failure to submit a Bid Bond as required will cause a bid to be rejected. The Bid Bond will be forfeited as liquidated damages if the successful bidder fails to provide a required Performance Bond within the period stipulated by AHTD or fails to honor their bid. Cashier's checks and certified checks submitted as Bid Bonds will be returned to unsuccessful bidders; surety bonds will be retained. The successful bidder will be required to furnish a **Performance Bond** in an amount stated in the Bid Invitation and in the form of a cashier's check, certified check, or surety bond issued by a surety company, unless otherwise stated in the Bid Invitation, as a guarantee of delivery of goods/services in accordance with the specifications and within the time established in the bid. **Personal and company checks are not acceptable as Performance Bonds.** In some cases, a cashier's check or certified check submitted as a Bid Bond will be held as the Performance Bond of the successful bidder. Cashier's checks or certified checks submitted as Performance Bonds will be refunded shortly after payment has been made to the successful bidder for completion of all terms of the bid; surety bonds will be retained. Surety bonds must be issued by a surety company authorized to do business in Arkansas, and must be signed by a Resident Local Agent licensed by the Arkansas State Insurance Commissioner to represent that surety company. Resident Agent's Power-of-Attorney must accompany the surety bond. Certain bids involving labor will require Performance Bonds in the form of surety bonds only (no checks of any kind allowed). In such cases, the company issuing the surety bond must comply with all stipulations herein and must be named in the U. S. Treasury listing of companies holding Certificates of Authority as acceptable sureties on Federal Bonds and as acceptable reinsuring companies. Any excess between the face amount of the bond and the underwriting limitation of the bonding company shall be protected by reinsurance provided by an acceptable reinsuring company. Annual Bid and Performance Bonds on file with E & P Division must have sufficient unencumbered funds to meet current bonding requirements, or the bid will be rejected, unless the balance is submitted as set forth above, prior to bid opening.
4. **TAXES:** The AHTD is not exempt from Arkansas State Sales and Use Taxes, or local option city/county sales taxes, when applicable, and bidders are responsible to the State Revenue Department for such taxes. These taxes should not be included in bid prices, but where required by law, will be paid by the AHTD as an addition thereto, and should be added to the billing to the AHTD. The AHTD is exempt from Federal Excise Taxes on all commodities except motor fuels; and excise taxes should not be included in bid prices except for motor fuels. Where applicable, tax exemption certificates will be furnished by the AHTD.
5. **"ALL OR NONE" BIDS:** Bidders who wish to bid "All or None" on two or more items shall so stipulate on the face of bid sheet; otherwise, bid may be awarded on an individual item basis.
6. **SPECIFICATIONS:** Complete specifications should be attached for any substitution or alternate offered, or where amplification is necessary. Bidder's name must be placed on all attachments to the bid.
7. **EXCEPTIONS TO SPECIFICATIONS:** Any exceptions to the bid specifications must be stated in the bid. Any exceptions to manufacturer's published literature must be stated in the bid, or it will be assumed that bidder is bidding exactly as stated in the literature.
8. **BRAND NAME REFERENCES:** All brand name references in bid specifications refer to that commodity or its equivalent, unless otherwise stated in Bid Invitation. Bidder should state brand or trade name of item being bid, if such name exists.
9. **FREIGHT:** All freight charges should be included in bid price. Any change in common carrier rates authorized by the Interstate Commerce Commission will be adjusted if such change occurs after the bid opening date. Receipted common carrier bills that reflect ICC authorized rate changes must be furnished.
10. **SAMPLES, LITERATURE, DEMONSTRATIONS:** Samples and technical literature must be provided free of any charge within 14 days of AHTD request, and free demonstrations within 30 days, unless AHTD extends time. Failure to provide as requested within this period may cause bid to be rejected. Samples, literature and demonstrations must be substantially the same as the item(s) being bid, unless otherwise agreed to by AHTD. Samples that are not destroyed will be returned upon request at bidders expense. Samples from successful bidders may be retained for comparison with items actually furnished.
11. **GUARANTY:** Unless otherwise indicated in Bid Invitation, it is understood and agreed that any item offered or shipped on this bid shall be newly manufactured, latest model and design, and in first class condition; and that all containers shall be new, suitable for storage or shipment and in compliance with all applicable laws relating to construction, packaging, labeling and registration.
12. **BACKORDERS OR DELAY IN DELIVERY:** Backorders or failure to deliver within the time required may constitute default. Vendor must give written notice to the AHTD, as soon as possible, of the reason for any delay and the expected delivery date. The AHTD has the right to extend delivery if reasons appear valid. If reason or delivery date is not acceptable, vendor is in default.
13. **DEFAULT:** All commodities furnished will be subject to inspection and acceptance by AHTD after delivery. Default in promised delivery or failure to meet specifications authorizes the AHTD to cancel award or any portion of same, to reasonably purchase commodities or services elsewhere and to charge full increase, if any, in cost and handling to defaulting vendor. Applicable bonds may be forfeited.
14. **ETHICS:** *"It shall be a breach of ethical standards for a person to be retained, or to retain a person, to solicit or secure a State contract upon an agreement of understanding for a commission, percentage, brokerage, or contingent fee, except for retention of bona fide employees or bona fide established commercial selling agencies maintained by the contractor for the purpose of securing business."* (Arkansas Code, Annotated, Section 19-11-708).

# **ARKANSAS STATE HIGHWAY AND TRANSPORTATION DEPARTMENT**

## **NOTICE OF NONDISCRIMINATION**

The Arkansas State Highway and Transportation Department (Department) complies with all civil rights provisions of federal statutes and related authorities that prohibit discrimination in programs and activities receiving federal financial assistance. Therefore, the Department does not discriminate on the basis of race, sex, color, age, national origin, religion (not applicable as a protected group under the Federal Motor Carrier Safety Administration Title VI Program), disability, Limited English Proficiency (LEP), or low-income status in the admission, access to and treatment in the Department's programs and activities, as well as the Department's hiring or employment practices. Complaints of alleged discrimination and inquiries regarding the Department's nondiscrimination policies may be directed to Joanna P. McFadden Section Head – EEO/DBE (ADA/504/Title VI Coordinator), P. O. Box 2261, Little Rock, AR 72203, (501)569-2298, (Voice/TTY 711), or the following email address: **[joanna.mcfadden@ahtd.ar.gov](mailto:joanna.mcfadden@ahtd.ar.gov)**

Free language assistance for Limited English Proficient individuals is available upon request.

This notice is available from the ADA/504/Title VI Coordinator in large print, on audiotape and in Braille.

**ARKANSAS STATE HIGHWAY AND TRANSPORTATION DEPARTMENT**

**SPECIFICATION 17-306-171**

**FOR**

**TOW TYPE PAVER**

**A. General Conditions:**

1. **Current Model:** Units furnished under this specification shall be the latest improved model in current production, as offered to commercial trade, built for the U.S. market, and shall be of quality workmanship and material. Machines manufactured for foreign markets will not be accepted. All equipment offered under this specification shall be new. Used, reconditioned, shopworn, demonstrator, prototype or discontinued models are not acceptable. Manufacturers of the units supplied must have been in the business of producing operational units for at least two years and must have recently sold similar units to domestic governmental agencies. The model furnished must have been in production for a minimum of one year, or be the latest version of a previous model. Bidder/s may be required to submit documentation substantiating the aforementioned requirements. A list of user references may also be required.
2. **Literature:** Manufacturers literature, verifying adherence of proposed unit to each line item addressed in this specification, shall be submitted with the bid. If any literature and/or specifications of items conflict with AHTD specifications, the conflict(s) shall be specifically noted, corrected and submitted with the bid.
3. Any deviations from specifications and requirements herein must be clearly pointed out by bidder. Otherwise it will be considered that equipment offered is in strict compliance with these specifications and requirements, and successful bidder will be held responsible therefor. Deviations must be explained in detail on an attached sheet. However, no implication is made by the Arkansas State Highway and Transportation Department that deviations will be acceptable.
4. **Manuals:** The successful bidder shall furnish one (1) Operator's Instruction Manual with each unit delivered and one (1) copy each of Shop Repair Manual and Parts Book to each FOB point.  
  
The successful bidder may provide Shop Repair Manuals and Parts Manuals on computer media (CD, DVD, USB Drive, etc.) in lieu of printed manuals.
5. **Training:** The successful bidder shall furnish qualified personnel to instruct AHTD operators and service technicians on operation and maintenance of machine.  
  
In addition, the successful bidder shall furnish information on any factory service schools which would be available for AHTD service technicians.
6. Shall be assembled, adjusted and made ready for continuous operation at time of delivery.
7. All parts, accessories and tools necessary for satisfactory operation of this unit shall be furnished whether or not they are specifically mentioned in this specification (including standard equipment as regularly furnished by manufacturer as shown on printed literature and specifications - unless specifically excluded by this specification).
8. **Parts Inventory & Service Facilities:** The successful bidder shall maintain a representative inventory of replacement parts and service facilities for servicing equipment bid on.
9. **Demonstration:** The Arkansas State Highway & Transportation Department reserves the right to require a demonstration, under actual working conditions, of equipment bid under this specification before award is made. The demonstration would be performed (free of any charge) by the bidder or an authorized representative at a mutually acceptable location. If requested, the bidder should be prepared to demonstrate the equipment within thirty (30) days after notification. Failure of the bidder to perform a satisfactory demonstration within the specified time may be grounds for rejection of the bid.
10. **Cooperative Purchasing:** Other tax-supported entities\* in Arkansas (cities, counties, state agencies, school districts, etc.) may purchase from this Contract on an individual basis under the same specifications and conditions, and at the pricing set forth by each vendor, all at the discretion of each vendor in each case. Prices could be reduced by a vendor for minor alterations in conditions (changing order quantities, deleting options, etc.) as agreed by both parties, but could not be raised above the contract bid price except for any additional freight charges. Vendors would not be required to sell to any such entity under this contract, and those entities would not be obligated to purchase from the contract.

Each entity wishing to purchase from the contract must make contact directly with the appropriate vendor(s). The Highway Department shall remain "out of the loop" for such transactions: all contact, orders, invoices, payments, etc. regarding such transactions must take place exclusively between the tax-supported entity and the vendor. The Department shall be held harmless of any and all liability arising from such transactions.

\* Tax-supported entities are defined as those receiving more than half of total funding from appropriated tax funds.

B. **Unit specifications:**

1. **General:** This specification is intended to cover a Tow Type Paving Machine with one or more propane fueled engine(s), a rubber tired undercarriage, independently operated material augers, and a hydraulically extendible screed with a basic paving width of 8' which provides infinitely variable paving widths from 8' to a maximum of no less than 12' and, by using cutoff shoes or ditch plates, can be used for paving widths from 4' to a maximum of no less than 80". Shall have the capacity to lay a mat up to a maximum thickness of no less than 6".
2. **Wheels & Tires:** Four (4) sets of bogie mounted or walking beam mounted pneumatic rubber tires (8 total tires). Tires shall be either 5.30 x 6 or 5.30 x 4.50, minimum 6 ply rating. Solid rubber tires on iron wheels may be used in lieu of pneumatic tires. Wheels shall be a minimum of 12" OD x 5" width. Mounting shall provide for optimum weight distribution.
3. **Operator's Station:** Shall have a minimum of one (1) control station, allowing for the control of the engine(s), material augers, material flow gates, screed extensions and other paver functions.
4. **Engine(s):** Shall have either one (1) or two (2) propane fueled engines. If a single engine is furnished, it shall develop a minimum of 20 horsepower at rated RPM. If two engines are furnished, each engine shall develop a minimum of 10 horsepower at rated RPM. Shall be equipped with 12 volt electrical system and include electric hour meter, starter(s), alternator(s) and one or more batteries. Muffler(s) and exhaust shall be equipped with heat shields and/or routed to provide operator protection. Engine(s) may be air or liquid cooled. If liquid cooled, cooling system shall have anti-freeze protection to -20° F, or lower.
5. **Fuel Tank(s):** A minimum of two (2) propane tanks of no less than 40 pounds capacity each shall be furnished. Shall provide fuel to operate engine(s) and for operating screed heating system. A lockable rack shall be provided on the machine to secure at least one (1) propane tank.
6. **Hydraulic System:** Hydraulic oil flow for all hydraulic functions shall be furnished by multiple hydraulic pumps or a single hydraulic pump with multiple pumping sections. Pump(s) shall be driven by engine(s) specified above and be of sufficient volume and pressure to operate the augers, screed extensions, material flow gate(s), screed lift, truck hitch, etc. The hydraulic system shall be configured to allow multiple hydraulic operations simultaneously. Shall have necessary filters, relief valves and reservoir with adequate capacity for system furnished.
7. **Back-Up Hydraulic System:** A hand operated type hydraulic pump that will operate all cylinder functions shall be provided to act as a back-up in the event of a primary hydraulic system failure.
8. **Hopper:** Shall have a minimum capacity of three (3) tons. Shall be self-cleaning with sloping design to funnel the material to the screed.
9. **Material Shut-Off Gate(s):** The hopper shall be equipped with hydraulically adjustable shut-off gate(s) for metering material delivery to the screed. Gate(s) shall be capable of completely closing and shutting off material flow to the screed.
10. **Truck Hitch:** Front of hopper shall be equipped with a hydraulic truck hitch controllable from the paver operator's station. The hitch tow arms shall be adjustable with a minimum of three (3) positions. Hitch rollers shall engage the truck wheel rims to quickly grip and secure a truck in proper attitude for unloading material into the hopper. The hitch rollers shall have a minimum of two (2) positions, pin set, to allow quick change from a twin screw dump truck to a single screw dump truck. The pin set positions shall have a minimum 3" of separation.
11. **Screed:** Shall be hydraulically extendible, consisting of a main screed section with independent, hydraulically extendible screed sections on each end of main screed. Basic screed width shall be 8' with infinitely variable telescoping width capability up to no less than 12'. Wear plates for both the main screed and the extendible screed sections shall be bolt-on constructed of minimum 1/4" thick 450 Brinell hardness abrasion resistant alloy steel. Main screed shall have adjustable crown control with maximum adjustment of no less than 2" negative to 2" positive. Screed shall have mat thickness controls allowing for mat thickness from 0" to a maximum of no less than 6" deep. Shall be equipped with an operator's catwalk.
  - A. **Screed Heat:** Screed shall be heated by a minimum of two (2) propane fired burners. Burner system shall be complete with all necessary hose, regulators, valves and fittings.
  - B. **Screed Lift:** The paver shall be equipped with a minimum of one (1) hydraulic cylinder for raising the screed.
  - C. **Cut-Off Shoes:** Shall be furnished for paving of less than 8' width.

12. Augers: The paver shall be equipped with two (2) independently operated augers. Each auger shall have a minimum diameter of 8" and be independently driven by a hydraulic motor.
13. Vandalism Protection: Shall be equipped with vandalism protection including the following items as a minimum:
  - Lockable fuel tank rack(s).
  - Lockable battery box cover. Battery located behind locking panels or inside an enclosure is acceptable in lieu of a locking cover.
  - Lockable filler cap for the hydraulic reservoir. Filler cap located behind locking panels or inside a lockable enclosure are acceptable in lieu of a locking cap.
14. Transport Chains: Shall be equipped with transport chains for transporting the machine on the back of a 6 CY or 10 CY dump truck.
15. Weight: Paver equipped with hydraulically extendible screed shall have a minimum weight of 3,500 pounds.
16. Color: Manufacturer's standard color is acceptable.
17. Warranty: Units purchased under this specification shall be warranted against defects in material and workmanship for a minimum period of twelve (12) months (365 days) from date unit is placed in operation by AHTD.
  - A. Warranty shall include all parts, labor and transportation costs to the location of equipment.
  - B. If equipment cannot be repaired on location, warranty shall include cost of transport to the facility where the repair work will be done.
  - C. It will be the responsibility of the successful bidder to insure that repairs are completed in a timely manner.
  - D. Recent prior failure to provide warranty-work, parts, replacement parts or service, in a timely manner, for equipment from the same manufacturer or dealer shall be grounds for the rejection of any submitted bid, or for the denial of any otherwise qualified low bidder, whether such failure is attributable to the manufacturer or the dealer of the equipment. For the purposes of this paragraph "timely manner" means a period of time not exceeding thirty (30) calendar days to provide requested warranty-work, parts, replacement parts, or service. For the purposes of this paragraph "manufacturer" means the original manufacturer of the equipment and its successor or successors, regardless of number, and whether acquired by sale, merger, or otherwise. For the purposes of this paragraph "replacement part" means a part redesigned by a manufacturer to correct a design or engineering defect and which replacement part is capable of providing dependable performance in normal operation conditions for its normal service life without failure. Such bid or bids may be rejected by the Department until such failure or failures have been remedied to the satisfaction of the Department and until such manufacturer or dealer is providing such warranty-work, parts, replacement parts, and service in a timely manner.