


ARKANSAS DEPARTMENT OF TRANSPORTATION  
CONSTRUCTION PLANS FOR STATE HIGHWAY

DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. RD. DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.			
				JOB NO.	100878		1	45
				② HWY. 49/HWY. 34 INTERS. IMPVTS. (MARMADUKE) (S)				



VICINITY MAP

HWY. 49 / HWY. 34  
INTERS. IMPVTS. (MARMADUKE) (S)

GREENE COUNTY

ROUTE 49 SECTION 2  
ROUTE 34 SECTION 4



JOB 100878

FED. AID PROJ. STPR-0028(46)

STA. 201+17.21  
BEGIN JOB 100878  
LOG MILE 5.40

STA. 207+83.55  
END JOB 100878

NOT TO SCALE



ARK. HWY. DIST. NO. 10

DESIGN TRAFFIC DATA

DESIGN YEAR	2040
2020 ADT	5300
2040 ADT	6400
2040 DHV	704
DIRECTIONAL DISTRIBUTION	0.60
TRUCKS	5%
DESIGN SPEED	20 MPH



APPROVED



*M.E. Banks*  
Banks, Emanuel  
Aug 26 2020 9:52 AM

DEPUTY DIRECTOR  
AND CHIEF ENGINEER

	BEGIN PROJECT	MID-POINT OF PROJECT	END PROJECT
LATITUDE	N 36°11'10"	N 36°11'13"	N 36°11'16"
LONGITUDE	W 90°23'06"	W 90°23'06"	W 90°23'06"

LENGTH OF PROJECT CALCULATED ALONG C.L.			
GROSS LENGTH OF PROJECT	666.34	FEET	OR 0.126 MILES
NET ROADWAY	666.34		0.126 MILES
NET BRIDGES	0.00		0.000 MILES
NET PROJECT	666.34		0.126 MILES

DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. RD. DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
09-22-20		10-29-20		6	ARK.			
09-28-20								
10-08-20						JOB NO. 100878	2	45

**INDEX OF SHEETS**

SHEET NO.	TITLE
1	TITLE SHEET
2	INDEX OF SHEETS, STANDARD DRAWINGS, GOVERNING SPECIFICATIONS, AND GENERAL NOTES
3	TYPICAL SECTIONS OF IMPROVEMENT
4 - 6	SPECIAL DETAILS
7 - 10	TEMPORARY EROSION CONTROL DETAILS
11 - 15	MAINTENANCE OF TRAFFIC DETAILS
16	PERMANENT PAVEMENT MARKING DETAILS
17 - 21	QUANTITIES
22	SUMMARY OF QUANTITIES AND REVISIONS
23	SURVEY CONTROL DETAILS
24 - 25	PLAN AND PROFILE SHEETS
26	ILLUMINATION NOTES AND QUANTITIES
27	ILLUMINATION TABLES
28	ILLUMINATION LAYOUT
29 - 30	ILLUMINATION DETAILS
31 - 45	CROSS SECTIONS

NOTE: CROSS SECTIONS NOT NORMALLY INCLUDED IN PLANS SOLD TO PROSPECTIVE BIDDERS, BUT MAY BE HAD UPON REQUEST.

**GENERAL NOTES**

- GRADE LINE DENOTES FINISHED GRADE WHERE SHOWN ON PLANS.
- ALL PIPE LINES, POWER, TELEPHONE, AND TELEGRAPH LINES TO BE MOVED OR LOWERED BY THE RESPECTIVE OWNERS AS PER AGREEMENT WITH SUCH OWNERS.
- ANY EQUIPMENT OR APPURTENANCE THAT INTERFERES WITH THE PROPOSED CONSTRUCTION AND WHICH MAY BE THE PROPERTY OF UTILITY SERVICE ORGANIZATIONS SHALL BE MOVED BY THE OWNERS UNLESS OTHERWISE PROVIDED.
- THE CONTRACTOR SHALL BE RESPONSIBLE FOR MAINTAINING U. S. MAILBOXES WITHIN THE PROJECT LIMITS IN SUCH A MANNER THAT THE PUBLIC MAY RECEIVE CONTINUED MAIL SERVICE. PAYMENT WILL BE CONSIDERED INCLUDED IN THE PRICE BID FOR THE VARIOUS BID ITEMS.
- ALL LAND MONUMENTS LOCATED WITHIN THE CONSTRUCTION AREA SHALL BE PROTECTED IN ACCORDANCE WITH SECTION 107.12 OF THE STANDARD SPECIFICATIONS.
- ALL TREES THAT DO NOT DIRECTLY INTERFERE WITH THE PROPOSED CONSTRUCTION SHALL BE SPARED AS DIRECTED BY THE ENGINEER. CARE AND DISCRETION SHALL BE USED TO ENSURE THAT ALL TREES NOT TO BE REMOVED SHALL BE HARMED AS LITTLE AS POSSIBLE DURING THE CONSTRUCTION OPERATIONS.
- THE CONTRACTOR SHALL BE RESPONSIBLE FOR PROVIDING A FENCE TO CONTROL LIVESTOCK IN AREAS WHERE PASTURES ARE SEVERED. WIRE FENCE MAY BE CONSTRUCTED INITIALLY, OR IN LIEU THEREOF, THE CONTRACTOR AT HIS OWN EXPENSE, MAY ELECT TO PROVIDE TEMPORARY FENCING SUITABLE TO CONTAIN LIVESTOCK.
- THE SEQUENCE AS SHOWN ON THE MAINTENANCE OF TRAFFIC PLANS IS A GENERAL OUTLINE FOR THE CONSTRUCTION OF THIS PROJECT, AND IN NO WAY IS IT INTENDED TO COVER EVERY ITEM IN THE PROJECT. ITEMS NOT CRITICAL TO THE CONSTRUCTION SEQUENCE MAY BE CONSTRUCTED IN ANY STAGE AS APPROVED BY THE RESIDENT ENGINEER.
- ALL FLEXIBLE BASE AND ASPHALTIC PAVEMENTS REMOVED SHALL BE PAID FOR UNDER THE ITEM NO. 210 - UNCLASSIFIED EXCAVATION.
- THE EXISTING ASPHALT PAVEMENT TO BE REMOVED FROM THE REMAINING PAVEMENT SHALL BE SEPARATED BY SAWING ALONG A NEAT LINE. AFTER SAWING, THE PAVEMENT TO BE REMOVED SHALL BE CAREFULLY REMOVED IN A MANNER THAT WILL NOT DAMAGE THE PAVEMENT THAT IS TO REMAIN. ANY DAMAGE OF THE ASPHALT PAVEMENT THAT IS TO REMAIN IN PLACE SHALL BE REPAIRED AT THE CONTRACTOR'S EXPENSE.

**ROADWAY STANDARD DRAWINGS**

DRWG. NO.	TITLE	DATE
CG-1	CURBING DETAILS	11-29-07
CPTJ-6A	TRANSVERSE & LONGITUDINAL JOINTS FOR CONCRETE PAVEMENT (NON-REINFORCED)	11-07-19
DR-1	DETAILS OF DRIVEWAYS & ISLANDS	11-07-19
FES-1	FLARED END SECTION	10-18-96
FES-2	FLARED END SECTION	10-18-96
FPC-9	DETAILS OF DROP INLETS & JUNCTION BOXES	11-16-01
FPC-9E	DETAILS OF DROP INLETS (TYPE C)	08-22-02
FPC-9M	DETAILS OF DROP INLET (TYPE MO)	08-22-02
PCC-1	CONCRETE PIPE CULVERT FILL HEIGHTS & BEDDING	02-27-14
PCM-1	METAL PIPE CULVERT FILL HEIGHTS & BEDDING	02-27-14
PM-1	PAVEMENT MARKING DETAILS	02-27-20
PU-1	DETAILS OF PIPE UNDERDRAIN	12-08-16
SD-6	HEAVY DUTY PULL BOX	11-16-17
SI-1	DETAILS OF SPECIAL ITEMS	10-25-18
TC-1	STANDARD TRAFFIC CONTROLS FOR HIGHWAY CONSTRUCTION	11-07-19
TC-2	STANDARD TRAFFIC CONTROLS FOR HIGHWAY CONSTRUCTION	11-07-19
TC-3	STANDARD TRAFFIC CONTROLS FOR HIGHWAY CONSTRUCTION	02-27-20
TEC-1	TEMPORARY EROSION CONTROL DEVICES	11-16-17
TEC-3	TEMPORARY EROSION CONTROL DEVICES	11-03-94
WF-3	CHAIN LINK FENCE	11-17-10
WR-1	WHEELCHAIR RAMPS NEW CONSTRUCTION AND ALTERATIONS	11-10-05

**GOVERNING SPECIFICATIONS**

ARKANSAS STATE HIGHWAY COMMISSION STANDARD SPECIFICATIONS FOR HIGHWAY CONSTRUCTION, EDITION OF 2014, AND THE FOLLOWING SPECIAL PROVISIONS AND SUPPLEMENTAL SPECIFICATIONS:

NUMBER	TITLE
ERRATA	ERRATA FOR THE BOOK OF STANDARD SPECIFICATIONS
FHWA-1273	REQUIRED CONTRACT PROVISIONS FEDERAL-AID CONSTRUCTION CONTRACTS
FHWA-1273	SUPPLEMENT - EQUAL EMPLOYMENT OPPORTUNITY - NOTICE TO CONTRACTORS
FHWA-1273	SUPPLEMENT - SPECIFIC EQUAL EMPLOYMENT OPPORTUNITY RESPONSIBILITIES (23 U.S.C. 140)
FHWA-1273	SUPPLEMENT - EQUAL EMPLOYMENT OPPORTUNITY - GOALS AND TIMETABLES
FHWA-1273	SUPPLEMENT - EQUAL EMPLOYMENT OPPORTUNITY - FEDERAL STANDARDS
FHWA-1273	SUPPLEMENT - POSTERS AND NOTICES REQUIRED FOR FEDERAL-AID PROJECTS
FHWA-1273	SUPPLEMENT - WAGE RATE DETERMINATION
100-3	CONTRACTOR'S LICENSE
100-4	DEPARTMENT NAME CHANGE
102-2	ISSUANCE OF PROPOSALS
108-1	LIQUIDATED DAMAGES
108-2	WORK ALLOWED PRIOR TO ISSUANCE OF WORK ORDER
210-1	UNCLASSIFIED EXCAVATION
303-1	AGGREGATE BASE COURSE
306-1	QUALITY CONTROL AND ACCEPTANCE
400-1	TACK COATS
400-4	DESIGN AND QUALITY CONTROL OF ASPHALT MIXTURES
400-5	PERCENT AIR VOIDS FOR ACHM MIX DESIGNS
400-6	LIQUID ANTI-STRIP ADDITIVE
400-7	TRACKLESS TACK
404-3	DESIGN OF ASPHALT MIXTURES
410-1	CONSTRUCTION REQUIREMENTS AND ACCEPTANCE OF ASPHALT CONCRETE PLANT MIX COURSES
410-2	DEVICES FOR MEASURING DENSITY FOR ROLLING PATTERNS
502-1	WELDED WIRE REINFORCEMENT
505-1	PORTLAND CEMENT CONCRETE DRIVEWAY
600-2	INCIDENTAL CONSTRUCTION
603-1	LANE CLOSURE NOTIFICATION
604-1	RETROREFLECTIVE SHEETING FOR TRAFFIC CONTROL DEVICES IN CONSTRUCTION ZONES
604-3	TRAFFIC CONTROL DEVICES IN CONSTRUCTION ZONES (MASH)
606-1	PIPE CULVERTS FOR SIDE DRAINS
620-1	MULCH COVER
621-1	FILTER SOCKS
632-1	CONCRETE ISLAND
633-1	CONCRETE WALKS, CONCRETE STEPS, AND HAND RAILING
634-1	CURBING
JOB 100878	BIDDING REQUIREMENTS AND CONDITIONS
JOB 100878	BROADBAND INTERNET SERVICE FOR ASPHALT CONCRETE PLANT
JOB 100878	BROADBAND INTERNET SERVICE FOR FIELD OFFICE
JOB 100878	CARGO PREFERENCE ACT REQUIREMENTS
JOB 100878	CLASS C FLY ASH IN PORTLAND CEMENT CONCRETE PAVEMENT AND CLASS S(AE) CONCRETE
JOB 100878	DELAY IN RIGHT OF WAY OCCUPANCY
JOB 100878	DISADVANTAGED BUSINESS ENTERPRISE BIDDER'S RESPONSIBILITIES
JOB 100878	ELECTRICAL CONDUCTORS-IN-CONDUIT
JOB 100878	EXTENSION FOR PIPE CULVERTS
JOB 100878	FLEXIBLE BEGINNING OF WORK - CALENDAR DAY CONTRACT
JOB 100878	GOALS FOR DISADVANTAGED BUSINESS ENTERPRISE PARTICIPATION
JOB 100878	LED ROADWAY ILLUMINATION POLE
JOB 100878	MANDATORY ELECTRONIC CONTRACT
JOB 100878	MANDATORY ELECTRONIC DOCUMENT SUBMITTAL
JOB 100878	PRICE ADJUSTMENT FOR ASPHALT BINDER
JOB 100878	PROHIBITION OF CERTAIN TELECOMMUNICATIONS AND VIDEO SURVEILLANCE SERVICES OR EQUIPMENT
JOB 100878	SERVICE POINT ASSEMBLY
JOB 100878	SHORING FOR CULVERTS
JOB 100878	SITE USE (A+C METHOD) - CALENDAR DAY CONTRACT
JOB 100878	SOIL STABILIZATION
JOB 100878	STAINING CONCRETE SURFACES
JOB 100878	SUBMISSION OF ASPHALT CONCRETE HOT MIX ACCEPTANCE TEST RESULTS
JOB 100878	THERMOPLASTIC PAVEMENT MARKING (YIELD LINE)
JOB 100878	UTILITY ADJUSTMENTS
JOB 100878	VERY EARLY STRENGTH CONCRETE
JOB 100878	WARM MIX ASPHALT
JOB 100878	WELLHEAD PROTECTION



Oct 29 2020 11:25 AM  
DocuSign

2 INDEX OF SHEETS, STANDARD DRAWINGS, GOVERNING SPECS., AND GENERAL NOTES

**INDEX OF SHEETS, STANDARD DRAWINGS, GOVERNING SPECIFICATIONS, AND GENERAL NOTES**


8/19/2020 R100878.DGN

DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. RD. DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.			
				JOB NO.	100878		3	45

2 TYPICAL SECTIONS OF IMPROVEMENT



Aug 21 2020 11:00 AM



C.C.C.&G. SECTION (HWY. 49 & HWY. 34)  
 STA. 101+07.27 TO STA. 104+04.75  
 STA. 104+95.25 TO STA. 107+90.88  
 STA. 201+17.21 TO STA. 204+06.85  
 STA. 204+93.15 TO STA. 207+83.55

• TO BE USED IF AND WHERE DIRECTED BY THE ENGINEER

NOTES:


REFER TO CROSS SECTIONS FOR DEVIATION FROM THE NORMAL SLOPES. NO CHANGES SHALL BE MADE FROM THE PLANNED SLOPES WITHOUT THE APPROVAL OF THE ENGINEER.

ASPHALT FOR LEVELING OF EXISTING PAVEMENT SHALL BE PLACED ONLY IF AND WHERE DIRECTED BY THE ENGINEER. CALCULATIONS FOR THE AMOUNT OF LEVELING AND/OR LEVELING OPERATIONS SHALL BE PERFORMED BEFORE CONSTRUCTING NOTCH AND WIDENING. CALCULATIONS WILL NOT BE PAID FOR DIRECTLY BUT PAYMENT WILL BE CONSIDERED INCLUDED IN THE VARIOUS PAY ITEMS.

THE FINAL 2" OF SURFACE COURSE IS TO BE PLACED AFTER ALL OTHER COURSES HAVE BEEN LAID. LONGITUDINAL JOINTS SHALL BE AT LANE LINES.

PRIOR TO AND DURING PLACEMENT OF PAVEMENT IN FRONT OF THE CURB AND GUTTER, THE CONTRACTOR SHALL PROVIDE POSITIVE DRAINAGE AT ALL TIMES. THE METHOD(S) USED SHALL BE APPROVED BY THE ENGINEER. PAYMENT FOR THIS WORK SHALL BE CONSIDERED INCLUDED IN THE PRICE BID FOR THE VARIOUS CONTRACT ITEMS.

THE EXISTING ASPHALT PAVEMENT TO BE REMOVED FROM THE REMAINING PAVEMENT SHALL BE SEPARATED BY SAWING ALONG A NEAT LINE. AFTER SAWING, THE PAVEMENT TO BE REMOVED SHALL BE CAREFULLY REMOVED IN A MANNER THAT WILL NOT DAMAGE THE PAVEMENT THAT IS TO REMAIN. ANY DAMAGE OF THE ASPHALT PAVEMENT THAT IS TO REMAIN IN PLACE SHALL BE REPAIRED AT THE CONTRACTOR'S EXPENSE.




C.C.C.&G. SECTION (ROUNDAABOUT)  
 STA. 0+00.00 TO STA. 2+82.74


• TO BE USED IF AND WHERE DIRECTED BY THE ENGINEER

DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. RD. DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.			
				JOB NO.	I00878		4	45


② SPECIAL DETAILS



Aug 21 2020 11:00 AM  
DocuSign




DETAIL FOR TRANSITIONS




TOP VIEW

MIN 3" COVER




FRONT VIEW



SIDE VIEW

PIPE EXTENSION  
REINFORCED CONCRETE COLLAR DETAIL




NOTE:  
PAVEMENT STRUCTURE FOR STATE HIGHWAYS, CITY STREETS,  
& COUNTY ROADS TO BE SAME AS MAIN LANES.


DETAIL OF TURNOUTS, ASPHALT STREETS,  
COUNTY ROADS & STATE HIGHWAYS  
CURB & GUTTER SECTION

DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. RD. DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.		5	45
				JOB NO.		100878		

2 SPECIAL DETAILS



Aug 21 2020 11:00 AM  
DocuSign




6" X 12" MESH FABRIC (TYPE 3) (W5.5 X W2.9) = 4.26 LBS./SQ. YD.


NOTES:

- LAP MESH FABRIC MIN. 12" LONGITUDINALLY AND MIN. 6" TRANSVERSELY.
- MESH FABRIC IS NOT REQUIRED WHEN WIDTH OF PORTLAND CEMENT CONCRETE BASE IS LESS THAN 12".
- MESH FABRIC (TYPE 3) WILL NOT BE PAID FOR DIRECTLY, BUT FULL COMPENSATION THEREFORE WILL BE CONSIDERED INCLUDED IN THE CONTRACT PRICE BID PER SQ. YD. FOR PORTLAND CEMENT CONCRETE BASE


DETAIL OF REINFORCING STEEL FOR PAVEMENT (MESH FABRIC TYPE 3)



TEMPORARY PAVEMENT DETAIL PLAN VIEW



TEMPORARY PAVEMENT DETAIL CROSS SECTION VIEW




P.C.C. BASE WIDENING DETAIL


P.C.C. BASE WIDENING TO BE USED IF AND WHERE DIRECTED BY THE ENGINEER.

DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. RD. DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.			
				JOB NO.		100878	6	45


② SPECIAL DETAILS



Aug 21 2020 11:01 AM  
DocuSign




CENTRAL CONCRETE ISLAND DETAIL



FACE SHALL MEET REQUIREMENTS OF TYPE B CURB

NOTE: CONCRETE WALK THROUGH ISLAND SHALL BE POURED MONOLITHICALLY. ALL MATERIALS REQUIRED TO CONSTRUCT CONCRETE WALK THRU ISLAND SHALL BE INCLUDED IN THE PRICE BID FOR CONCRETE ISLAND.

CONCRETE WALK THROUGH ISLAND DETAIL



2/3/2020  
R100878.DGN

DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. RD. DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.		7	45
				JOB NO.	100878			

② TEMPORARY EROSION CONTROL DETAILS



Aug 21 2020 11:01 AM

**LEGEND**  
 (E-II) = SILT FENCE

STA. 101+07.27  
 BEGIN HWY. 34  
 LOG MILE 7.29

STA. 207+83.55  
 END HWY. 49  
 END JOB 100878


STA. 201+17.21  
 BEGIN JOB 100878  
 BEGIN HWY. 49  
 LOG MILE 5.40

STA. 107+90.88  
 END HWY. 34

**REVISIONS**


DATE OF REVISION	REVISION

2/3/2020  
R100878.DGN



DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. RD. DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.		8	45
				JOB NO.	100878			

② TEMPORARY EROSION CONTROL DETAILS



Aug 21 2020 11:01 AM

DocuSign

**LEGEND**

(E-11)	= SILT FENCE
(E-13)	= FILTER SOCK

STA. 101+07.27  
BEGIN HWY. 34  
LOG MILE 7.29

STA. 207+83.55  
END HWY. 49  
END JOB 100878


STA. 201+17.21  
BEGIN JOB 100878  
BEGIN HWY. 49  
LOG MILE 5.40

STA. 107+90.88  
END HWY. 34

**REVISIONS**

DATE OF REVISION	REVISION

2/3/2020  
R100878.DGN





DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. RD. DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.		9	45
				JOB NO.		100878		

② TEMPORARY EROSION CONTROL DETAILS



Aug 21 2020 11:01 AM  
DocuSign

**LEGEND**

(E-11)	= SILT FENCE
(E-13)	= FILTER SOCK

STA. 101+07.27  
BEGIN HWY. 34  
LOG MILE 7.29

STA. 207+83.55  
END HWY. 49  
END JOB 100878


STA. 201+17.21  
BEGIN JOB 100878  
BEGIN HWY. 49  
LOG MILE 5.40

STA. 107+90.88  
END HWY. 34

**REVISIONS**

DATE OF REVISION	REVISION

2/3/2020  
R100878.DGN



DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. RD. DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.		10	45
				JOB NO.		100878		

② TEMPORARY EROSION CONTROL DETAILS



Aug 21 2020 11:02 AM  
DocuSign

**LEGEND**

(E-11)	= SILT FENCE
(E-13)	= FILTER SOCK

STA. 101+07.27  
BEGIN HWY. 34  
LOG MILE 7.29

STA. 207+83.55  
END HWY. 49  
END JOB 100878


STA. 201+17.21  
BEGIN JOB 100878  
BEGIN HWY. 49  
LOG MILE 5.40

STA. 107+90.88  
END HWY. 34

**REVISIONS**

DATE OF REVISION	REVISION

2/3/2020  
R100878.DGN




DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. RD. DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.			
				JOB NO.		I00878	11	45

② MAINTENANCE OF TRAFFIC DETAILS




Aug 21 2020 11:02 AM

DocuSign




ADVANCE WARNING (ALL STAGES)



DRIVEWAY/TRAFFIC CONE DETAIL

- (4) W8-1 (30" x 30")  
ALL STAGES TO BE USED IF AND WHERE DIRECTED BY THE ENGINEER
- (4) W21-5a (36" x 36")  
ALL STAGES TO BE USED IF AND WHERE DIRECTED BY THE ENGINEER




ADVANCE WARNING - SIDE ROADS (ALL STAGES)

- STA. 101+00 LT. & RT., 4TH ST.
- STA. 108+00 LT. & RT., 2ND ST.
- STA. 201+00 LT. & RT., MAIN ST.
- STA. 208+00 LT. & RT., MILL ST.

DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. RD. DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.		12	45
				JOB NO.	100878			

② MAINTENANCE OF TRAFFIC DETAILS



Aug 21 2020 11:02 AM



(4) RI-1  
(30" x 30")

TO BE USED AS SHOWN IN THE STAGE 1 MAINTENANCE OF TRAFFIC DETAIL

STA. 101+07.27  
BEGIN HWY. 34  
LOG MILE 7.29

STA. 207+83.55  
END HWY. 49  
END JOB 100878

STA. 201+17.21  
BEGIN JOB 100878  
BEGIN HWY. 49  
LOG MILE 5.40

STA. 107+90.88  
END HWY. 34

STAGE 1 CONSTRUCTION SEQUENCE:


- INSTALL ADVANCE WARNING SIGNS AND END ROAD WORK SIGNS AT THE END OF JOB AS SHOWN ON THE ADVANCE WARNING DETAIL.
- APPLY LEVELING COURSE TO EXISTING LANES IF AND WHERE DIRECTED BY THE ENGINEER.
- INSTALL CONSTRUCTION PAVEMENT MARKINGS AND STOP SIGNS AS SHOWN IN THE STAGE 1 MAINTENANCE OF TRAFFIC DETAILS.
- USE VERTICAL PANELS SPACED 20' O.C. TO DELINEATE THE WORK ZONE. USE TRAFFIC CONES TO DELINEATE DRIVEWAYS.
- NOTCH AND WIDEN THE NORTHWEST AND SOUTHEAST QUADRANTS AS SHOWN IN THE STAGE 1 MAINTENANCE OF TRAFFIC DETAILS.

STAGE 1 QUANTITIES

- SIGNS = 374.0 SQ. FT.
- VERTICAL PANELS = 48 EACH
- TRAFFIC CONES = 61 EACH
- CONSTRUCTION PAVEMENT MARKINGS = 5770 LIN. FT.


2/3/2020  
R100878.DGN

STAGE 1  
MAINTENANCE OF TRAFFIC DETAILS



DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. RD. DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.		13	45
				JOB NO.		100878		

② MAINTENANCE OF TRAFFIC DETAILS



Aug 21 2020 11:02 AM



(4) RI-1  
(30" x 30")  
TO BE USED AS SHOWN IN THE STAGE 2 MAINTENANCE OF TRAFFIC DETAIL

STA. 101+07.27  
BEGIN HWY. 34  
LOG MILE 7.29

STA. 207+83.55  
END HWY. 49  
END JOB 100878

STA. 201+17.21  
BEGIN JOB 100878  
BEGIN HWY. 49  
LOG MILE 5.40

STA. 107+90.88  
END HWY. 34

STAGE 2 CONSTRUCTION SEQUENCE:


- REMOVE CONSTRUCTION PAVEMENT MARKINGS ALONG HWY. 34 FROM STA. 102+44.55 TO STA. 106+77.45
- INSTALL CONSTRUCTION PAVEMENT MARKINGS AND STOP SIGNS AS SHOWN IN THE STAGE 2 MAINTENANCE OF TRAFFIC DETAILS.
- USE VERTICAL PANELS SPACED 20' O.C. TO DELINEATE THE WORK ZONE. USE TRAFFIC CONES TO DELINEATE DRIVEWAYS.
- NOTCH AND WIDEN THE NORTHEAST AND SOUTHWEST QUADRANTS AS SHOWN IN THE STAGE 2 MAINTENANCE OF TRAFFIC DETAILS.

STAGE 2 QUANTITIES

- SIGNS = 374.0 SQ. FT.
- VERTICAL PANELS = 41 EACH
- TRAFFIC CONES = 54 EACH
- CONSTRUCTION PAVEMENT MARKINGS = 1609 LIN. FT.
- REMOVAL OF CONSTRUCTION PAVEMENT MARKINGS = 1355 LIN. FT.

2/3/2020  
R100878.DGN

STAGE 2  
MAINTENANCE OF TRAFFIC DETAILS



DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. RD. DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.		14	45
				JOB NO.	100878			

② MAINTENANCE OF TRAFFIC DETAILS



Aug 21 2020 11:03 AM



(4) RI-1  
(30" x 30")  
TO BE USED AS SHOWN IN THE STAGE 3 MAINTENANCE OF TRAFFIC DETAIL

STA. 101+07.27  
BEGIN HWY. 34  
LOG MILE 7.29

STA. 207+83.55  
END HWY. 49  
END JOB 100878

STA. 201+17.21  
BEGIN JOB 100878  
BEGIN HWY. 49  
LOG MILE 5.40


STA. 107+90.88  
END HWY. 34

STAGE 3 CONSTRUCTION SEQUENCE:  
REMOVE/INSTALL CONSTRUCTION PAVEMENT MARKINGS AND STOP SIGNS AS SHOWN IN STAGE 3 MAINTENANCE OF TRAFFIC DETAILS.  
USE TRAFFIC CONES TO DELINEATE THE CENTRAL ISLAND. CONSTRUCT THE CENTRAL ISLAND.  
AFTER CENTRAL ISLAND HAS CURED, REMOVE TRAFFIC CONES AND USE TRAFFIC CONES TO DELINEATE THE APPROACH ISLANDS. CONSTRUCT THE APPROACH ISLANDS.

STAGE 3 QUANTITIES  
SIGNS = 374.0 SQ. FT.  
TRAFFIC CONES = 25 EACH  
CONSTRUCTION PAVEMENT MARKINGS = 1368 LIN. FT.  
REMOVAL OF CONSTRUCTION PAVEMENT MARKINGS = 3565 LIN. FT.


2/3/2020  
R100878.DGN

STAGE 3  
MAINTENANCE OF TRAFFIC DETAILS




DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. RD. DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.		15	45
				JOB NO.	100878			

② MAINTENANCE OF TRAFFIC DETAILS



Aug 21 2020 11:03 AM



STAGE 4 CONSTRUCTION SEQUENCE:

- REMOVE/INSTALL CONSTRUCTION PAVEMENT MARKINGS AS SHOWN IN STAGE 4 MAINTENANCE OF TRAFFIC DETAILS.
- USE VERTICAL PANELS SPACED 20' O.C. TO DELINEATE THE WORK ZONE. USE TRAFFIC CONES TO DELINEATE DRIVEWAYS.
- NOTCH TEMPORARY PAVEMENT AND CONSTRUCT REMAINDER OF THE PROPOSED INTERSECTION AS SHOWN IN THE STAGE 4 MAINTENANCE OF TRAFFIC DETAILS.
- APPLY FINAL 2" LIFT OF ACHM SURFACE COURSE AND INSTALL PERMANENT PAVEMENT MARKINGS AS SHOWN IN THE PERMANENT PAVEMENT MARKING DETAILS.

STAGE 4 QUANTITIES

- SIGNS = 349.0 SQ. FT.
- VERTICAL PANELS = 29 EACH
- TRAFFIC CONES = 18 EACH
- CONSTRUCTION PAVEMENT MARKINGS = 597 LIN. FT.
- REMOVAL OF CONSTRUCTION PAVEMENT MARKINGS = 62 LIN. FT.

STAGE 4 MAINTENANCE OF TRAFFIC DETAILS




2/3/2020 R100878.DGN

PERMANENT PAVEMENT MARKINGS

RAISED PAVEMENT MARKERS TYPE 11 (YEL/YEL) (80' O.C.) = 21 EACH  
 THERMOPLASTIC PAVEMENT MARKING WHITE (6") = 1333 LIN. FT.  
 THERMOPLASTIC PAVEMENT MARKING WHITE (8") = 37 LIN. FT.  
 THERMOPLASTIC PAVEMENT MARKING WHITE (12") = 320 LIN. FT.  
 THERMOPLASTIC PAVEMENT MARKING YELLOW (6") = 2311 LIN. FT.  
 THERMOPLASTIC PAVEMENT MARKING YELLOW (8") = 362 LIN. FT.  
 THERMOPLASTIC PAVEMENT MARKING (YIELD LINE) = 52 LIN. FT.

DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. RD. DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.		16	45
				JOB NO.		100878		

2 PERMANENT PAVEMENT MARKING DETAILS



APPROACH STRIPING DETAIL


PERMANENT PAVEMENT MARKING DETAILS

2/3/2020 R100878.DGN



DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. RD. DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.		17	45
				JOB NO.	I00878		17	45

② QUANTITIES



Aug 21 2020 11:03 AM  
DocuSign

**ADVANCE WARNING SIGNS AND DEVICES**

SIGN NUMBER	DESCRIPTION	SIGN SIZE	STAGE 1	STAGE 2	STAGE 3	STAGE 4	MAXIMUM NUMBER REQUIRED	TOTAL SIGNS REQUIRED		VERTICAL PANELS	TRAFFIC CONE
								NO.	SQ. FT.		
			LIN. FT. - EACH							EACH	
W20-1	ROAD WORK 1500 FT.	48"x48"	4	4	4	4	4	4	64.0		
W20-1	ROAD WORK 1000 FT.	48"x48"	4	4	4	4	4	4	64.0		
W20-1	ROAD WORK 500 FT.	48"x48"	4	4	4	4	4	4	64.0		
W20-1	ROAD WORK AHEAD	48"x48"	4	4	4	4	4	4	64.0		
G20-2	END ROAD WORK	48"x24"	4	4	4	4	4	4	32.0		
R1-1	STOP	30"x30"	4	4	4	4	4	4	25.0		
W21-5a	RIGHT SHOULDER CLOSED	36"x36"	4	4	4	4	4	4	36.0		
W8-1	BUMP	30"x30"	4	4	4	4	4	4	25.0		
VERTICAL PANELS			48	41		29	48			48	
TRAFFIC CONES			61	54	25	18	61				61
<b>TOTALS:</b>								374.0		48	61

NOTE: THIS IS A HIGH TRAFFIC VOLUME ROAD AS DEFINED IN SECTION 604.03, STANDARD SPECIFICATIONS FOR HIGHWAY CONSTRUCTION.

**CONSTRUCTION PAVEMENT MARKINGS AND PERMANENT PAVEMENT MARKINGS**

DESCRIPTION	STAGE 1	STAGE 2	STAGE 3	STAGE 4	END OF JOB	CONSTRUCTION PAVEMENT MARKINGS	REMOVAL OF CONSTRUCTION PAVEMENT MARKINGS	RAISED PAVEMENT MARKERS	THERMOPLASTIC PAVEMENT MARKING						
								TYPE II (YELLOW/YELLOW)	6"		8"		12"	YIELD LINE	
									WHITE	YELLOW	WHITE	YELLOW	WHITE		
LIN. FT. - EACH						LIN. FT.	LIN. FT.	EACH	LIN. FT.						
CONSTRUCTION PAVEMENT MARKINGS	5770	1609	1368	597		9344									
REMOVAL OF CONSTRUCTION PAVEMENT MARKINGS		1355	3565	62			4982								
RAISED PAVEMENT MARKERS TYPE II (YELLOW/YELLOW)					21			21							
THERMOPLASTIC PAVEMENT MARKING WHITE (6")					1333				1333						
THERMOPLASTIC PAVEMENT MARKING YELLOW (6")					2311					2311					
THERMOPLASTIC PAVEMENT MARKING WHITE (8")					37						37				
THERMOPLASTIC PAVEMENT MARKING YELLOW (8")					362							362			
THERMOPLASTIC PAVEMENT MARKING WHITE (12")					320								320		
THERMOPLASTIC PAVEMENT MARKING (YIELD LINE)					52									52	
<b>TOTALS:</b>						9344	4982	21	1333	2311	37	362	320	52	

NOTE: THIS IS A HIGH TRAFFIC VOLUME ROAD AS DEFINED IN SECTION 604.03, STANDARD SPECIFICATIONS FOR HIGHWAY CONSTRUCTION.

**REMOVAL AND DISPOSAL OF ITEMS**

STATION	STATION	LOCATION	CURB	CURB AND GUTTER	CONCRETE PAVEMENT	CONCRETE DRIVEWAYS	WALKS	BUILDINGS
			LIN. FT.	LIN. FT.	SQ. YD.	SQ. YD.	SQ. YD.	EACH
101+37	102+60	HWY. 34 LT.	104					
203+37	204+00	HWY. 49 RT.	122					
101+10	107+90	HWY. 34 RT.		572				
101+10	107+80	HWY. 34 LT.		455				
101+36	102+22	HWY. 34 LT.			565			
104+76	105+95	HWY. 34 RT.			970			
205+25	205+58	HWY. 49 RT.			515			
102+22	102+42	HWY. 34 LT.				360		
105+81	106+17	HWY. 34 LT.				215		
106+90	107+41	HWY. 34 LT.				735		
202+40	202+80	HWY. 49 RT.				500		
205+58	205+88	HWY. 49 RT.				855		
206+74	206+94	HWY. 49 RT.				635		
101+10	107+89	HWY. 34 RT.					1850	
201+20	207+83	HWY. 49 LT.					2300	
204+85	207+73	HWY. 49 RT.					1050	
103+80	103+80	HWY. 34 RT.						1
<b>TOTALS:</b>			226	1027	2050	3300	5200	1

**REMOVAL AND DISPOSAL OF FENCE**

STATION	STATION	LOCATION	FENCE
			LIN. FT.
202+45	204+30	HWY. 49 LT.	250
<b>TOTAL:</b>			250

**CLEARING AND GRUBBING**


STATION	STATION	LOCATION	CLEARING	GRUBBING
			STATION	STATION
203+85	204+00	HWY. 49 LT.	1	1
105+30	105+50	HWY. 34 RT.	1	1
<b>TOTALS:</b>			2	2

QUANTITIES

R100878.DGN 2/3/2020

DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. RD. DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.			
				JOB NO.	I00878		18	45

② QUANTITIES



Aug 21 2020 11:04 AM

EARTHWORK

STATION	STATION	LOCATION / DESCRIPTION	UNCLASSIFIED EXCAVATION	COMPACTED EMBANKMENT	* SOIL STABILIZATION
			CU. YD.		TON
100+07.27	104+04.75	HWY. 34 WEST - STAGE 1	48	79	
100+07.27	104+04.75	HWY. 34 WEST - STAGE 2	45	108	
103+00.00	104+04.75	HWY. 34 WEST - STAGE 4	25	43	
104+95.25	108+90.88	HWY. 34 EAST - STAGE 1	159	9	
104+95.25	108+90.88	HWY. 34 EAST - STAGE 2	55	56	
104+95.25	107+00.00	HWY. 34 EAST - STAGE 4	61	62	
200+17.21	204+06.85	HWY. 49 SOUTH - STAGE 1	58	81	
200+17.21	204+06.85	HWY. 49 SOUTH - STAGE 2	79	112	
203+00.00	204+06.85	HWY. 49 SOUTH - STAGE 4	38	56	
204+93.15	208+83.55	HWY. 49 NORTH - STAGE 1	65	94	
204+93.15	208+83.55	HWY. 49 NORTH - STAGE 2	66	111	
204+93.15	206+61.00	HWY. 49 NORTH - STAGE 4	38	83	
0+00.00	2+82.74	ROUNDAABOUT CENTRAL ISLAND - STAGE 3	87		
ENTIRE PROJECT		APPROACH ISLANDS - STAGE 3	15		
ENTIRE PROJECT		APPROACHES	5	70	
ENTIRE PROJECT		TO BE USED IF AND WHERE DIRECTED BY THE ENGINEER			100
<b>TOTALS:</b>			<b>844</b>	<b>964</b>	<b>100</b>

\* QUANTITY ESTIMATED.  
SEE SECTION 104.03 OF THE STD. SPECS.

NOTE: EARTHWORK QUANTITIES SHOWN ABOVE SHALL BE PAID AS PLAN QUANTITY.

CONCRETE WALKS

STATION	STATION	LOCATION	LENGTH	CONCRETE WALKS
			LIN. FT.	SQ. YD.
101+18	107+89	HWY. 34 LT. & RT.	776	431
201+29	207+68	HWY. 49 LT. & RT.	713	396
<b>TOTAL:</b>				<b>827</b>

REMOVAL AND DISPOSAL OF CULVERTS AND DROP INLETS

STATION	DESCRIPTION	PIPE CULVERTS	DROP INLETS
		EACH	EACH
101+20	HWY. 34 LT.	2	1
101+28	HWY. 34 RT.		1
201+76	HWY. 49 LT.	1	
202+25	HWY. 49 LT.	1	
202+75	HWY. 49 LT.	1	
203+30	HWY. 49 LT.	1	
203+78	HWY. 49 LT.	1	
204+35	HWY. 49 LT.	1	
204+54	HWY. 49 LT.	1	
204+79	HWY. 49 LT.	1	1
204+96	HWY. 49 LT.	2	1
205+23	HWY. 49 LT.	1	
206+61	HWY. 49 LT.	1	
<b>TOTALS:</b>		<b>14</b>	<b>4</b>

NOTE: QUANTITIES SHOWN ABOVE SHALL INCLUDE REMOVAL & DISPOSAL OF ALL HEADWALLS AND FLARED END SECTIONS IF APPLICABLE.

SOIL LOG

STATION	LATITUDE			LONGITUDE			LOCATION	DEPTH FEET	LIQUID LIMIT	PLASTICITY INDEX	AASHTO CLASSIFICATION	COLOR
	DEG	MIN	SEC	DEG	MIN	SEC						
103+00	36	11	15.60	90	23	5.70	6' RT.	0-5'	47	27	A-7-6(29)	BROWN
108+00	36	11	10.70	90	23	5.60	6' LT.	0-5'	30	13	A-6(9)	BROWN
203+00	36	11	12.90	90	23	8.30	15' RT.	0-5'	40	21	A-3(13)	BROWN
208+00	36	11	13.40	90	23	2.10	8' LT.	0-5'	33	16	A-3(14)	BROWN

SOIL CHARACTERISTICS TABULATED ABOVE ARE REPRESENTATIVE AT THE LOCATION OF THE SAMPLE, AND FROM SURFACE INDICATIONS ARE TYPICAL FOR THE LIMITS SHOWN. THESE DATA ARE SHOWN FOR INFORMATION ONLY. THE STATE WILL NOT BE RESPONSIBLE FOR VARIATIONS IN THE SOIL CHARACTERISTICS AND/OR EXTENT OF SAME DIFFERING FROM THE ABOVE TABULATIONS.

EROSION CONTROL

STATION	STATION	LOCATION	PERMANENT EROSION CONTROL					TEMPORARY EROSION CONTROL							
			SEEDING	LIME	MULCH COVER	WATER	SECOND SEEDING APPLICATION	SOLID SODDING	TEMPORARY SEEDING	MULCH COVER	WATER	FILTER SOCK (12")	SILT FENCE	*SEDIMENT REMOVAL & DISPOSAL	
			ACRE	TON	ACRE	M.GAL.	ACRE	SQ.YD.	ACRE	ACRE	M.GAL.	(E-13) LIN. FT.	(E-11) LIN. FT.	CU. YD.	
ENTIRE PROJECT		CLEARING AND GRUBBING													
ENTIRE PROJECT		STAGE 1	0.05	0.10	0.05	5.1	0.05			0.50	0.50	10.2	50	135	7
ENTIRE PROJECT		STAGE 2	0.05	0.10	0.05	5.1	0.05			0.50	0.50	10.2	16	150	1
ENTIRE PROJECT		STAGE 4				8.1			644				38		1
ENTIRE PROJECT		TO BE USED IF AND WHERE DIRECTED BY THE ENGINEER.	0.03	0.06	0.03	3.1	0.03			0.25	0.25	5.1	26	38	2
<b>TOTALS:</b>			<b>0.13</b>	<b>0.26</b>	<b>0.13</b>	<b>21.4</b>	<b>0.13</b>	<b>644</b>	<b>1.25</b>	<b>1.25</b>	<b>25.5</b>	<b>130</b>	<b>323</b>	<b>16</b>	

BASIS OF ESTIMATE:  
LIME .....2 TONS / ACRE OF SEEDING  
WATER.....102.0 M.G. / ACRE OF SEEDING  
WATER.....20.4 M.G. / ACRE OF TEMPORARY SEEDING  
WATER.....12.6 GAL. / SQ. YD. OF SOLID SODDING

NOTE: THE TEMPORARY EROSION CONTROL DEVICES SHOWN ABOVE AND ON THE PLANS SHALL BE INSTALLED IN SUCH A SEQUENCE AS TO DETER EROSION AND SEDIMENTATION ON U.S. WATERWAYS AS EXPLAINED BY THE NATIONAL POLLUTANT DISCHARGE ELIMINATION SYSTEM PERMIT.

\*QUANTITIES ESTIMATED.  
SEE SECTION 104.03 OF THE STD. SPECS.

DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. RD. DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.		19	45
				JOB NO.		I00878		

② QUANTITIES



Aug 21 2020 11:04 AM

CONCRETE ISLAND

STATION	LOCATION/DESCRIPTION	CURB FACE TYPE	CONCRETE ISLAND	STAINING CONCRETE SURFACES
			SQ.YD.	SQ.FT.
0+00	ROUNDAABOUT CENTER			2827
101+80	HWY. 34 LT. - FORESLOPE	D	88	
102+75	HWY. 34 LT. - FORESLOPE	D	28	
103+80	HWY. 34 - APPROACH ISLAND	B	49	386
103+75	HWY. 34 LT. - FORESLOPE	D	121	
105+15	HWY. 34 - APPROACH ISLAND	B	30	206
202+00	HWY. 49 RT. - FORESLOPE	D	73	
203+00	HWY. 49 RT. - FORESLOPE	D	34	
203+80	HWY. 49 - APPROACH ISLAND	B	38	279
204+00	HWY. 49 RT. - FORESLOPE	D	167	
205+25	HWY. 49 - APPROACH ISLAND	B	42	315
<b>TOTALS:</b>			<b>670</b>	<b>4013</b>

CONCRETE COMBINATION CURB AND GUTTER

STATION	STATION	LOCATION	TYPE A (1' 6")
			LIN. FT.
101+27	107+91	HWY. 34 LT. & RT.	1287
201+17	207+84	HWY. 49 LT. & RT.	1264
<b>TOTAL:</b>			<b>2551</b>

FENCING

STATION	STATION	LOCATION	* 5' CHAIN LINK FENCE
			LIN. FT.
202+44	203+41	HWY. 49 LT.	77
<b>TOTAL:</b>			<b>77</b>

\* DENOTES ALTERNATE BID ITEM.

WHEELCHAIR RAMPS

STATION	LOCATION	TYPE 3
		SQ.YD.
101+15	HWY. 34 RT.	3.9
101+25	HWY. 34 LT.	5.4
103+80	HWY. 34 LT.	3.8
103+80	HWY. 34 RT.	3.9
105+20	HWY. 34 LT.	3.9
105+20	HWY. 34 RT.	3.7
107+60	HWY. 34 LT.	5.4
107+70	HWY. 34 RT.	5.4
201+25	HWY. 49 LT.	4.0
201+55	HWY. 49 RT.	5.4
203+82	HWY. 49 LT.	3.8
203+82	HWY. 49 RT.	3.9
205+23	HWY. 49 LT.	3.8
205+23	HWY. 49 RT.	3.7
207+65	HWY. 49 RT.	4.9
207+70	HWY. 49 LT.	4.5
<b>TOTAL:</b>		<b>69.4</b>

SELECTED PIPE BEDDING

LOCATION	SELECTED PIPE BEDDING
	CU.YD.
ENTIRE PROJECT TO BE USED IF AND WHERE DIRECTED BY THE ENGINEER	110
<b>TOTAL:</b>	<b>110</b>

NOTE: QUANTITY ESTIMATED. SEE SECTION 104.03 OF THE STD. SPECS.

PAVEMENT REPAIR OVER CULVERTS (CONCRETE)

STATION	LOCATION	WIDTH	LENGTH	CU.YD.
		FEET		
107+57	HWY. 34	7.92	36	17.6
201+68	HWY. 49	8.50	28	14.7
205+28	HWY. 49	7.92	22	10.8
<b>TOTAL:</b>				<b>43.1</b>

AVG. DEPTH = 20"

4" PIPE UNDERDRAIN

STATION	STATION	LOCATIONS	4" PIPE UNDERDRAINS
			LIN. FT.
* ENTIRE PROJECT TO BE USED IF AND WHERE DIRECTED BY THE ENGINEER			500
<b>TOTAL:</b>			<b>500</b>

\* NOTE: QUANTITY ESTIMATED. SEE SECTION 104.03 OF THE STD. SPECS.

UNDERDRAINS SHALL BE STUBBED INTO THE PROPOSED DROP INLET IF AND WHERE DIRECTED BY THE ENGINEER. PAYMENT FOR THIS TO BE INCLUDED IN THE UNIT PRICE BID FOR 4" PIPE UNDERDRAIN.

COLD MILLING ASPHALT PAVEMENT

STATION	STATION	LOCATION	AVG. WIDTH	COLD MILLING ASPHALT PAVEMENT
			FEET	SQ. YD.
100+07.27	101+07.27	MAIN LANES	VAR.	432.58
107+90.88	108+90.88	MAIN LANES	VAR.	525.38
200+17.21	201+17.21	MAIN LANES	VAR.	501.24
207+83.55	208+83.55	MAIN LANES	VAR.	439.68
<b>TOTAL:</b>				<b>1898.88</b>


NOTE: AVERAGE MILLING DEPTH 1".

2/3/2020

R00878.DGN

DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. RD. DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.		20	45
				JOB NO.	100878			

② QUANTITIES



Aug 21 2020 11:04 AM

DRIVEWAYS

STATION	SIDE	LOCATION	WIDTH	**MODIFIED CURB		PORTLAND CEMENT CONCRETE DRIVEWAY	ACHM SURFACE COURSE (1/2") 220 LBS. PER SQ. YD. (PG 64-22)		AGGREGATE BASE COURSE (CLASS 7)	STANDARD DRAWINGS
				STATION	STATION		SQ. YD.	TON		
102+42	LT.	HWY. 34	40	102+08	102+76	101.55				DR-1
102+73	RT.	HWY. 34	16	102+51	102+95	39.11	25.71	2.83	10.50	DR-1
103+13	LT.	HWY. 34	40	102+79	103+47	60.44	37.11	4.08	15.15	DR-1
106+00	LT.	HWY. 34	32	105+70	106+30	89.13				DR-1
106+06	RT.	HWY. 34	22	105+81	106+31	44.44	42.68	4.69	17.43	DR-1
106+35	LT.	HWY. 34	16	106+13	106+57	39.11	13.72	1.51	5.60	DR-1
107+09	LT.	HWY. 34	40	106+75	107+43	103.28				DR-1
201+76	LT.	HWY. 49	16	201+54	201+98	39.11	16.89	1.86	6.90	DR-1
202+25	LT.	HWY. 49	16	202+03	202+47	39.11	16.89	1.86	6.90	DR-1
202+60	RT.	HWY. 49	40	202+26	202+94	142.66				DR-1
202+75	LT.	HWY. 49	16	202+53	202+97	39.11	18.79	2.07	7.67	DR-1
203+27	RT.	HWY. 49	20	203+03	203+51	62.05				DR-1
205+73	RT.	HWY. 49	30	205+44	206+02	131.66				DR-1
206+61	LT.	HWY. 49	16	206+39	206+83	39.11	13.07	1.44	5.34	DR-1
206+84	RT.	HWY. 49	20	206+60	207+08	106.00				DR-1
* ENTIRE PROJECT TEMPORARY DRIVES										
									150.00	
<b>TOTALS:</b>						<b>1075.87</b>	<b>184.86</b>	<b>20.34</b>	<b>225.49</b>	

BASIS OF ESTIMATE:  
 ACHM SURFACE COURSE (1/2").....94.8% MIN. AGGR.....5.2% ASPHALT BINDER  
 MAXIMUM NUMBER OF GYRATIONS = 115 FOR FG 64-22  
 THE CONTRACTOR, WITH THE APPROVAL OF THE ENGINEER, WILL BE ALLOWED TO SUBSTITUTE A HIGHER PERFORMANCE GRADE ASPHALT SURFACE COURSE FOR DRIVEWAYS AND MINOR SIDE STREET CONSTRUCTION AT NO ADDITIONAL COST TO THE DEPARTMENT.

\* QUANTITY ESTIMATED  
 SEE SECTION 104.03 OF THE STD. SPECS.  
 TO BE USED IF AND WHERE DIRECTED BY THE ENGINEER.

\*\* FOR INFORMATION ONLY

ASPHALT CONCRETE PATCHING FOR MAINTENANCE OF TRAFFIC

LOCATION	TON	TACK COAT
		GALLON
ENTIRE PROJECT - TO BE USED IF AND WHERE DIRECTED BY THE ENGINEER	25	50
<b>TOTALS:</b>	<b>25</b>	<b>50</b>

BASIS OF ESTIMATE:  
 ASPHALT CONCRETE PATCHING FOR MAINTENANCE OF TRAFFIC...25 TON/MILE  
 TACK COAT FOR MAINTENANCE OF TRAFFIC.....50 GAL./MILE  
 \* QUANTITY ESTIMATED.  
 SEE SECTION 104.03 OF THE STD. SPECS.

ACHM PATCHING OF EXISTING ROADWAY

DESCRIPTION	TON
ENTIRE PROJECT - TO BE USED IF AND WHERE DIRECTED BY THE ENGINEER	25
<b>TOTAL:</b>	<b>25</b>

NOTE: QUANTITY ESTIMATED.  
 SEE SECTION 104.03 OF THE STD. SPECS.

STRUCTURES

STATION	DESCRIPTION	REINFORCED CONCRETE PIPE CULVERT			SIDE DRAIN	PIPE CULVERT STORM DRAIN ALTERNATES 1 & 2	FLARED END SECTIONS FOR R.C. PIPE CULVERTS	DROP INLETS			JUNCT. BOXES (TYPE E)	YARD DRAINS	SOLID SODDING	WATER	STD. DWG. NOS.
		(CLASS III)	(CLASS V)					TYPE	EXT.						
		18"	18"	22"X14"				12"	4'	8'					
101+15	CONST. DROP INLET ON LT. W/EXT. W/PIPE INLET W/FES AND PIPE OUTLET	18				1	1	1				5	0.06	SPECIAL DETAIL, FES-1, FES-2, FPC-9E, FPC-9M, PCC-1	
101+28	CONST. JUNCTION BOX ON RT.									1				FPC-9	
102+00	CONST. DROP INLET ON LT. W/EXT. AND PIPE OUTLET					154	1	1						FPC-9E, FPC-9M, PCC-1, PCM-1	
103+45	CONST. DROP INLET ON RT. AND PIPE OUTLET					76	1							FPC-9E, FPC-9M, PCC-1, PCM-1	
103+57	CONST. DROP INLET ON LT. AND PIPE OUTLET		34				1							FPC-9E, FPC-9M, PCC-1	
103+75	CONST. DROP INLET ON LT. AND PIPE OUTLET					14	1							FPC-9E, FPC-9M, PCC-1, PCM-1	
103+91	CONST. DROP INLET ON LT. AND PIPE OUTLET					14	1							FPC-9E, FPC-9M, PCC-1, PCM-1	
201+29	CONST. JUNCTION BOX ON LT. W/ PIPE INLET W/FES AND PIPE OUTLET	20								1		5	0.06	SPECIAL DETAIL, FES-1, FES-2, FPC-9, PCC-1	
201+45	CONST. DROP INLET ON LT. W/EXT. AND PIPE OUTLET					16	1	1						FPC-9E, FPC-9M, PCC-1, PCM-1	
201+68	CONST. DROP INLET ON RT. AND PIPE OUTLET		34				1	1						FPC-9E, FPC-9M, PCC-1	
204+00	CONST. DROP INLET ON LT. W/EXT. AND PIPE OUTLET					250	1	1						FPC-9E, FPC-9M, PCC-1, PCM-1	
205+28	CONST. DROP INLET ON LT. W/EXT. AND PIPE OUTLET					60	1	1						FPC-9E, FPC-9M, PCC-1, PCM-1	
205+28	CONST. DROP INLET ON RT. W/EXT. AND PIPE OUTLET		38				1	1						FPC-9E, FPC-9M, PCC-1	
207+50	CONST. DROP INLET ON LT. W/EXT. AND PIPE OUTLET					218	1		1					FPC-9E, FPC-9M, PCC-1, PCM-1	
207+76	CONST. JUNCTION BOX ON LT. W/ PIPE INLET W/FES AND PIPE OUTLET	6				26				1		5		FES-1, FES-2, FPC-9, PCC-1, PCM-1	
* ENTIRE PROJECT TO BE USED AS DIRECTED BY THE ENGINEER															
					600						6			FPC-9, PCM-1	
<b>TOTALS:</b>		<b>44</b>	<b>72</b>	<b>34</b>	<b>600</b>	<b>828</b>	<b>3</b>	<b>12</b>	<b>7</b>	<b>1</b>	<b>3</b>	<b>6</b>	<b>15</b>	<b>0.12</b>	

BASIS OF ESTIMATE:  
 WATER.....12.6 GAL. / SQ. YD. OF SOLID SODDING

NOTE: FOR R.C. PIPE CULVERT INSTALLATIONS USE TYPE 3 BEDDING UNLESS OTHERWISE SPECIFIED.


NOTE: FOR C.M. PIPE CULVERT INSTALLATIONS USE TYPE 2 BEDDING UNLESS OTHERWISE SPECIFIED.

2/3/2020

R100878.DGN

DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. RD. DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.		21	45
				JOB NO.		100878		

② QUANTITIES



Aug 21 2020 11:04 AM

DocuSign

BASE AND SURFACING (BOX 1 OF 2)

STATION	STATION	LOCATION	LENGTH FEET	PORTLAND CEMENT CONCRETE BASE				TACK COAT						TOTAL GALLONS	
				AVG. WIDTH FEET	8" U.T. SQ. YD.	AVG. WIDTH FEET	5" U.T. SQ. YD.	(0.05 GAL. PER SQ. YD.)			(0.17 GAL. PER SQ. YD.)				
								TOTAL WID. FEET	SQ. YD.	GALLON	TOTAL WID. FEET	SQ. YD.	GALLON		
<b>MAIN LANES</b>															
100+07.27	101+07.27	HWY. 34 - TRANSITION	100.00												
101+07.27	104+04.75	HWY. 34 - C.C.C.&G. SECTION	297.48	VAR.	210.96	VAR.	69.79	VAR.	1098.44	54.92				54.92	
104+95.25	107+90.88	HWY. 34 - C.C.C.&G. SECTION	295.63	VAR.	209.51	VAR.	86.36	VAR.	1831.82	91.59				91.59	
107+90.88	108+90.88	HWY. 34 - TRANSITION	100.00								VAR.	525.38	89.31	89.31	
200+17.21	201+17.21	HWY. 49 - TRANSITION	100.00									VAR.	501.24	85.21	85.21
201+17.21	204+06.85	HWY. 49 - C.C.C.&G. SECTION	289.64	VAR.	213.53	VAR.	81.43	VAR.	1408.64	70.43				70.43	
204+93.15	205+95.00	HWY. 49 - C.C.C.&G. SECTION	101.85	VAR.	227.25	VAR.	99.38	VAR.	1329.56	66.48				66.48	
207+83.55	208+83.55	HWY. 49 - TRANSITION	100.00								VAR.	439.68	74.75	74.75	
0+00.00	2+82.74	ROUNDAABOUT - C.C.C.&G. SECTION	282.74					VAR.	1266.63	63.33				63.33	
0+00.00	2+82.74	ROUNDAABOUT - CENTRAL ISLAND	282.74												
<b>ADDITIONAL FOR LEVELING</b>															
101+07.27	104+04.75	HWY. 34 - C.C.C.&G. SECTION	297.48								VAR.	944.58	160.58	160.58	
104+95.25	107+90.88	HWY. 34 - C.C.C.&G. SECTION	295.63								VAR.	722.65	122.85	122.85	
201+17.21	204+06.85	HWY. 49 - C.C.C.&G. SECTION	289.64								VAR.	708.01	120.36	120.36	
204+93.15	207+83.55	HWY. 49 - C.C.C.&G. SECTION	290.40								VAR.	709.87	120.68	120.68	
0+00.00	2+82.74	ROUNDAABOUT - C.C.C.&G. SECTION	282.74								VAR.	247.26	42.03	42.03	
<b>TOTALS:</b>					861.25		336.96		6935.09	346.75		5231.25	889.31	1236.06	

BASIS OF ESTIMATE:  
TACK COAT QUANTITIES WERE CALCULATED USING THE EMULSIFIED ASPHALT RATES. REFER TO SS-400-1 FOR THE RESIDUAL ASPHALT APPLICATION RATES.

BASE AND SURFACING (BOX 2 OF 2)

STATION	STATION	LOCATION	ACHM BASE COURSE (1 1/2")				ACHM BINDER COURSE (1")				ACHM SURFACE COURSE (1/2")						PORTLAND CEMENT CONCRETE PAVEMENT			
			AVG. WID. FEET	SQ. YD.	POUND / SQ. YD.	PG 64-22 TON	AVG. WID. FEET	SQ. YD.	POUND / SQ. YD.	PG 64-22 TON	AVG. WID. FEET	SQ. YD.	POUND / SQ. YD.	PG 64-22 TON	AVG. WID. FEET	SQ. YD.	POUND / SQ. YD.	PG 64-22 TON	TOTAL PG 64-22 TON	8" U.T. SQ. YD.
<b>MAIN LANES</b>																				
100+07.27	101+07.27	HWY. 34 - TRANSITION																		
101+07.27	104+04.75	HWY. 34 - C.C.C.&G. SECTION	VAR.	67.76	550.00	18.63	VAR.	67.76	330.00	11.18	VAR.	67.76	220.00	7.45	VAR.	432.58	220.00	47.58	47.58	
104+95.25	107+90.88	HWY. 34 - C.C.C.&G. SECTION	VAR.	395.60	550.00	108.79	VAR.	395.60	330.00	65.27	VAR.	395.60	220.00	43.52	VAR.	997.83	220.00	109.76	153.28	
107+90.88	108+90.88	HWY. 34 - TRANSITION													VAR.	525.38	220.00	57.79	57.79	
200+17.21	201+17.21	HWY. 49 - TRANSITION													VAR.	501.24	220.00	55.14	55.14	
201+17.21	204+06.85	HWY. 49 - C.C.C.&G. SECTION	VAR.	199.29	550.00	54.80	VAR.	199.29	330.00	32.88	VAR.	199.29	220.00	21.92	VAR.	966.33	220.00	106.30	128.22	
204+93.15	205+95.00	HWY. 49 - C.C.C.&G. SECTION	VAR.	196.87	550.00	54.14	VAR.	190.56	330.00	31.44	VAR.	190.56	220.00	20.96	VAR.	905.69	220.00	99.63	120.59	
207+83.55	208+83.55	HWY. 49 - TRANSITION													VAR.	439.68	220.00	48.36	48.36	
0+00.00	2+82.74	ROUNDAABOUT - C.C.C.&G. SECTION	VAR.	356.50	550.00	98.04	VAR.	356.50	330.00	58.82	VAR.	356.50	220.00	39.22	VAR.	553.41	220.00	60.88	100.10	
0+00.00	2+82.74	ROUNDAABOUT - CENTRAL ISLAND	VAR.	314.16	440.00	69.12													314.16	
<b>ADDITIONAL FOR LEVELING</b>																				
101+07.27	104+04.75	HWY. 34 - C.C.C.&G. SECTION									VAR.	944.58	VAR.	129.88					129.88	
104+95.25	107+90.88	HWY. 34 - C.C.C.&G. SECTION									22.00	722.65	VAR.	119.24					119.24	
201+17.21	204+06.85	HWY. 49 - C.C.C.&G. SECTION									22.00	708.01	VAR.	58.41					58.41	
204+93.15	207+83.55	HWY. 49 - C.C.C.&G. SECTION									22.00	709.87	VAR.	97.61					97.61	
0+00.00	2+82.74	ROUNDAABOUT - C.C.C.&G. SECTION									VAR.	247.26	VAR.	115.59					115.59	
<b>TOTALS:</b>				1530.18		403.52		1209.71		199.59		4542.08		653.80		6261.60		688.78	1342.58	314.16

BASIS OF ESTIMATE:  
ACHM SURFACE COURSE (1/2").....94.8% MIN. AGGR.....5.2% ASPHALT BINDER  
ACHM BINDER COURSE (1").....95.9% MIN. AGGR.....4.1% ASPHALT BINDER  
ACHM BASE COURSE (1 1/2").....96.1% MIN. AGGR.....3.9% ASPHALT BINDER  
MAXIMUM NUMBER OF GYRATIONS = 115 FOR PG 64-22

QUANTITIES

2/3/2020 R100878.DGN

SUMMARY OF QUANTITIES

ITEM NUMBER	ITEM	QUANTITY	UNIT
201	CLEARING	2	STATION
201	GRUBBING	2	STATION
202	REMOVAL AND DISPOSAL OF CURB	226	LN. FT.
202	REMOVAL AND DISPOSAL OF CURB AND GUTTER	1027	LN. FT.
202	REMOVAL AND DISPOSAL OF FENCE	250	LN. FT.
202	REMOVAL AND DISPOSAL OF CONCRETE PAVEMENT	2050	SQ. YD.
202	REMOVAL AND DISPOSAL OF CONCRETE DRIVEWAYS	3300	SQ. YD.
202	REMOVAL AND DISPOSAL OF WALKS	5200	SQ. YD.
202	REMOVAL AND DISPOSAL OF DROP INLETS	4	EACH
202	REMOVAL AND DISPOSAL OF PIPE CULVERTS	14	EACH
202	REMOVAL AND DISPOSAL OF BUILDINGS	1	EACH
SS & 210	UNCLASSIFIED EXCAVATION	844	CU. YD.
210	COMPACTED EMBANKMENT	964	CU. YD.
SP & 210	SOIL STABILIZATION	100	TON
SS & 303	AGGREGATE BASE COURSE (CLASS 7)	225	TON
309	PORTLAND CEMENT CONCRETE BASE (5" UNIFORM THICKNESS)	337	SQ. YD.
309	PORTLAND CEMENT CONCRETE BASE (8" UNIFORM THICKNESS)	861	SQ. YD.
SS & 401	TACK COAT	1286	GAL.
SP, SS, & 405	MINERAL AGGREGATE IN ACHM BASE COURSE (1 1/2")	388	TON
SP, SS, & 405	ASPHALT BINDER (PG 64-22) IN ACHM BASE COURSE (1 1/2")	16	TON
SP, SS, & 406	MINERAL AGGREGATE IN ACHM BINDER COURSE (1")	192	TON
SP, SS, & 406	ASPHALT BINDER (PG 64-22) IN ACHM BINDER COURSE (1")	8	TON
SP, SS, & 407	MINERAL AGGREGATE IN ACHM SURFACE COURSE (1/2")	1292	TON
SP, SS, & 407	ASPHALT BINDER (PG 64-22) IN ACHM SURFACE COURSE (1/2")	71	TON
412	COLD MILLING ASPHALT PAVEMENT	1899	SQ. YD.
SP, SS, & 414	ASPHALT CONCRETE PATCHING FOR MAINTENANCE OF TRAFFIC	25	TON
SP, SS, & 415	ACHM PATCHING OF EXISTING ROADWAY	25	TON
SP & 501	PORTLAND CEMENT CONCRETE PAVEMENT (8" UNIFORM THICKNESS)	314	SQ. YD.
SS & 505	PORTLAND CEMENT CONCRETE DRIVEWAY	1075.87	SQ. YD.
601	MOBILIZATION	1.00	LUMP SUM
SP & 602	FURNISHING FIELD OFFICE	1	EACH
SS & 603	MAINTENANCE OF TRAFFIC	1.00	LUMP SUM
SS & 604	SIGNS	374	SQ. FT.
SS & 604	TRAFFIC CONE	61	EACH
604	CONSTRUCTION PAVEMENT MARKINGS	9344	LN. FT.
604	REMOVAL OF CONSTRUCTION PAVEMENT MARKINGS	4982	LN. FT.
SS & 604	VERTICAL PANELS	48	EACH
606	18" REINFORCED CONCRETE PIPE CULVERTS (CLASS III)	44	LN. FT.
606	18" REINFORCED CONCRETE PIPE CULVERTS (CLASS III)	828	LN. FT.
606	18" SMOOTH LINED POLYMER PRECOATED METALLIC COATED CORRUGATED STEEL PIPE (ALTERNATE NO. 2)	828	LN. FT.
606	18" REINFORCED CONCRETE PIPE CULVERTS (CLASS V)	72	LN. FT.
SS & 606	22" X 14" REINFORCED CONCRETE ARCH PIPE CULVERTS (CLASS V)	34	LN. FT.
606	12" SIDE DRAIN	600	LN. FT.
606	18" FLARED END SECTIONS FOR REINFORCED CONCRETE PIPE CULVERTS	3	EACH
606	SELECTED PIPE BEDDING	110	CU. YD.
SS & 609	DROP INLETS (TYPE MO)	12	EACH
SS & 609	JUNCTION BOXES (TYPE E)	3	EACH
SS & 609	DROP INLET EXTENSIONS (4')	7	EACH
SS & 609	DROP INLET EXTENSIONS (8')	1	EACH
SS & 609	YARD DRAINS	6	EACH
SS & 611	4" PIPE UNDERDRAINS	500	LN. FT.
615	PAVEMENT REPAIR OVER CULVERTS (CONCRETE)	43.1	CU. YD.
619	5' STEEL CHAIN LINK FENCE	77	LN. FT.
619	5' ALUMINUM CHAIN LINK FENCE	77	LN. FT.
620	LIME	1	TON
620	SEEDING	0.13	ACRE
SS & 620	MULCH COVER	1.38	ACRE
620	WATER	47.0	M. GAL.
621	TEMPORARY SEEDING	1.25	ACRE
621	SILT FENCE	323	LN. FT.
621	SEDIMENT REMOVAL AND DISPOSAL	16	CU. YD.
SS & 621	FILTER SOCK (12")	130	LN. FT.
623	SECOND SEEDING APPLICATION	0.13	ACRE
624	SOLID SODDING	659	SQ. YD.
SS & 632	CONCRETE ISLAND	670	SQ. YD.
SS & 633	CONCRETE WALKS	827	SQ. YD.
SS & 634	CONCRETE COMBINATION CURB AND GUTTER (TYPE A) (1' 6")	2551	LN. FT.
635	ROADWAY CONSTRUCTION CONTROL	1.00	LUMP SUM
641	WHEELCHAIR RAMPS (TYPE 3)	69	SQ. YD.
SP	ELECTRICAL CONDUCTORS-IN-CONDUIT (2C/8 A.W.G., E.G.C.)	1187	LN. FT.
SP	ELECTRICAL CONDUCTORS-IN-CONDUIT (2C/12 A.W.G., E.G.C.)	573	LN. FT.
710	NON-METALLIC CONDUIT (2")	1228	LN. FT.
711	CONCRETE PULL BOX (TYPE 2 HD)	15	EACH
SP	LED ROADWAY ILLUMINATION POLE (6,000 LUMENS, COBRA HEAD, SHOE BASE, 30')	12	EACH
SP	SERVICE POINT ASSEMBLY (2 CIRCUITS)	1	EACH
719	THERMOPLASTIC PAVEMENT MARKING WHITE (6")	1333	LN. FT.
719	THERMOPLASTIC PAVEMENT MARKING WHITE (8")	37	LN. FT.
719	THERMOPLASTIC PAVEMENT MARKING WHITE (12")	320	LN. FT.
719	THERMOPLASTIC PAVEMENT MARKING YELLOW (6")	2311	LN. FT.
719	THERMOPLASTIC PAVEMENT MARKING YELLOW (8")	362	LN. FT.
SP & 719	THERMOPLASTIC PAVEMENT MARKING (YIELD LINE)	52	LN. FT.
721	RAISED PAVEMENT MARKERS (TYPE I)	21	EACH
SP	STAINING CONCRETE SURFACES	4013	SQ. FT.

\* DENOTES ALTERNATE BID ITEMS.

REVISIONS

DATE	REVISION	SHEET NUMBER
9/22/2020	ADDED RESTRAINING CONDITION SPECIAL PROVISION	2 & 22
9/28/2020	ADDED DELAY IN RIGHT OF WAY OCCUPANCY SPECIAL PROVISION AND REVISED RESTRAINING CONDITION SPECIAL PROVISION	2 & 22
10/8/2020	REVISED SS 100-3. ADDED SUPPLEMENTAL SPECIFICATIONS 400-7 "TRACKLESS TACK" AND 502-1 "WELDED WIRE	2 & 22
10/29/2020	ADDED THE SPECIAL PROVISION "PROHIBITION OF CERTAIN TELECOMMUNICATIONS AND VIDEO SURVEILLANCE SERVICES OR EQUIPMENT".	2 & 22

DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. RD. DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
09-22-20		10-29-20		6	ARK.			
09-28-20								
10-08-20								
				JOB NO.		100878	22	45

2 SUMMARY OF QUANTITIES AND REVISIONS



Oct 29 2020 11:25 AM  
DocuSign

DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. RD. DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.		23	45
				JOB NO.		100878		

2 SURVEY CONTROL DETAILS




Aug 21 2020 11:05 AM

HWY. 49 - NORTH SIDE

POINT NO.	TYPE	STATION	NORTHING	EASTING
8002	POB	204+50.00	678620.0487	1788991.1708
8003	POE	209+00.00	679070.0486	1788990.8812

HWY. 49 - SOUTH SIDE

POINT NO.	TYPE	STATION	NORTHING	EASTING
8000	POB	200+00.00	678166.3534	1788987.5824
8001	POE	204+50.00	678616.3430	1788990.6418



SURVEY CONTROL COORDINATES

Project Name: s100878  
 Date: 3/15/2017  
 Coordinate System: ARKANSAS STATE PLANE - NORTH ZONE BASED ON GPS CONTROL (VT AND HZ BASED ON GPS MON), 280017A - 280024  
 UNITS: U.S. SURVEY FOOT  
 PROJECTED TO GROUND.

Point Name	Northing	Easting	Elev	Feature	Description
1	677791.3894	1788956.8493	273.649	CTL	STD AHTD MON. STAMPED PN#1
2	678300.3948	1788955.9973	278.697	CTL	STD AHTD MON. STAMPED PN#2
3	678654.7081	1789020.3558	286.937	CTL	STD AHTD MON. STAMPED PN#3
4	678937.0660	1789016.0647	287.892	CTL	STD AHTD MON. STAMPED PN#4
5	679289.5344	1789011.7226	284.091	CTL	STD AHTD MON. STAMPED PN#5
6	678636.0224	1788260.8459	293.037	CTL	STD AHTD MON. STAMPED PN#6
7	678640.5181	1788618.1143	292.077	CTL	STD AHTD MON. STAMPED PN#7
8	678622.3999	1789307.4155	278.508	CTL	STD AHTD MON. STAMPED PN#8
9	678598.2210	1789737.8686	270.843	CTL	STD AHTD MON. STAMPED PN#9
100	678575.0431	1786373.2666	280.043	GPS	AHTD GPS MON 280017A
101	673291.2024	1786704.5133	272.841	GPS	AHTD GPS MON 280024
900	675171.9221	1788192.7903	274.073	TBM	RBR&ACAP

\*Note - Rebar and Cap - Standard - 5/8" Rebar with 2" Aluminum Cap stamped (standard markings common to all caps), or as indicated (other markings indicated in the point description of the individual point). ALL DISTANCES ARE GROUND. USE CAF = 1.0 FOR STAKEOUT FOR THIS PROJECT. A PROJECT CAF OF 0.9999764962 HAS BEEN USED TO COMPUTE THE ABOVE GROUND COORDINATES. THIS CAF IS INTENDED FOR USE WITHIN THE PROJECT LIMITS. GRID DISTANCE = GROUND DISTANCE X CAF. GRID COORDINATES ARE STORED UNDER FILE NAME s100878gi.CTL. HORIZONTAL DATUM: NAD 83 (1997). VERTICAL DATUM: NAVD 88 POSITIONAL ACCURACY THIRD ORDER, UNLESS SPECIFIED OTHERWISE AT A SPECIFIC POINT.

REFERENCE POINTS (1500 SERIES) ARE TO BE USED TO ESTABLISH CONTROL IF THE PRIMARY CONTROL POINTS LISTED ABOVE HAVE BEEN DESTROYED. REFERENCE POINTS ARE NOT TO BE USED FOR VERTICAL CONTROL.

BASIS OF BEARING: ARKANSAS STATE PLANE GRID BEARINGS - 0301-NORTH ZONE DETERMINED FROM GPS CONTROL POINTS: 280017A - 280024 CONVERGENCE ANGLE: 00-56-24 RIGHT AT PN#4 LT: N 36-11-16 LG: W09-23-05 GRID AZIMUTH = ASTRONOMICAL AZIMUTH - CONVERGENCE ANGLE.

HWY. 34  
 P.I. = 108+78.65  
 Δ = 17°45'40" LT.  
 D = 18'00'00"  
 T = 49.73'  
 L = 98.67'  
 P.C. = 108+28.92  
 P.T. = 109+27.59  
 NO SUPER

HWY. 34  
 P.I. = 105+60.47  
 Δ = 17°46'28" LT.  
 D = 18'00'00"  
 T = 49.77'  
 L = 98.75'  
 P.C. = 105+10.70  
 P.R.C. = 106+09.45  
 NO SUPER

HWY. 34  
 P.I. = 107+13.41  
 Δ = 36°10'31" RT.  
 D = 18'00'00"  
 T = 103.96'  
 L = 200.97'  
 P.R.C. = 106+09.45  
 P.T. = 108+10.42  
 NO SUPER

HWY. 34 - WEST SIDE

POINT NO.	TYPE	STATION	NORTHING	EASTING
8001	POB	104+50.00	678616.3430	1788990.6418
8007	PC	105+10.70	678617.0955	1789051.3370
8009	PRC	106+09.45	678633.4932	1789148.3115
8011	PT	108+10.42	678634.8628	1789345.9595
8012	PC	108+28.92	678629.2423	1789363.5808
8014	PT	109+27.59	678614.1900	1789460.7003
8015	POE	110+00.00	678614.2792	1789533.1099

HWY. 34 - EAST SIDE

POINT NO.	TYPE	STATION	NORTHING	EASTING
8004	POB	100+00.00	678619.5532	1788541.3308
8005	P1	102+44.55	678623.0843	1788785.8523
8006	P1	103+34.75	678618.3845	1788875.9296
8002	POE	104+50.00	678620.0487	1788991.1708

ROUNDBOUT

POINT NO.	TYPE	STATION	NORTHING	EASTING
8016	PC	0+00.00	678650.3456	1788959.4199
8018	PCC	1+41.37	678586.0461	1789022.3927
8016	PT	2+82.74	678650.3456	1788959.4199


2/3/2020

R100878.DGN

SURVEY CONTROL DETAILS


DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. RD. DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.		24	45
				JOB NO. 100878		24		45

2 PLAN AND PROFILE SHEETS



Aug 21 2020 11:05 AM  
DocuSign

**STA. 207+83.55**  
**END HWY. 49**  
**END JOB 100878**



STA. 101+15 CONSTRUCT  
DROP INLET ON LT.  
WITH 4' EXTENSION  
AND 18" X 10' PIPE INLET WITH F.E.S.  
AND 18" X 8' PIPE OUTLET  
CONNECT TO EXIST. 18" X 48' R.C. PIPE  
DROP INLET H = 4'-3"  
TYPE MO DROP INLET = 4' DIA.  
TYPE C DROP INLET = 4' X 3'  
18" R.C. PIPE = 18 LIN. FT.

STA. 102+00 CONSTRUCT  
DROP INLET ON LT.  
WITH 4' EXTENSION  
AND 18" X 154' PIPE OUTLET  
CONNECT TO DROP INLET @ STA. 103+57  
DROP INLET H = 2'-3"  
TYPE MO DROP INLET = 4' DIA.  
TYPE C DROP INLET = 4' X 3'  
18" R.C. PIPE = 154 LIN. FT.  
18" SLPPCS PIPE = 154 LIN. FT.

STA. 103+57 CONSTRUCT  
DROP INLET ON LT.  
AND 18" X 34' PIPE OUTLET  
CONNECT TO DROP INLET @ STA. 103+45  
DROP INLET H = 4'-4"  
TYPE MO DROP INLET = 4' DIA.  
TYPE C DROP INLET = 4' X 3'  
18" R.C. PIPE (CLASS V) = 34 LIN. FT.

STA. 103+75 CONSTRUCT  
DROP INLET ON LT.  
AND 18" X 14' PIPE OUTLET  
CONNECT TO DROP INLET @ STA. 103+57  
DROP INLET H = 4'-0"  
TYPE MO DROP INLET = 4' DIA.  
TYPE C DROP INLET = 4' X 3'  
18" R.C. PIPE = 14 LIN. FT.  
18" SLPPCS PIPE = 14 LIN. FT.

STA. 101+20 IN PLACE  
DROP INLET ON LT.  
AND 18" X 16' R.C. PIPE INLET  
WITH HDWL.  
AND 18" X 48' C.M. PIPE OUTLET  
REMOVE

STA. 101+28 IN PLACE  
DROP INLET ON RT.  
REMOVE

STA. 203+30 IN PLACE  
18" X 26' C.M. PIPE CULVERT  
LT. SIDE DRAIN  
REMOVE

STA. 203+78 IN PLACE  
18" X 17' C.M. PIPE CULVERT  
LT. SIDE DRAIN  
REMOVE

STA. 204+35 IN PLACE  
DROP INLET ON LT.  
AND 18" X 25' R.C. PIPE OUTLET  
REMOVE

STA. 204+54 IN PLACE  
DROP INLET ON LT.  
AND 18" X 79' R.C. PIPE CULVERT  
LT. CROSS DRAIN  
REMOVE

STA. 204+79 IN PLACE  
DROP INLET ON LT.  
AND 18" X 45' R.C. PIPE OUTLET  
REMOVE

STA. 204+96 IN PLACE  
DROP INLET ON LT.  
AND 18" X 48' C.M. PIPE INLET  
AND 18" X 18' R.C. PIPE OUTLET  
REMOVE

STA. 205+23 IN PLACE  
DROP INLET ON LT.  
LT. SIDE DRAIN  
REMOVE

STA. 101+28 CONSTRUCT  
JUNCTION BOX ON RT.  
JUNCTION BOX H = 4'-3"  
TYPE E JUNCTION BOX = 3' X 3'

ALL R.C. PIPE CULVERTS SHALL BE  
CLASS III UNLESS OTHERWISE SPECIFIED.  
FOR ALL R.C. PIPE CULVERT INSTALLATIONS  
USE TYPE 3 BEDDING UNLESS OTHERWISE SPECIFIED.  
FOR ALL SLPPCS PIPE CULVERT INSTALLATIONS  
USE TYPE 2 BEDDING UNLESS OTHERWISE SPECIFIED.

STA. 103+91 CONSTRUCT  
DROP INLET ON LT.  
AND 18" X 14' PIPE OUTLET  
CONNECT TO DROP INLET @ STA. 103+75  
DROP INLET H = 3'-9"  
TYPE MO DROP INLET = 4' DIA.  
TYPE C DROP INLET = 4' X 3'  
18" R.C. PIPE = 14 LIN. FT.  
18" SLPPCS PIPE = 14 LIN. FT.

STA. 207+50 CONSTRUCT  
DROP INLET ON LT.  
WITH 8' EXTENSION  
AND 18" X 218' PIPE OUTLET  
CONNECT TO DROP INLET @ STA. 205+28  
DROP INLET H = 3'-8"  
TYPE MO DROP INLET = 4' DIA.  
TYPE C DROP INLET = 4' X 3'  
18" R.C. PIPE = 218 LIN. FT.  
18" SLPPCS PIPE = 218 LIN. FT.

STA. 207+76 CONSTRUCT  
JUNCTION BOX ON LT.  
AND 18" X 6' PIPE INLET WITH F.E.S.  
AND 18" X 26' PIPE OUTLET  
CONNECT TO DROP INLET @ STA. 207+50  
JUNCTION BOX H = 3'-9"  
TYPE E JUNCTION BOX = 3' X 3'  
18" R.C. PIPE = 32 LIN. FT.  
18" SLPPCS PIPE = 26 LIN. FT.

STA. 206+61 IN PLACE  
18" X 19' R.C. PIPE CULVERT  
LT. SIDE DRAIN  
REMOVE AND CONSTRUCT  
APPROACH ON LT. = 5 CU. YD.

STA. 103+13 CONSTRUCT  
APPROACH ON LT. = 5 CU. YD.

STA. 102+42 CONSTRUCT  
APPROACH ON LT. = 5 CU. YD.

STA. 206+61 IN PLACE  
18" X 19' R.C. PIPE CULVERT  
LT. SIDE DRAIN  
REMOVE AND CONSTRUCT  
APPROACH ON LT. = 5 CU. YD.

ROUNDABOUT  
P.I. = N.A.  
Δ = 360°00'00" RT.  
T = 45'  
L = N.A.  
P.C. = 0+00.00  
P.T. = 2+82.74  
NO SUPER

STA. 205+28 CONSTRUCT  
DROP INLET ON LT.  
WITH 4' EXTENSION  
AND 18" X 60' PIPE OUTLET  
CONNECT TO DROP INLET @ STA. 103+91  
DROP INLET H = 4'-2"  
TYPE MO DROP INLET = 4' DIA.  
TYPE C DROP INLET = 4' X 3'  
18" R.C. PIPE = 60 LIN. FT.  
18" SLPPCS PIPE = 60 LIN. FT.

**STA. 101+07.27**  
**BEGIN HWY. 34**  
**LOG MILE 7.29**

STA. 103+45 CONSTRUCT  
DROP INLET ON RT.  
AND 18" X 76' PIPE OUTLET  
CONNECT TO DROP INLET @ STA. 204+00  
DROP INLET H = 4'-11"  
TYPE MO DROP INLET = 4' DIA.  
TYPE C DROP INLET = 4' X 3'  
18" R.C. PIPE = 76 LIN. FT.  
18" SLPPCS PIPE = 76 LIN. FT.

STA. 102+73 CONSTRUCT  
APPROACH ON RT. = 5 CU. YD.

STA. 202+75 IN PLACE  
18" X 36' C.M. PIPE CULVERT  
LT. SIDE DRAIN  
REMOVE AND CONSTRUCT  
APPROACH ON LT. = 5 CU. YD.

STA. 202+25 IN PLACE  
18" X 16' C.M. PIPE CULVERT  
LT. SIDE DRAIN  
REMOVE AND CONSTRUCT  
APPROACH ON LT. = 5 CU. YD.

STA. 202+75 IN PLACE  
18" X 36' C.M. PIPE CULVERT  
LT. SIDE DRAIN  
REMOVE AND CONSTRUCT  
APPROACH ON LT. = 5 CU. YD.

STA. 202+25 IN PLACE  
18" X 16' C.M. PIPE CULVERT  
LT. SIDE DRAIN  
REMOVE AND CONSTRUCT  
APPROACH ON LT. = 5 CU. YD.

STA. 201+76 IN PLACE  
18" X 16' C.M. PIPE CULVERT  
LT. SIDE DRAIN  
REMOVE AND CONSTRUCT  
APPROACH ON LT. = 5 CU. YD.

STA. 201+45 CONSTRUCT  
DROP INLET ON LT.  
WITH 4' EXTENSION  
AND 18" X 16' PIPE OUTLET  
CONNECT TO JUNCTION BOX @ STA. 201+29  
DROP INLET H = 3'-5"  
TYPE MO DROP INLET = 4' DIA.  
TYPE C DROP INLET = 4' X 3'  
18" R.C. PIPE = 16 LIN. FT.  
18" SLPPCS PIPE = 16 LIN. FT.

STA. 201+29 CONSTRUCT  
JUNCTION BOX ON LT.  
AND 18" X 16' PIPE INLET WITH F.E.S.  
AND 18" X 4' PIPE OUTLET  
CONNECT TO EXIST. 18" X 28' R.C. PIPE  
JUNCTION BOX H = 3'-4"  
TYPE E JUNCTION BOX = 3' X 3'  
18" R.C. PIPE = 20 LIN. FT.

STA.	STA.	SIDE	TYPE	LIN. FT.
202+44	203+41	LT.	5' C.L.	77

STA. 206+84 CONSTRUCT  
APPROACH ON RT. = 5 CU. YD.

STA. 205+73 CONSTRUCT  
APPROACH ON RT. = 5 CU. YD.

STA. 205+28 CONSTRUCT  
DROP INLET ON RT.  
WITH 4' EXTENSION  
AND 18" X 38' PIPE OUTLET  
CONNECT TO DROP INLET @ STA. 205+28 LT.  
DROP INLET H = 3'-9"  
TYPE MO DROP INLET = 4' DIA.  
TYPE C DROP INLET = 4' X 3'  
18" R.C. PIPE (CLASS V) = 38 LIN. FT.

STA. 106+00 CONSTRUCT  
APPROACH ON LT. = 5 CU. YD.

STA. 106+35 CONSTRUCT  
APPROACH ON LT. = 5 CU. YD.

STA. 107+09 CONSTRUCT  
APPROACH ON LT. = 5 CU. YD.

STA. 107+09 CONSTRUCT  
APPROACH ON LT. = 5 CU. YD.

STA. 106+06 CONSTRUCT  
APPROACH ON RT. = 5 CU. YD. UNCL. EXC.

STA. 203+27 CONSTRUCT  
APPROACH ON RT. = 5 CU. YD.

STA. 202+60 CONSTRUCT  
APPROACH ON RT. = 5 CU. YD.

STA. 203+27 CONSTRUCT  
APPROACH ON RT. = 5 CU. YD.

STA. 201+67.50 CONSTRUCT  
DROP INLET ON RT.  
WITH 4' EXTENSION  
AND 22" X 14" X 34' ARCH PIPE OUTLET  
CONNECT TO DROP INLET @ STA. 201+45  
DROP INLET H = 3'-5"  
TYPE MO DROP INLET = 4' DIA.  
TYPE C DROP INLET = 4' X 3'  
22" X 14" R.C. ARCH PIPE (CLASS V) = 34 LIN. FT.

STA. 201+67.50 CONSTRUCT  
DROP INLET ON RT.  
WITH 4' EXTENSION  
AND 22" X 14" X 34' ARCH PIPE OUTLET  
CONNECT TO DROP INLET @ STA. 201+45  
DROP INLET H = 3'-5"  
TYPE MO DROP INLET = 4' DIA.  
TYPE C DROP INLET = 4' X 3'  
22" X 14" R.C. ARCH PIPE (CLASS V) = 34 LIN. FT.

STA. 201+17.21  
**BEGIN JOB 100878**  
**BEGIN HWY. 49**  
**LOG MILE 5.40**

HWY. 34  
P.I. = 108+78.65  
Δ = 17°45'40" LT.  
D = 18'00'00"  
T = 49.73'  
L = 98.67'  
P.C. = 108+28.92  
P.T. = 109+27.59  
NO SUPER

HWY. 34  
P.I. = 107+13.41  
Δ = 36°10'31" RT.  
D = 18'00'00"  
T = 103.96'  
L = 200.97'  
P.R.C. = 106+09.45  
P.T. = 108+10.42  
NO SUPER

HWY. 34  
P.I. = 107+13.41  
Δ = 36°10'31" RT.  
D = 18'00'00"  
T = 103.96'  
L = 200.97'  
P.R.C. = 106+09.45  
P.T. = 108+10.42  
NO SUPER

HWY. 34  
P.I. = 107+13.41  
Δ = 36°10'31" RT.  
D = 18'00'00"  
T = 103.96'  
L = 200.97'  
P.R.C. = 106+09.45  
P.T. = 108+10.42  
NO SUPER

HWY. 34  
P.I. = 107+13.41  
Δ = 36°10'31" RT.  
D = 18'00'00"  
T = 103.96'  
L = 200.97'  
P.R.C. = 106+09.45  
P.T. = 108+10.42  
NO SUPER

HWY. 34  
P.I. = 107+13.41  
Δ = 36°10'31" RT.  
D = 18'00'00"  
T = 103.96'  
L = 200.97'  
P.R.C. = 106+09.45  
P.T. = 108+10.42  
NO SUPER

HWY. 34  
P.I. = 107+13.41  
Δ = 36°10'31" RT.  
D = 18'00'00"  
T = 103.96'  
L = 200.97'  
P.R.C. = 106+09.45  
P.T. = 108+10.42  
NO SUPER

HWY. 34  
P.I. = 107+13.41  
Δ = 36°10'31" RT.  
D = 18'00'00"  
T = 103.96'  
L = 200.97'  
P.R.C. = 106+09.45  
P.T. = 108+10.42  
NO SUPER

HWY. 34/HWY. 49/ROUNDBOUT

8/10/2020 R100878.DGN





**GENERAL NOTES:**

1. ALL ELECTRICAL WORK SHALL BE PERFORMED IN ACCORDANCE WITH NATIONAL ELECTRICAL CODE (NFPA 70, CURRENT EDITION), LIFE SAFETY CODE (NFPA 101, CURRENT EDITION), UNDERGROUND FACILITIES DAMAGE PREVENTION ACT (§14-271-101 ET SEQ.), AND LOCAL ELECTRICAL CODE. IN ADDITION, ALL PARTS OF THIS INSTALLATION SHALL BE IN ACCORDANCE WITH THE ARKANSAS DEPARTMENT OF TRANSPORTATION STANDARD SPECIFICATIONS FOR HIGHWAY CONSTRUCTION, CURRENT EDITION.
2. PRIOR TO CONSTRUCTION, THE CONTRACTOR SHALL PROVIDE DOCUMENTATION TO PROJECT ENGINEER, TO ENSURE ARKANSAS STATE CODES (§17-28-101 ET SEQ. AND §20-31-101 ET SEQ.) ARE MET. THE DOCUMENTATION SHALL INCLUDE:
  - (1) ELECTRICIANS' LICENSE INFORMATION AND EXPIRATION DATE.
  - (2) THE RATIO OF LICENSED-ELECTRICIAN-TO-APPRENTICE-ELECTRICIANS.
  - (3) PRINTED SEARCH RESULT OF LICENSED ELECTRICIANS FROM ARKANSAS DEPARTMENT OF LABOR ELECTRICIAN LICENSEE DIRECTORY (<https://www.ark.org/labor/electrician/search.php>)
 ALL LICENSES SHALL BE VALID AND CURRENT.
3. THE CONTRACTOR SHALL NOT ENGAGE IN EXCAVATION OR DEMOLITION ACTIVITIES WITHOUT HAVING FIRST NOTIFIED THE ARKANSAS ONE CALL CENTER IN ACCORDANCE WITH UNDERGROUND FACILITIES DAMAGE PREVENTION ACT. NOT ALL UTILITY COMPANIES ARE MEMBERS OF THE ARKANSAS ONE CALL SYSTEM. THE CONTRACTOR IS ADVISED TO CONTACT ALL NON-MEMBER UTILITIES AS WELL AS THE ONE CALL CENTER.
4. UNDERGROUND UTILITIES EXIST WITHIN AND ADJACENT TO THE LIMITS OF CONSTRUCTION. SOME UTILITES MAY HAVE BEEN RELOCATED SINCE THE TIME OF DESIGN AND THE CONTRACTOR'S NOTICE TO PROCEED. THE CONTRACTOR SHALL CONTACT THE UTILITY COMPANIES INVOLVED AND VERIFY THE LOCATIONS OF UNDERGROUND UTILITIES. THE CONTRACTOR SHALL MAINTAIN THE UTILITY LOCATION MARKINGS UNTIL IT IS NO LONGER NECESSARY.
5. THE CONTRACTOR SHALL BE RESPONSIBLE FOR ALL COSTS OF REPAIR OR REPLACEMENT OF EXISTING UTILITES DAMAGED DURING THE CONSTRUCTION.
6. ANY EQUIPMENT OR APPURTENANCE THAT INTERFERES WITH THE PROPOSED CONSTRUCTION AND WHICH MAYBE THE PROPERTY OF UTILITY SERVICE ORGANIZATIONS SHALL BE MOVED BY THE OWNERS UNLESS OTHERWISE PROVIDED.
7. CONDUIT INSTALLED UNDER ROADWAY SURFACES SHALL BE INSTALLED BY A PUSHING OR BORING METHOD OR AS DIRECTED BY ENGINEER. PVC OR HDPE CONDUIT SHALL BE USED. PVC CONDUIT SHALL BE MARKED "DIR. BORING" OR "DIRECTIONAL BORING" AS PER NEC.
8. NON-DESTRUCTIVE MEG TEST AND CURRENT LEAKAGE TEST SHALL BE PERFORMED ON NEW CONDUCTORS, IN THE PRESENCE OF FIELD INSPECTOR. THE TEST VOLTAGE SHALL BE LIMITED TO 600 VOLTS. ANY CONDUCTOR NOT MEETING THE MINIMUM ACCEPTABLE VALUE SHALL BE REPLACED AT THE CONTRACTOR'S EXPENSE USING NEW CONDUCTOR. THE RESULTS SHALL BE DOCUMENTED AND PROVIDED TO THE JOB ENGINEER. THE CONTRACTOR SHALL BE RESPONSIBLE FOR ALL DAMAGES CAUSED BY MEG TEST WHILE DEVICES OR ACCESSORIES ARE STILL CONNECTED AND SHALL BE REPLACED AT CONTRACTOR'S EXPENSE. SEE SPECIAL PROVISION ELECTRICAL CONDUCTORS-IN-CONDUIT.
9. PULL BOX LIDS SHALL CLOSE FLUSH WITHOUT PINCHING ANY CONDUCTORS. CONDUIT LENGTHS IN PULL BOXES SHALL BE SET ACCORDINGLY. ANY CONDUCTORS THAT HAVE BEEN DAMAGED BY PINCHING SHALL BE COMPLETELY REPLACED AT CONTRACTOR'S EXPENSE.
10. EACH ROADWAY ILLUMINATION POLE SHALL BE BONDED TO EQUIPMENT GROUNDING CONDUCTOR PER NEC. SEE ARTICLES 250 AND 410.
11. ALL ELECTRICAL COMPONENTS SHALL BE UL LISTED.
12. ALL LUMINAIRE ASSEMBLIES SHALL HAVE BUG RATING OF U0.
13. BEFORE FINAL ACCEPTANCE, CONTRACTOR SHALL PROVIDE 2 SETS OF LEDGER SIZE (11" X 17") AS-BUILT PLANS TO THE MAINTENANCE AUTHORITY AND ARDOT.
14. PULL CABLE SHALL BE MINIMUM 1/4" PULL NYLON OR POLYESTER ROPE, OR 1200 LBS PULL TAPE WHEN PULLING CONDUCTORS. STEEL CABLE OR FISH TAPE SHALL NOT BE USED. CONNECT PULLING DEVICES TO COPPER WIRE AND NOT TO JACKET. USE PULLING COMPOUND PER MANUFACTURER'S REQUIREMENTS. ALL BENDS SHALL NOT BE LESS THAN RECOMMENDED BY NEC FOR CONDUCTORS USED.
15. ALL CONCRETE PULL BOXES SHALL BE TYPE 2 HD UNLESS OTHERWISE INDICATED ON THE PLANS.
16. SLACK CABLES IN PULL BOXES SHALL BE 3 FEET.

DATE REVISED	DATE FILED	DATE REVISED	DATE FILED	FED. RD. DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.			
							JOB NO. 100878	26 45

② ILLUMINATION NOTES AND QUANTITIES

**SUMMARY OF QUANTITIES**

ITEM NO.	ITEM	QUANTITIES TOTAL	UNIT
SP	ELECTRICAL CONDUCTORS-IN-CONDUIT (2C/8 A.W.G., E.G.C.)	1187	LIN. FT.
SP	ELECTRICAL CONDUCTORS-IN-CONDUIT (2C/12 A.W.G., E.G.C.)	573	LIN. FT.
710	NON-METALLIC CONDUIT (2")	1228	LIN. FT.
711	CONCRETE PULL BOX (TYPE 2 HD)	15	EACH
SP	SERVICE POINT ASSEMBLY (2 CIRCUITS)	1	EACH
SP	LED ROADWAY ILLUMINATION POLE (6,000 LUMENS, COBRA HEAD, SHOE BASE, 30')	12	EACH



LOCATION: HWY. 49/HWY. 34  
 CITY: MARMADUKE  
 COUNTY: GREENE  
 DISTRICT: 10 SCALE: N/A DRAWN BY: PC

DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.			
							JOB NO. 100878	27 45

2 ILLUMINATION TABLES

LUMINAIRE SCHEDULE								
POLE NO.	NORTHING	EASTING	STA.	OFFSET (FT)	CENTER LINE	POLE HT. (FT)	POLE ARM (FT)	ORIENTATION ANGLE (PLAN NORTH = 0°, CLOCKWISE ROTATION)
POLE A-1	678626.62	1789233.59	106+95.28	22.88	HWY. 34	30	8	0°
POLE A-2	678598.69	1789121.20	105+75.45	26.37		30	8	345°
POLE A-3	678580.01	1789046.75	204+14.05	56.36	HWY. 49	30	8	310°
POLE A-4	678521.86	1789014.56	203+55.68	24.56		30	8	270°
POLE A-5	678389.72	1789011.87	202+23.53	22.77		30	8	270°
POLE A-6	678566.75	1788947.66	204+00.11	42.65		30	8	40°
POLE A-7	678595.73	1788873.11	103+33.11	22.77	HWY. 34	30	8	0°
POLE A-8	678599.97	1788756.05	102+14.42	22.68		30	8	0°
POLE B-1	678675.64	1789028.00	205+05.57	36.86	HWY. 49	30	8	220°
POLE B-2	678662.80	1788946.87	204+92.78	44.27		30	8	130°
POLE B-3	678777.80	1789014.32	206+07.74	23.25		30	8	270°
POLE B-4	678888.98	1789014.15	207+18.92	23.15		30	8	270°
SERVICE POINT	678593.94	1789119.76	105+73.24	30.72	HWY. 34	N/A	N/A	N/A

ELECTRICAL SERVICE DATA								
CIRCUIT ID	LOCATION	SERVICE VOLTAGE	SERVICE CONDUIT SIZE	SERVICE CONDUCTORS	MAIN CIRCUIT BREAKER	BRANCH CIRCUIT BREAKER	BRANCH CIRCUIT (AMPS)	KVA LOAD
A	NORTHING 678593.94 EASTING 1789119.76	240V, SINGLE PHASE	2" NMC	2C/8 A.W.G., E.G.C.	2P/100A	2P/10A	1.84	0.44
B		240V, SINGLE PHASE	2" NMC	2C/8 A.W.G., E.G.C.		2P/10A	0.92	0.22

VOLTAGE DROP, CIRCUIT A, 2C/8AWG, EGC									
SEGMENT	VOLTAGE	PHASE	SETS	CONDUCTOR	CURRENT	Z/1000ft	LENGTH	VD	% VD
SP TO POLE A-2	240	1	1	8	0.23	0.78	12	0.00	0.00
POLE A-2 TO POLE A-1	240	1	1	8	0.46	0.78	110	0.08	0.03
POLE A-2 TO POLE A-3	240	1	1	8	0.69	0.78	75	0.08	0.03
POLE A-3 TO POLE A-4	240	1	1	8	0.92	0.78	66	0.09	0.04
POLE A-4 TO POLE A-5	240	1	1	8	1.15	0.78	117	0.21	0.09
POLE A-4 TO POLE A-6	240	1	1	8	1.38	0.78	105	0.23	0.09
POLE A-6 TO POLE A-7	240	1	1	8	1.61	0.78	80	0.20	0.08
POLE A-7 TO POLE A-8	240	1	1	8	1.84	0.78	118	0.34	0.14
TOTAL									0.51

NOTE: NEC 230.31(B) STATES MINIMUM UNDERGROUND SERVICE CONDUCTOR SIZE TO BE 8 AWG.

VOLTAGE DROP, CIRCUIT B, 2C/8AWG, EGC									
SEGMENT	VOLTAGE	PHASE	SETS	CONDUCTOR	CURRENT	Z/1000ft	LENGTH	VD	% VD
SP TO POLE B-1	240	1	1	8	0.23	0.78	185	0.07	0.03
POLE B-1 TO POLE B-2	240	1	1	8	0.46	0.78	110	0.08	0.03
POLE B-1 TO POLE B-3	240	1	1	8	0.69	0.78	112	0.12	0.05
POLE B-3 TO POLE B-4	240	1	1	8	0.92	0.78		0.00	0.00
TOTAL									0.11

NOTE: NEC 230.31(B) STATES MINIMUM UNDERGROUND SERVICE CONDUCTOR SIZE TO BE 8 AWG.

ILLUMINATION STATISTICS				
DESCRIPTION	AVERAGE (FC)	MAXIMUM (FC)	MINIMUM (FC)	AVG/MIN
ROUNDAABOUT	1.0	1.6	0.3	3.3:1
HWY. 34 EAST	0.7	1.2	0.3	2.3:1
HWY. 34 WEST	0.6	1.2	0.2	3.0:1
HWY. 49 NORTH	0.7	1.2	0.3	2.3:1
HWY. 49 SOUTH	0.6	1.3	0.2	3.0:1
CROSSWALK EAST	1.2	1.4	0.9	1.3:1
CROSSWALK WEST	1.3	1.4	1.2	1.1:1
CROSSWALK NORTH	0.9	1.1	0.7	1.3:1
CROSSWALK SOUTH	1.5	1.7	1.2	1.3:1

- NOTE:
- CALCULATIONS WERE BASED ON 0.87 LIGHT LOSS FACTOR.
  - ILLUMINATION VALUES FOR ROUNDAABOUT AND HIGHWAYS REPRESENT HORIZONTAL ILLUMINANCE.
  - ILLUMINATION VALUES FOR CROSSWALKS REPRESENT VERTICAL ILLUMINANCE.

ILLUMINATION DESIGN CRITERIA		
DESCRIPTION	AVG. (FC)	AVG/MIN
ROUNDAABOUT	0.7	6:1
ROADWAY	0.7	4:1


- NOTE:
- DESIGN BASIS FOR ROADWAY LIGHTING WERE AASHTO ROADWAY LIGHTING DESIGN GUIDE, 7TH ED.
  - DESIGN BASIS FOR ROUNDAABOUT WERE IESNA RP-8-18, LOCAL/LOCAL FOR A ROUNDAABOUT ON NON-CONTINUOUSLY LIGHTED ROADWAYS.



LOCATION: HWY. 49/HWY. 34  
 CITY: MARMADUKE  
 COUNTY: GREENE  
 DISTRICT: 10 SCALE: N/A DRAWN BY: PC


DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. DIST. NO.	STATE	FED. PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.			
						JOB NO. 100878	28	45

2 ILLUMINATION LAYOUT



**LIGHTING NOTES:**

- FOR LUMINAIRE ORIENTATION AND X-Y COORDINATES OF POLES, SEE LUMINAIRE SCHEDULE.
- UNLESS OTHERWISE INDICATED, PULL BOX (TYPE 2 HD) SHALL BE INSTALLED WITHIN 5' OF POLE FOUNDATION.
- INSTALL 2#12 XHHW-2, 1#12 E.G.C. FROM PULL BOX TO LUMINAIRES.
- INSTALL CONDUIT BELL END FITTINGS ON NON-METALLIC CONDUIT ENDS. THE COST OF FITTINGS SHALL BE CONSIDERED SUBSIDIARY TO THE PAY ITEM, "NON-METALLIC CONDUIT (2)".
- THE DEGREE OF TILT ON LUMINAIRES SHALL BE ZERO.
- ALL SPLICES SHALL BE WATERTIGHT AND UL-LISTED FOR CONTINUOUS USE IN SUBMERSIBLE INSTALLATIONS.
- USE MINIMUM 1/4" PULL ROPE OR 1200 LBS. PULL TAPE WHEN PULLING CONDUCTORS.
- E.G.C. SHALL BE EXOTHERMICALLY BONDED TO GROUND ROD.
- CONDUCT A MINIMUM 14-DAY BURN TEST FOR THE COMPLETE LIGHTING SYSTEM. REPLACE BURNED OUT AND NOTICEABLY DIM LUMINAIRES; MALFUNCTIONING EQUIPMENT SHALL BE CORRECTED, AND RETEST THE SYSTEM. OTHERWISE REMOVE AND REPLACE WITH NEW EQUIPMENT.
- SEE STANDARD DRAWING SD-6 FOR PULL BOX CONSTRUCTION.




LOCATION: HWY. 49/HWY. 34  
 CITY: MARMADUKE  
 COUNTY: GREENE  
 DISTRICT: 10 SCALE: 1" = 60' DRAWN BY: PC

MAINT\_100878 Lighting.dgn 1/23/2020

DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. DIST. NO.	STATE	FED. PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.			
						JOB NO. 100878	29	45

ILLUMINATION DETAILS




NOTES:

- LUMINAIRE POLES SHALL MEET THE REQUIREMENTS OF 90 MPH WIND ZONE WITH A 1.3 GUST FACTOR ON THE AASHTO STANDARD SPECIFICATIONS FOR STRUCTURAL SUPPORTS FOR HIGHWAY SIGNS LUMINAIRES AND TRAFFIC SIGNALS, 2001 EDITION WITH 2003 AND 2006 INTERIMS.
- STEEL LUMINAIRE POLES SHALL BE A MINIMUM OF 11 GAUGE. STEEL LUMINAIRE POLES SHALL BE HOT-DIPPED GALVANIZED. OTHER DIMENSIONS PER MANUFACTURER'S RECOMMENDATION AS NECESSARY TO MEET THE REQUIREMENTS OF THE SP - LED ROADWAY ILLUMINATION POLE.
- LUMINAIRE POLES SHALL BE FABRICATED FROM ASTM A572 GRADE 50 OR 65 STEEL.
- POLE CAP OR TENON CAP SHALL BE PROVIDED.
- ANCHOR BOLTS SHALL MEET THE REQUIREMENTS OF SECTION 714 OF THE STANDARD SPECIFICATIONS. THE TOP 8" OF ALL ANCHOR BOLTS SHALL BE GALVANIZED PER ASTM M232. ANCHOR BOLTS IN FOUNDATIONS SHALL BE 1.25" X 30" FOR MOUNTING HEIGHT OF 40' OR GREATER, 1" X 30" FOR MOUNTING HEIGHT LESS THAN 40'. ANCHOR BOLTS SHALL HAVE TOP END THREADED NOT LESS THAN 5" AND FURNISHED WITH GALVANIZED HEX NUTS, LOCK WASHERS, AND TEMPLATE. THE LOWER END OF THE BOLT SHALL BE THREADED AND FURNISHED WITH HEX NUT AND TEMPLATE.




MINIMUM 3' FROM THE FACE OF CURB SEE LUMINAIRE SCHEDULE




ANCHOR BOLT DETAIL


COBRA HEAD LUMINAIRE WITH SHOE BASE



PLAN



POLE FOUNDATION/PULL BOX WIRING DETAIL




ROADWAY LUMINAIRE POLE FOUNDATION



LOCATION:	HWY. 49/HWY. 34
CITY:	MARMADUKE
COUNTY:	GREENE
DISTRICT:	10
SCALE:	N/A
DRAWN BY:	PC


DATE REVISED	DATE FILED	DATE REVISED	DATE FILED	FED. RD. DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.			
						JOB NO. 100878	30	45

2 ILLUMINATION DETAILS




NOTE:  
 1. NYLON BUSHINGS SHALL BE INSERTED INTO ALL GRSC ENTERING CABINETS.  
 2. USE MINIMUM 1/4" PULL ROPE OR 1200 LBS. PULL TAPE WHEN PULLING CONDUCTORS.

LUMINAIRE SERVICE POINT ASSEMBLY  
 120V/240 VAC LUMINAIRE SERVICE POINT ASSEMBLY  
 FOR ROADWAY LIGHTING



ONE-LINE DIAGRAM



TYPICAL WIRING FOR LUMINAIRE  
 THREE-WIRE CIRCUIT-CENTER GROUNDED  
 LUMINAIRE SERVED AT 240 VAC.  
 (120/240 VOLT SERVICE)  
 LUMINAIRE WIRING SCHEMATICS





- KEYED NOTES:
- FUSED CONNECTOR - SHALL BE WATERTIGHT, UL-LISTED, AND DESIGNED AS BREAKAWAY (HOMAC FLOOD-SEAL, EATON BUSSMANN OR EQUAL). USE A FUSED CONNECTOR FOR THE LINE WIRE ON ALL POLES. USE MANUFACTURER'S RECOMMENDED FUSE SIZE.
  - UN-FUSED CONNECTOR - SHALL BE WATERTIGHT AND SHALL BE DESIGNED AS BREAKAWAY (HOMAC FLOOD-SEAL, EATON BUSSMANN, OR EQUAL).



LOCATION: HWY. 49/HWY. 34  
 CITY: MARMADUKE  
 COUNTY: GREENE  
 DISTRICT: 10 SCALE: N/A DRAWN BY: PC

DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. RD. DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.			
						JOB NO. 100878	31	45





② CROSS SECTIONS



R100878.DGN 2/3/2020

DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. RD. DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.			
				JOB NO.	100878		32	45

② CROSS SECTIONS




R100878.DGN 2/3/2020



DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. RD. DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.			
						JOB NO. 100878	33	45


② CROSS SECTIONS



R100878.DGN 2/3/2020

DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. RD. DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.			
						JOB NO. 100878	34	45

② CROSS SECTIONS






2/3/2020  
R100878.DGN

HWY. 49  
 STA. 204+00 TO STA. 204+00

DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. RD. DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.			
						JOB NO. 100878	35	45

2 CROSS SECTIONS



CUT AREA 24 SQ.FT.  
FILL AREA 3 SQ.FT.  
STAGE 1

CUT AREA 33 SQ.FT.  
FILL AREA 0 SQ.FT.  
STAGE 2

CUT AREA 12 SQ.FT.  
FILL AREA 17 SQ.FT.  
STAGE 4

STA. 204+93.15 C.L. HWY. 49 =  
STA. 2+47.63 C.L. ROUNDABOUT  
ELEV. 287.73

CUT VOLUME 0 CU.YD.  
FILL VOLUME 0 CU.YD.  
STAGE 1

CUT VOLUME 0 CU.YD.  
FILL VOLUME 0 CU.YD.  
STAGE 2




CUT VOLUME 0 CU.YD.  
FILL VOLUME 0 CU.YD.  
STAGE 4

HWY. 49  
STA. 205+00 TO STA. 205+68

2/3/2020  
R100878.DGN

DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. RD. DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.			
						JOB NO. 100878	36	45




2 CROSS SECTIONS



R100878.DGN 2/3/2020

DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. RD. DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.			
				JOB NO.	100878		37	45




② CROSS SECTIONS



2/3/2020  
R100878.DGN

DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. RD. DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.			
						JOB NO. 100878	38	45





② CROSS SECTIONS



R100878.DGN 2/3/2020

DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. RD. DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.			
				JOB NO.	100878		39	45




2 CROSS SECTIONS



RI00878.DGN 2/3/2020

DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. RD. DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.			
				JOB NO.	100878		40	45

② CROSS SECTIONS






R100878.DGN 2/3/2020



DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. RD. DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.			
						JOB NO. 100878	41	45




② CROSS SECTIONS



R100878.DGN 2/3/2020

DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. RD. DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.			
						JOB NO. 100878	42	45

2 CROSS SECTIONS




HWY. 34  
 STA. 103+57 TO STA. 103+91

2/3/2020 R100878.DGN

DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. RD. DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.			
						JOB NO.	100878	43

② CROSS SECTIONS







2/3/2020  
R100878.DGN

HWY. 34  
STA. 104+00 TO STA. 104+00

DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. RD. DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.			
						JOB NO. 100878	44	45




2 CROSS SECTIONS



2/3/2020  
R100878.DGN


DATE REVISED	DATE FILMED	DATE REVISED	DATE FILMED	FED. RD. DIST. NO.	STATE	FED. AID PROJ. NO.	SHEET NO.	TOTAL SHEETS
				6	ARK.			
				JOB NO.	100878		45	45

② CROSS SECTIONS




HWY. 34  
STA. 107+90.88 TO STA. 108+90.88


R100878.DGN 2/3/2020




TYPE A




TYPE B-1




TYPE C



TYPE B-2




TYPE E-1




TYPE E-2


CONCRETE COMBINATION CURB AND GUTTER




DETAIL OF GUTTER SLOPE  
GUTTER SHALL BE CONSTRUCTED ON 2% SLOPE AWAY FROM ROADWAY, REGARDLESS OF ROADWAY SLOPE.



TYPE A




TYPE B



TYPE C


INTEGRAL CURB




LONGITUDINAL SECTION

ELEVATION


ALTERNATE CONSTRUCTION METHOD FOR INTEGRAL CURB




TYPE A



TYPE B




TYPE D



TYPE E

CONCRETE CURB



NOTE: USE MODIFIED CURB AS SPECIFIED ON STD. DR-1. COMPENSATION FOR MODIFIED CURB WILL BE CONSIDERED INCLUDED IN THE PRICE BID FOR THE TYPE OF CURB OR CURB AND GUTTER SPECIFIED.


DETAILS OF MODIFIED CURB

DATE	REVISION	DATE FILMED
11-29-07	REVISED GUTTER SLOPE & MODIFIED CURB DETAILS	
11-10-05	ADDED DETAILS OF TYPE E CURBS	
11-16-01	REVISED CONCRETE CURB TYPE B	
11-18-98	REVISED MODIFIED CURB	
6-2-94	ADDED NOTE TO SPECIAL MODIFIED CURB	
8-5-93	CORRECTED GUTTER SLOPE	8-5-93
10-1-92	ADDED DETAILS OF GUTTER SLOPE	10-1-92
5-24-90	ADDED DETAILS OF MODIFIED CURB	5-24-90
11-30-89	VARIABLE DEPTH TYPE A & B 1	11-30-89
7-15-88	REVISED MODIFIED CURB	630-7-15-88
1-1-73	REVISED MODIFIED CURB	500-1-1-73
10-2-72	REVISED AND REDRAWN	512-10-2-72

ARKANSAS STATE HIGHWAY COMMISSION


CURBING DETAILS

STANDARD DRAWING CG-1




LONGITUDINAL JOINT

NOTE: THE TIE BAR SUPPORT SHOWN ABOVE MAY BE ELIMINATED IF OTHER APPROVED METHODS FOR PLACING AND SUPPORTING THE TIE BARS ARE PROVIDED.  
TIE BARS SHALL BE 15' FROM TRANSVERSE JOINTS.



ROUND STEEL BAR DOWEL  
1 1/4" DIA. WHEN T < 10"  
1 1/2" DIA. WHEN T ≥ 10"


NOTE: EACH DOWEL TO BE COATED ACCORDING TO SECTION 502 OF THE STANDARD SPECIFICATIONS.




ONE-HALF 24' PAVEMENT  
12 DOWELS  
PLAN

NOTE: FOR 20' PAVEMENT USE 20 DOWELS @ 12' CTRS. WITH 6" SPACING FROM C.L. AND EDGE OF SLAB TO FIRST BAR. FOR 15' PAVEMENT USE 15 DOWELS @ 12' CTRS. WITH 6" SPACING FROM C.L. AND EDGE OF SLAB TO FIRST BAR. FOR 26' PAVEMENT USE 26 DOWELS @ 12' CTRS. WITH 6" SPACING FROM C.L. AND EDGE OF SLAB TO FIRST BAR. FOR PAVEMENT WIDTHS OTHER THAN THOSE SHOWN ABOVE, USE DOWELS AT 12' CTRS. WITH 6" MAX. SPACING FROM C.L. TO FIRST BAR. DISTANCE FROM EDGE OF SLAB TO FIRST BAR SHALL BE ADJUSTED TO MAINTAIN 12" DOWEL BAR SPACING

CONTRACTION JOINT DETAILS



DETAIL OF SAWED CONTRACTION JOINT




DETAIL OF EXPANSION JOINT

JOINT CONFIGURATION FOR TYPE 3 OR 4 JOINT SEALANT


JOINT WIDTH	SEALANT THICKNESS ①	BACKER ROD DIAMETER	BACKER ROD PLACEMENT DEPTH ②
INCHES			
1/4	1/4	3/8	1/2
3/8	1/4	1/2	1/2
1/2	1/4	5/8	1/2
5/8	3/8	3/4	3/4
3/4	3/8	7/8	3/4
1 1/2	3/4	2	1 1/4

JOINT CONFIGURATION FOR TYPE 5 JOINT SEALANT

JOINT WIDTH	SEALANT THICKNESS ①	BACKER ROD DIAMETER	BACKER ROD PLACEMENT DEPTH ②
INCHES			
1/4	1/2	3/4	3/4
3/8	3/4	1/2	1




PLAN SHOWING EXPANSION JOINTS AT BRIDGE APPROACH SLABS




ELEVATION

NOTE: ALL DOWEL BARS SHALL CONFORM TO THE DETAILS FOR CONTRACTION JOINTS.



\*NOTE: T/3 SAW CUT NOT REQUIRED FOR LONGITUDINAL CONSTRUCTION JOINT.

DETAIL OF SAWED LONGITUDINAL JOINT AND LONGITUDINAL CONSTRUCTION JOINT





DETAIL OF JOINT SUPPORT FOR EXPANSION JOINTS


REINFORCING SHALL BE GRADE 40 OR GRADE 60 DEFORMED BARS.

GENERAL NOTES

- \*T\* DENOTES THICKNESS OF SLAB.
- DOWEL BARS SHALL BE PLACED IN ACCORDANCE WITH THE DIMENSIONS SHOWN. A TOLERANCE OF PLUS OR MINUS ONE INCH WILL BE ALLOWED FOR THE VERTICAL AND LATERAL PLACEMENT AND A TOLERANCE OF PLUS OR MINUS 1/4" WILL BE ALLOWED FOR THE TILT AND SKEW. DOWEL BARS SHALL BE FIELD COATED FOR A MINIMUM DISTANCE OF 2" GREATER THAN HALF THE LENGTH OF THE BAR WITH AN APPROVED GREASE AS A BOND BREAKER JUST PRIOR TO PLACEMENT OF CONCRETE.
- THE EXPANSION JOINT SUPPORT MAY BE CONSTRUCTED WITH CLASS "A", "S" OR PAVING CONCRETE. PAYMENT FOR THE JOINT SUPPORT SHALL BE FOR THE CONTRACT UNIT PRICE BID FOR THE CLASS OF CONCRETE SPECIFIED IN THE PLANS. PAYMENT FOR ALL OTHER WORK AND MATERIALS REQUIRED FOR THE CONSTRUCTION OF THE JOINT SUPPORT SHALL BE INCLUDED IN THE PRICE BID FOR THE ABOVE ITEMS.
- CONTRACTION JOINTS SHALL BE CONSTRUCTED ON 15' CENTERS.
- TOOLING NOT REQUIRED FOR SELF-LEVELING SILICONE.
- UNLESS OTHERWISE SPECIFIED IN THE PLANS, CONCRETE SHOULDERS SHALL BE CONSTRUCTED ACCORDING TO THE DETAILS SHOWN HEREON. CONTRACTION JOINTS SHALL MATCH CONTRACTION JOINTS IN THE LANES.
- TIE WIRES IN DOWEL BAR ASSEMBLIES SHALL NOT BE CUT PRIOR TO PLACEMENT OF PAVING CONCRETE.



LONGITUDINAL CONSTRUCTION JOINT  
NOTE: TIE BARS SHALL BE 15' FROM TRANSVERSE JOINTS.



SECTION


TRANSVERSE CONSTRUCTION JOINT

DATE	REVISION	DATE FILMED
11-07-19	REV. EXP. JOINT REF ON APP. SLAB	
5-25-06	ADDED GENERAL NOTE 7	
10-9-03	REMOVED TIE BAR COATING & REVISED GENERAL NOTES	
11-16-01	ADDED TOOL SEALANT AND NOTE 5; REVISED NOTE 3	
4-26-96	REVISED CONTRACTION JOINT NOTE	
11-3-94	ADDED NOTE RE: REINF. BARS	
4-1-93	REVISED DOWEL BARS & GEN. NOTES	4-1-93
10-1-92	REVISED DOWEL SPACING	10-1-92
8-15-91	ADDED SPAC FOR CONTR JTS & DEL KEYWAY	
05-24-90	REVISED TIE BAR, DOWEL & JOINT SIZE	
01-25-90	ADDED EXPANSION JOINT	01-25-90
11-30-89	CHANGED T/4+1 TO T/3+1	11-30-89
03-23-89	ALTERED SAWED JOINT & ADDED NOTE	512-03-23-89
07-15-88	REVISED AND REDRAWN	632-07-15-88


ARKANSAS STATE HIGHWAY COMMISSION

TRANSVERSE & LONGITUDINAL JOINTS FOR CONCRETE PAVEMENT (NON-REINFORCED)


STANDARD DRAWING CPTJ - 6A



PLAN VIEW



ISOMETRIC VIEW




EXTENSION TYPICAL SECTIONS

- 1: CONCRETE - 6" P.C. CONCRETE DRIVEWAY
- 2: ASPHALT - 2" ACHM SURFACE COURSE (1/2")  
4" ACHM BINDER COURSE (1") OR  
4" ACHM BASE COURSE (1-1/2")
- 3: ASPHALT - 2" ACHM SURFACE COURSE (1/2")  
7" AGGREGATE BASE COURSE
- 4: AGGREGATE - 6" AGGREGATE BASE COURSE


THE TYPE OF EXTENSION SHALL BE AS SHOWN IN THE PLANS. THE CONTRACTOR MAY, WITH THE APPROVAL OF THE ENGINEER, SUBSTITUTE A LOWER NUMBERED TYPE OF EXTENSION IN LIEU OF THE TYPE SPECIFIED IN THE PLANS, BUT AT NO ADDITIONAL COST TO THE DEPARTMENT.

DRIVEWAY EXTENSION DETAILS




DRIVEWAY VERTICAL ALIGNMENT DETAILS


NOTE: DRIVEWAYS MAY NOT BE SLOPED AWAY FROM THE ROADWAY UNLESS APPROVED BY THE ENGINEER.



SECTION A-A



SECTION B-B  
CURBED ISLAND BEHIND WALK




CURBED ISLANDS FOR CHANNELIZATION


REFER TO PLANS FOR TYPE OF CURB FACE TO BE USED. NO DIRECT PAYMENT WILL BE MADE FOR THE CURB FACES SHOWN ON THE ISLAND DETAILS. PAYMENT FOR THE CURB FACE WILL BE INCLUDED IN THE UNIT PRICE BID FOR THE ITEM "CONCRETE ISLAND".

DATE	REV	DATE FILMED	DESCRIPTION
11-07-19			REVISED WALK DETAILS
2-27-14			REVISED PLAN & ISOMETRIC VIEW
11-29-07			ADDED CHANNELIZATION ISLAND WITH TYPE C CURB FACE & REVISED DRIVEWAY SLOPE NOTE & VERTICAL ALIGNMENT DETAIL
11-10-05			REV. APRON SLOPE & DEPTH OF AGG. BASE.
8-22-02			ADDED ISLAND DETAILS & NOTES
3-30-00			REV. MOD. CURB WIDTH & TRANS. NOTE
11-19-98			REVISED NOTES
11-18-98			REDRAWN AND REISSUED







TYPICAL PIPE CULVERT WITH FLARED END SECTION & 3:1 FORESLOPE



TYPICAL PIPE CULVERT WITH FLARED END SECTION & FLATTENED ADJACENT SLOPES



TYPICAL MULTIPLE PIPE CULVERT WITH FLARED END SECTIONS & FLATTENED ADJACENT SLOPES



PLAN VIEW 3:1 FORESLOPES

R.C. CURTAIN WALL DIMENSIONS & QUANTITIES


PIPE DIA.	H <sub>1</sub>	L <sub>1</sub>	L	L (DBL.) / 2	SINGLE R.C.P.C.		DOUBLE R.C.P.C.	
					CONC. CU. YDS.	REINF. STEEL LBS.	CONC. CU. YDS.	REINF. STEEL LBS.
18"	11 1/2"	3'-5"	8'-0"	6'-3"	0.31	27.7	0.45	39.5
24"	1'-0 1/2"	4'-6"	9'-6"	7'-6"	0.37	33.4	0.53	48.0
30"	1'-3 1/2"	5'-7"	11'-0"	9'-0"	0.45	39.0	0.67	59.0
36"	1'-7"	6'-8"	13'-0"	10'-6"	0.58	52.6	0.83	73.9
42"	2'-1 1/2"	7'-3"	15'-6"	12'-0"	0.82	77.1	1.10	100.7
48"	2'-5"	7'-10"	17'-0"	13'-0"	0.98	94.9	1.27	120.4
54"	2'-9 1/2"	8'-5"	18'-6"	14'-0"	1.16	115.8	1.47	143.7
60"	3'-4"	9'-0"	20'-6"	15'-6"	1.47	149.7	1.84	180.3
72"	4'-5"	10'-2"	25'-6"	18'-6"	2.31	232.6	2.73	271.0

NOTE: QUANTITIES SHOWN ARE FOR ONE (1) CURTAIN WALL.

REINFORCING STEEL SCHEDULE


PIPE DIA.	SINGLE R.C. PIPE CULVERT								DOUBLE R.C. PIPE CULVERT									
	H401		H402		V401		V402		H401		H402		H403		V401		V402	
	L	NO.	L	NO.	L	NO.	L	NO.	L	NO.	L	NO.	L	NO.	L	NO.	L	NO.
18"	7'-8"	2	1'-11 1/2"	4	1'-7 1/2"	8	8"	8	12'-2"	2	1'-11 1/2"	4	8"	2	1'-7 1/2"	10	8"	14
24"	9'-2"	2	2'-2"	4	1'-8 1/2"	10	8"	9	14'-8"	2	2'-2"	4	8"	2	1'-8 1/2"	12	8"	18
30"	10'-8"	2	2'-4 1/2"	4	1'-11 1/2"	10	8"	12	17'-8"	2	2'-4 1/2"	4	8"	2	1'-11 1/2"	14	8"	22
36"	12'-8"	2	2'-10"	6	2'-3"	12	8"	14	20'-8"	2	2'-10"	6	8"	3	2'-3"	14	8"	28
42"	15'-2"	2	3'-9 1/2"	8	2'-9 1/2"	16	8"	15	23'-8"	2	3'-9 1/2"	8	8"	4	2'-9 1/2"	18	8"	30
48"	16'-8"	2	4'-3"	10	3'-1"	18	8"	16	25'-8"	2	4'-3"	10	8"	5	3'-1"	20	8"	32
54"	18'-2"	2	4'-8 1/2"	12	3'-5 1/2"	20	8"	17	27'-8"	2	4'-9"	12	8"	6	3'-5 1/2"	22	8"	34
60"	20'-2"	2	5'-5"	14	4'-0"	24	8"	18	30'-8"	2	5'-5"	14	8"	7	4'-0"	26	8"	36
72"	25'-2"	2	7'-4"	18	5'-1"	30	8"	20	36'-8"	2	7'-4"	18	8"	9	5'-1"	33	8"	40

ALL REINFORCING STEEL #4 BARS @ 6" O.C.



NOTE: THE PORTION OF THE R.C. CURTAIN WALL BENEATH THE FLARED END SECTION (LOWER 1'-0") SHALL BE PLACED MONOLITHICALLY. THE FLARED END SECTION SHALL THEN BE SET IN PLACE & THE REMAINING PORTIONS OF THE R.C. CURTAIN WALL PLACED.

R.C. CURTAIN WALL DETAILS



NOTE: THE PRECAST CURTAIN WALL WILL BE SET AND BACKFILLED WITH COMPACTED MATERIAL. THE FLARED END SECTION SHALL THEN BE SET IN PLACE AND THE 1" RECESS FILLED WITH GROUT. WHERE "L" EXCEEDS 11' THE CURTAIN WALL MAY BE CAST IN TWO (2) OR MORE SECTIONS. THE METHOD OF JOINING THE SECTIONS FOR INSTALLATION SHALL BE APPROVED BY THE ENGINEER.


SOLID SODDING

PIPE DIA.	SINGLE R.C.P.C.						DOUBLE R.C.P.C.					
	3:1	4:1	6:1	3:1	4:1	6:1	3:1	4:1	6:1	3:1	4:1	6:1
18"	5	7	12	6	8	13	5	7	12	6	8	13
24"	8	12	19	9	13	20	8	12	19	9	13	20
30"	13	18	29	14	19	30	13	18	29	14	19	30
36"	17	26	41	18	28	43	17	26	41	18	28	43
42"	23	35	55	25	37	57	23	35	55	25	37	57
48"	29	46	68	31	48	70	29	46	68	31	48	70
54"	35	57	85	37	59	87	35	57	85	37	59	87
60"	45	62	104	48	65	107	45	62	104	48	65	107
72"	64	92	156	67	95	159	64	92	156	67	95	159


NOTE: QUANTITIES SHOWN ABOVE ARE FOR ONE (1) END OF F.E.S.

GENERAL NOTES

1. A CAST-IN-PLACE OR PRECAST CURTAIN WALL MAY BE USED. PAYMENT FOR THE CURTAIN WALL SHALL BE CONSIDERED TO BE INCLUDED IN THE UNIT PRICE BID EACH FOR FLARED END SECTIONS OF THE SEVERAL SIZES, WHICH PRICE SHALL BE FULL COMPENSATION FOR FURNISHING ALL MATERIALS INCLUDING REINFORCING STEEL AND CONCRETE; FOR FORMS, MIXING AND PLACING; FOR EXCAVATION AND BACKFILL; AND FOR ALL LABOR, TOOLS, EQUIPMENT AND INCIDENTALS NECESSARY TO COMPLETE THE WORK.
2. ALL EXPOSED EDGES SHALL BE CHAMFERED 3/4".
3. CONCRETE FOR CURTAIN WALL SHALL MEET THE REQUIREMENTS FOR CLASS A OR S CONCRETE AS PROVIDED IN SECTION 802 OF THE STANDARD SPECIFICATIONS OR FOR PAVING CONCRETE AS PROVIDED IN SECTION 501 OF THE STANDARD SPECIFICATIONS.
4. WELDED WIRE MESH 3 x 3 W/10 x W/10 MAY BE USED IN LIEU OF REINFORCING BARS.




END VIEW




SECTIONAL VIEW "X-X"

10-18-96	ADDED NOTE TO SOLID SODDING		ARKANSAS STATE HIGHWAY COMMISSION
10-12-95	CORRECTED SPELLING		
11-3-94	ADDED GENERAL NOTE NO. 4		
8-15-91	REV. CURTAIN WALL QUANT. STEEL SCH. & SOLID SOD QUANT.		
3-2-81	ALLOW PRECAST IN 2 OR MORE PIECES CHAMFER EDGES		
5-15-80	ADDED PRECAST WALL & GENERAL NOTES		
10-2-72	REVISED AND REDRAWN		
DATE	REVISION	FILMED	STANDARD DRAWING FES-1



### TABLE OF DIMENSIONS




DIA.	WALL	A	B	C	D	E	S	DIA. + 1"	P	R-1	R-2	G-T	WT.	h
18"	2 1/2"	9"	2'-3"	3'-10"	6'-1"	3'-0"	3:1	19"	29"	15 1/2"	12"	2"	1000	1'-0 1/2"
24"	3"	9 1/2"	3'-7 1/2"	2'-6"	6'-1 1/2"	4'-0"	3:1	25"	33 3/8"	16 1/8"	14"	2 1/2"	1600	1'-1 1/2"
30"	3 1/2"	1'-0"	4'-6"	1'-7 3/4"	6'-1 3/4"	5'-0"	3:1	31"	37"	18 1/2"	15"	3 1/4"	1940	1'-4 5/8"
36"	4"	1'-3"	5'-3"	2'-10 3/4"	8'-1 3/4"	6'-0"	3:1	37"	47 1/8"	24 1/8"	20"	3 1/2"	4100	1'-8"
42"	4 1/2"	1'-9"	5'-3"	2'-11"	8'-2"	6'-6"	3:1	43"	53 3/8"	27 1/2"	22"	3 1/2"	5380	2'-2 1/2"
48"	5"	2'-0"	6'-0"	2'-2"	8'-2"	7'-0"	3:1	49"	56 1/2"	28 1/2"	22"	3 1/2"	6550	2'-6"
54"	5 1/2"	2'-4"	6'-6"	1'-10"	8'-4"	7'-6"	3:1	55"	65 1/2"	33 3/8"	24"	4"	8750	2'-10 1/2"
60"	6"	2'-10"	6'-6"	1'-10"	8'-4"	8'-0"	3:1	61"	72 1/2"	36 1/8"	24"	4"	9270	3'-5"
72"	7"	3'-10"	6'-6"	1'-10"	8'-4"	9'-0"	3:1	73"	77 3/8"	38 3/8"	24"	5"	13250	4'-6"



### ARCH PIPE

EQUIV. DIA.	• SPAN		• RISE		W	A	B	C	D	E	P	R2	G-T	S
	AASHTO M 206	AHD NOMINAL	AASHTO M 206	AHD NOMINAL										
INCHES														
15	18	18	11	11	2"	4"	2'-0"	4'-0"	6'-0"	3'-0"	29"	12"	1 1/2"	2 1/2:1
18	22	22	13 1/2	14	2 1/2"	5"	2'-0"	4'-1"	6'-1"	3'-6"	32 1/8"	13"	2 1/2"	2 1/2:1
21	26	26	15 1/2	16	2 3/4"	7"	2'-3"	3'-10"	6'-1"	4'-0"	34 1/8"	14"	2 1/2"	2 1/2:1
24	28 1/2	29	18	18	3"	9"	2'-3"	3'-10"	6'-1"	5'-0"	36 3/8"	15"	2 1/2"	2 1/2:1
30	36 1/4	36	22 1/2	23	3 1/2"	10"	3'-1"	3'-0 1/2"	6'-1 1/2"	6'-0"	47 1/8"	20"	3"	2 1/2:1
36	43 3/4	44	26 3/8	27	4"	10 1/2"	4'-0"	2'-11 1/2"	6'-1 1/2"	6'-6"	54 3/8"	22"	3 1/2"	2 1/2:1
42	51 1/8	51	31 3/8	31	4 1/2"	11 1/2"	4'-7"	1'-10 1/4"	6'-5 1/4"	7'-2"	59 1/2"	23"	3 3/4"	2 1/2:1
48	58 1/2	59	36	36	5"	1'-3"	5'-3"	2'-10 3/4"	8'-1 3/4"	7'-10"	70 3/8"	24"	4 1/4"	2 1/2:1
54	65	65	40	40	5 1/2"	1'-7"	5'-3"	2'-11"	8'-2"	8'-6"	72 1/8"	24"	4 3/4"	2 1/2:1
60	73	73	45	45	6"	1'-10"	5'-6"	2'-8"	8'-2"	9'-0"	77 3/8"	24"	5"	2 1/2:1

• THE MEASURED SPAN AND RISE SHALL NOT VARY MORE THAN ± 2 PER CENT FROM THE VALUES SPECIFIED BY AASHTO M 206.




### CIRCULAR PIPE

D. DIA.	GAUGE	A	B. MAX.	H	L	W	S
12	16	6	6	6	21	24	2 1/2:1
15	16	7	8	6	26	30	2 1/2:1
18	16	8	10	6	31	36	2 1/2:1
21	16	9	12	6	36	42	2 1/2:1
24	16	10	13	6	41	48	2 1/2:1
30	14	12	16	8	51	60	2 1/2:1
36	14	14	19	9	60	72	2 1/2:1
42	12	16	22	11	69	84	2 1/2:1
48	12	18	27	12	78	90	2 1/2:1
54	12	18	30	12	84	102	2:1
60	12	18	33	12	87	114	1 3/4:1
66	12	18	36	12	87	120	1 1/2:1
72	12	18	39	12	87	126	1 1/3:1

### C.M. ARCH PIPE


EQUIV. DIA.	SPAN	RISE	INCHES				S	GAUGE	
			A	B MAX.	H	L			
15"	17	13	7	9	6	19	30	2 1/2:1	16
18"	21	15	7	10	6	23	36	2 1/2:1	16
21"	24	18	8	12	6	28	42	2 1/2:1	16
24"	28	20	9	14	6	32	48	2 1/2:1	16
30"	35	24	10	16	6	39	60	2 1/2:1	14
36"	42	29	12	18	8	46	75	2 1/2:1	14
42"	49	33	13	21	9	53	85	2 1/2:1	12
48"	57	38	18	26	12	63	90	2 1/2:1	12
54"	64	43	18	30	12	70	102	2 1/4:1	12
60"	71	47	18	33	12	77	114	2 1/4:1	12




NOTE: ALTERNATE CONNECTIONS TO THE PIPE CULVERTS, IN ACCORDANCE WITH MANUFACTURER'S STANDARD PRACTICES, MAY BE MADE SUBJECT TO THE APPROVAL OF THE ENGINEER.

### END SECTIONS FOR CORRUGATED METAL PIPE CULVERTS


10-18-96	REVISED ASTM REF. TO AASHTO		ARKANSAS STATE HIGHWAY COMMISSION
5-15-80	REVISED DISTANCE BETWEEN MULTIPLE R.C.P. F.E.S.	664-5-15-80	
7-14-78	C.M. ARCH SIZES TO CONFORM WITH AASHTO SIZES	752-7-14-78	
8-22-75	ADDED MULTIPLE PIPE CULVERTS	517-8-22-75	FLARED END SECTION
12-5-74	REMOVED NOTE RE REINF. FOR R.C. F.E.S.	500-12-5-74	
5-24-73	CMP END SECTION, SHOW PIPE PAY LENGTH	627-5-24-73	
10-2-72	REVISED AND REDRAWN	760-10-2-72	STANDARD DRAWING FES-2
DATE	REVISION	FILMEN	




SECTION B-B



PLAN




PLAN




SECTION A-A

DROP INLET (TYPE E)

NOTE: REINF. BARS TO BE #4 BARS ON 6" CTRS. WITH 1/2" MIN. COVER. THIS TYPE DROP INLET TO BE USED WHERE NOT SUBJECTED TO TRAFFIC.




SECTION B-B




APPROX. WEIGHT = 11 LBS. (CAST IRON)  
 PLAN  
 NOTE: THIS DETAIL IS TYPICAL. OTHERS MAY BE USED WITH PRIOR APPROVAL OF THE ENGINEER.

DETAIL OF STEP FOR DROP INLET




SECTION A-A




SECTION B-B

METHOD OF CONSTRUCTING DROP INLET ON EXISTING R.C. BOX CULVERT




HEAVY DUTY RING & COVER


APPROXIMATE TOTAL WEIGHT = 333 LBS.



RING SECTION




PLAN




SECTION A-A

JUNCTION BOX (TYPE E)


NOTE: REINF. BARS TO BE #4 BARS ON 6" CTRS. WITH 1/2" MIN. COVER. THIS TYPE JUNCTION BOX TO BE USED WHERE NOT SUBJECTED TO TRAFFIC.



SECTION B-B




SECTION A-A




SECTION B-B

METHOD OF CONSTRUCTING DROP INLET ON NEW R.C. BOX CULVERT

NOTE: "C" DIMENSIONS AND REINFORCING BAR SIZES, SHALL CONFORM TO THOSE SHOWN ON STANDARD DRAWING FOR DROP INLET.




SECTION A-A



SECTION B-B


GRATE FOR TYPE E DROP INLET

APPROXIMATE MINIMUM WATERWAY OPENING = 260 SQ. IN.



DETAIL OF YARD DRAIN

NOTE: CONCRETE COLLAR TO BE CAST IN PLACE. 12" PIPE CULVERTS TO BE MEASURED AND PAID FOR AS " 12" SIDE DRAIN "




USE NEENAH R-590I-C OR EQUIVALENT BICYCLE SAFE FRAME AND GRATE

- GENERAL NOTES:
1. ALL EXPOSED CORNERS SHALL BE 3/4" CHAMFERED.
  2. STEPS SHALL BE INSTALLED ON 16" CENTERS ON ALL INLETS 4'-0" HIGH OR OVER, OR AS APPROVED BY THE ENGINEER.
  3. EXPANSION JOINT MATERIAL SHALL BE 3/4" PREFORMED FIBER.
  4. GRATE OR GRATE AND FRAME SHALL BE CONSTRUCTED OF CAST IRON AND SHALL CONFORM TO THE REQUIREMENTS OF THE STANDARD SPECIFICATIONS FOR GRAY IRON CASTINGS AASHTO M 105 CLASS 35B. GRATE MAY BE USED WITHOUT FRAME.
  5. GRATE AND FRAME SHALL NOT BE PAINTED.
  6. GRATE SHALL BE BICYCLE SAFE.
  7. HEAVY DUTY RING SHALL ALWAYS BE INSTALLED WITH FLANGE ON TOP.
  8. HEAVY DUTY RING AND COVER SHALL BE CONSTRUCTED OF CAST IRON AND SHALL CONFORM TO THE REQUIREMENTS OF THE STANDARD SPECIFICATIONS FOR GRAY IRON CASTINGS AASHTO M 105 CLASS 35B & AASHTO M 306.
  9. HEAVY DUTY RING AND COVER SHALL NOT BE PAINTED.
  10. DIMENSIONS SHOWN FOR RING AND COVER ARE TYPICAL. THE CONTRACTOR MAY SUBSTITUTE SIMILAR CASTINGS WITH THE APPROVAL OF THE ENGINEER, REQUESTING APPROVAL FOR CASTING DESIGNS MAY BE MADE BY REFERRING TO PREVIOUSLY APPROVED DRAWINGS.


DATE	REV.	REVISION	DATE FILMED
11-16-01		ADDED NOTE 10	
1-12-00		REVISED HEAVY DUTY RING & COVER	
7-02-98		CHANGED GRATE DETAIL, DELETED DI (TYPE D), REPLACED RING & COVER W/HEAVY DUTY RING & COVER, ADDED JUNCTION BOX (TYPE E)	
6-26-97		ADDED DIMENSION TO TYPE IV-A	
10-18-96		ADDED DETAIL OF YARD DRAIN	
8-15-91		DELETE TYPE IV GRATE	
7-15-88		REVISED STEP DETAIL	
5-20-83		REVISED DETAILS OF GRATES (TYPE IV & IV-A)	
2-4-83		ADDED GENERAL NOTE NO. 4	
3-2-81		ADDED TYPE IV-A GRATE	
5-22-74		DELETED INLET (TYPE F) & GRATE (TYPE III)	
10-2-72		REVISED AND REDRAWN	

ARKANSAS STATE HIGHWAY COMMISSION  
 DETAILS OF DROP INLETS  
 & JUNCTION BOXES  
 STANDARD DRAWING FPC-9







PLAN - W/SINGLE EXTENSION



FRONT ELEVATION




SECTION C-C




HEAVY DUTY RING & COVER

1. HEAVY DUTY RING AND COVER SHALL BE CONSTRUCTED OF CAST IRON AND SHALL CONFORM TO THE REQUIREMENTS OF THE STANDARD SPECIFICATIONS FOR GRAY IRON CASTINGS AASHTO M105 CLASS 35B & AASHTO M306.
2. HEAVY DUTY RING AND COVER SHALL NOT BE PAINTED.
3. HEAVY DUTY RING SHALL ALWAYS BE INSTALLED WITH FLANGE ON TOP.




DETAIL OF NOTCH FOR SIDEWALKS




SECTION A-A

APPROX. WEIGHT = 11 LBS. (CAST IRON)  
PLAN  
NOTE: THIS DETAIL IS TYPICAL. OTHERS MAY BE USED WITH PRIOR APPROVAL OF THE ENGINEER.

DETAIL OF STEP FOR DROP INLET



SECTION B-B




BACK OPENING

WHEN OPENING IN BACK IS CALLED FOR ON PLANS EXTEND OPENING AS SHOWN IN DETAIL. PAYMENT TO BE INCLUDED IN PRICE BID FOR DROP INLET (TYPE MO).

- GENERAL NOTES:
1. ALL EXPOSED CORNERS TO HAVE 3/4" CHAMFER.
  2. STEPS SHALL BE INSTALLED IN ALL INLETS 4'-0" HIGH AND OVER OR AS DIRECTED BY THE ENGINEER.
  3. ALL REINFORCING BARS SHALL BE GRADE 60 AND HAVE MIN. 1/2" COVER.
  4. DROP INLETS AND EXTENSION ON CURVED SECTIONS SHALL CONFORM TO THE CURVATURE OF THE CURB.
  5. 4" DIA. COLUMNS SPACED AT MAX. 4'-0" INTERVALS SHALL BE INSTALLED ALONG INLET AND EXTENSION TO SUPPORT TOP.
  6. BASE AND INLET WALLS SHALL BE CAST MONOLITHICALLY.
  7. THE THROAT SHALL BE CAST INTEGRALLY WITH THE GUTTER.
  8. PAYMENT FOR CURB AND/OR CURB AND GUTTER WITHIN THE LIMITS OF DROP INLETS AND DROP INLET EXTENSIONS SHALL BE CONSIDERED INCLUDED IN PAYMENT MADE FOR DROP INLETS AND/OR DROP INLET EXTENSIONS.
  9. PIPES MAY ENTER DROP INLET FROM ANY ANGLE OR ELEVATION AS MAY BE APPROVED BY THE ENGINEER.
  10. APPROPRIATE SIZE TYPE C DROP INLETS MAY BE SUBSTITUTED FOR TYPE MO DROP INLETS AS APPROVED BY THE ENGINEER. PAYMENT TO BE AS DROP INLET (TYPE MO).
  11. DURING CONSTRUCTION OF THE ROADWAY THE CONTRACTOR SHALL MAINTAIN DRAINAGE INTO OR AROUND THE DROP INLET AS APPROVED BY THE ENGINEER.
  12. 4"x2" NOTCH SHALL BE FORMED IN ALL DROP INLETS TO SUPPORT SIDEWALK CONSTRUCTION. REFER TO DETAIL OF NOTCH FOR SIDEWALKS.
  13. DIMENSIONS SHOWN FOR RING AND COVER ARE TYPICAL. THE CONTRACTOR MAY SUBSTITUTE SIMILAR CASTINGS WITH THE APPROVAL OF THE ENGINEER. REQUESTING APPROVAL FOR CASTING DESIGNS MAY BE MADE BY REFERRING TO PREVIOUSLY APPROVED DRAWINGS.

LEAVE OPENING IN BACK WHEN CALLED FOR ON PLANS REFER TO BACK OPENING DETAIL

MINIMUM WALL THICKNESS			
DIA. OF D.I.	DIA. OF OUTLET PIPE	CAST IN PLACE	PRECAST
4" I.D.	12" THRU 27"	6"	5"
5" I.D.	30" THRU 42"	8"	6"
6" I.D.	48" THRU 54"	8"	7"



SECTION A-A

DATE	REVISIONS	DATE FILMED
8-22-02	ADDED PAY LIMIT CURB NOTES TO SECTIONS A-A & B-B	
11-16-01	ADDED NOTE 13	
1-12-00	REVISED HEAVY DUTY RING & COVER	
5-13-99	ADDED NOTCH DETAIL FOR SIDEWALKS	
7-02-98	REP. NOTE 8, REV. PLAN DET., REV. PICTURE FOR NEW RING & COVER, ADDED HEAVY DUTY RING & COVER AND DETAIL OF STEP FOR DROP INLET	
4-26-96	ADDED NOTE 11 AND OPENING DIMENSION	
10-12-95	CORRECTED #6 BAR SPACING	
7-20-95	CORRECTED DIAMETER OF D.I. IN BOX	
2-2-95	TYPE C TO TWO (OPEN BACK DETAIL)	
11-3-94	REVISED GENERAL NOTES	
4-1-93	REV. BACK OPEN DETAIL & NOTE	11-3-94
8-15-91	REVISED NOTES 11, 12 & ADDED BK. OPEN DETAIL	4-1-93
11-30-89	ADDED NOTE NO. 12	8-15-91
8-23-89	ADDED NOTE & MINIMUM WALL THICKNESS	11-30-89
7-15-88	ADDED EXTEND NOTE TO SECTION A-A	8-23-89
1-14-87	MODIFIED WALL THICKNESS	7-15-88
6-12-87	ISSUED	1-14-87

ARKANSAS STATE HIGHWAY COMMISSION

DETAILS OF DROP INLET (TYPE MO)

STANDARD DRAWING FPC-9M

**REINFORCED CONCRETE ARCH PIPE DIMENSIONS**

EQUIV. DIA.	SPAN		RISE	
	AASHTO M 206	ARDDOT NOMINAL	AASHTO M 206	ARDDOT NOMINAL
INCHES	INCHES			
15	18	18	11	11
18	22	22	13½	14
21	26	26	15½	16
24	28½	29	18	18
30	36¼	36	22½	23
36	43¾	44	26¾	27
42	51½	51	31¾	31
48	58½	59	36	36
54	65	65	40	40
60	73	73	45	45
72	88	88	54	54
84	102	102	62	62
90	115	115	72	72
96	122	122	77½	77
108	138	138	87½	87
120	154	154	96¾	97
132	168¾	169	106½	107

THE MEASURED SPAN AND RISE SHALL NOT VARY MORE THAN ± 2 PERCENT FROM THE VALUES SPECIFIED BY AASHTO M206.

**REINFORCED CONCRETE HORIZONTAL ELLIPTICAL PIPE DIMENSIONS**

EQUIV. DIA.	AASHTO M 207	
	SPAN	RISE
INCHES	INCHES	
18	23	14
24	30	19
27	34	22
30	38	24
33	42	27
36	45	29
39	49	32
42	53	34
48	60	38
54	68	43
60	76	48
66	83	53
72	91	58
78	98	63
84	106	68

THE MEASURED SPAN AND RISE SHALL NOT VARY MORE THAN ± 2 PERCENT FROM THE VALUES SPECIFIED BY AASHTO M207.

**CONSTRUCTION SEQUENCE**

1. PLACE STRUCTURAL BEDDING MATERIAL TO GRADE. DO NOT COMPACT.
2. INSTALL PIPE TO GRADE.
3. COMPACT STRUCTURAL BEDDING OUTSIDE THE MIDDLE THIRD OF THE PIPE.
4. PLACE AND COMPACT THE HAUNCH AREA UP TO THE MIDDLE OF THE PIPE.
5. COMPLETE BACKFILL ACCORDING TO SUBSECTION 606.03.(f)(1).

NOTE: HAUNCH AND STRUCTURAL BEDDING MATERIAL WILL NOT BE PAID FOR SEPARATELY, BUT COMPENSATION WILL BE CONSIDERED TO BE INCLUDED IN THE PRICE BID PER LINEAR FOOT OF CONCRETE PIPE.


**- LEGEND -**

- D<sub>i</sub> = NORMAL INSIDE DIAMETER OF PIPE
- D<sub>o</sub> = OUTSIDE DIAMETER OF PIPE
- H = FILL COVER HEIGHT OVER PIPE (FEET)
- MIN. = MINIMUM
- UNDISTURBED SOIL

INSTALLATION TYPE	MATERIAL REQUIREMENTS FOR HAUNCH AND STRUCTURAL BEDDING
TYPE 1	AGGREGATE BASE COURSE (CLASS 5 OR CLASS 7)
TYPE 2	SELECTED MATERIALS (CLASS SM-1, SM-2, OR SM-4) OR TYPE 1 INSTALLATION MATERIAL*
TYPE 3**	AASHTO CLASSIFICATION A-1 THRU A-6 SOIL OR TYPE 1 OR 2 INSTALLATION MATERIAL

\* SM-3 WILL NOT BE ALLOWED.

\*\* MATERIALS SHALL NOT INCLUDE ORGANIC MATERIALS OR STONES LARGER THAN 3 INCHES.



**EMBANKMENT AND TRENCH INSTALLATIONS**

1. MATERIAL IN THE HAUNCH AND OUTER STRUCTURAL BEDDING SHALL BE COMPACTED TO 95% OF THE MAXIMUM DENSITY ACCORDING TO THE TYPE OR CLASS OF MATERIAL USED.
2. FOR TRENCHES WITH WALLS OF NATURAL SOIL, THE DENSITY OF THE SOIL IN THE LOWER SIDE ZONE SHALL BE AS FIRM AS THE 95% DENSITY REQUIRED FOR THE HAUNCH. IF THE EXISTING SOIL DOES NOT MEET THIS CRITERIA, IT SHALL BE REMOVED AND RECOMPACTED TO 95% OF THE MAXIMUM DENSITY ACCORDING TO THE TYPE OF MATERIAL USED.
3. FOR EMBANKMENTS, THE MATERIAL IN THE LOWER SIDE ZONE SHALL BE COMPACTED TO 95% OF THE MAXIMUM DENSITY ACCORDING TO THE TYPE OR CLASS OF MATERIAL USED.

**GENERAL NOTES**

1. CONCRETE PIPE CULVERT CONSTRUCTION SHALL CONFORM TO ARKANSAS DEPARTMENT OF TRANSPORTATION STANDARD SPECIFICATIONS FOR HIGHWAY CONSTRUCTION (CURRENT EDITION), WITH APPLICABLE SUPPLEMENTAL SPECIFICATIONS AND SPECIAL PROVISIONS. UNLESS OTHERWISE NOTED IN THE PLANS, SECTION AND SUBSECTION REFER TO THE STANDARD CONSTRUCTION SPECIFICATIONS.
2. CONCRETE PIPE CULVERT DESIGN SHALL CONFORM TO AASHTO LRFD BRIDGE DESIGN SPECIFICATIONS, FIFTH EDITION (2010) WITH 2010 INTERIMS.
3. ALL PIPE SHALL CONFORM TO SECTION 606. CIRCULAR R.C. PIPE CULVERTS SHALL CONFORM TO AASHTO M170. R.C. ARCH PIPE CULVERTS SHALL CONFORM TO AASHTO M206 AND HORIZONTAL ELLIPTICAL PIPE CULVERTS SHALL CONFORM TO AASHTO M207.
4. ALL PIPE SHALL BE PROTECTED DURING CONSTRUCTION BY A COVER SUFFICIENT TO PREVENT DAMAGE FROM PASSAGE OF EQUIPMENT.
5. THE MINIMUM TRENCH WIDTH SHALL BE THE OUTSIDE DIAMETER OF THE PIPE PLUS 24 INCHES. THE MAXIMUM ALLOWABLE TRENCH WIDTH SHALL BE THE MINIMUM WIDTH PRACTICABLE FOR WORKING CONDITIONS.
6. MULTIPLE PIPE CULVERTS SHALL BE INSTALLED WITH A MINIMUM CLEARANCE OF 24 INCHES BETWEEN STRINGS OF PIPE. REFER TO STD. DWG. FES-2 FOR MINIMUM CLEARANCE WHERE FLARED END SECTIONS ARE USED.
7. IMPERVIOUS MATERIAL SHOULD BE PLACED AS DIRECTED BY THE ENGINEER AT THE ENDS OF THE CULVERT TO PREVENT LOSS OF STRUCTURAL BEDDING WHEN PERVIOUS MATERIAL IS USED FOR STRUCTURAL BEDDING AND/OR BACKFILL.
8. NOT MORE THAN ONE LIFTING HOLE MAY BE PROVIDED IN CONCRETE PIPE TO FACILITATE HANDLING. HOLE MAY BE CAST IN PLACE, CUT INTO THE FRESH CONCRETE AFTER FORMS ARE REMOVED, OR DRILLED. THE HOLE SHALL NOT BE MORE THAN TWO INCHES IN DIAMETER OR TWO INCHES SQUARE. CUTTING OR DISPLACEMENT OF REINFORCEMENT WILL NOT BE PERMITTED. SPALLED AREAS AROUND THE HOLE SHALL BE REPAIRED IN A WORKMANLIKE MANNER. LIFTING HOLE SHALL BE FILLED WITH MORTAR, CONCRETE, OR OTHER METHOD AS APPROVED BY THE ENGINEER.
9. WHEN DIRECTED BY THE ENGINEER, UNSUITABLE MATERIAL THAT IS ENCOUNTERED AT THE BOTTOM OF THE EXCAVATED TRENCH (BELOW THE AREA IDENTIFIED AS "STRUCTURAL BEDDING" ABOVE) WILL BE EXCAVATED AND REPLACED WITH SELECTED PIPE BEDDING. THE QUANTITY OF MATERIAL REQUIRED TO BACKFILL THE UNDERCUT AREA UP TO THE SELECTED PIPE BEDDING PAY LIMIT DESIGNATED ABOVE WILL BE MEASURED AND PAID FOR AS "SELECTED PIPE BEDDING."
10. WHEN THE EXISTING MATERIAL EXCAVATED FOR THE PIPE TRENCH IS DETERMINED BY THE ENGINEER TO BE UNSUITABLE FOR BACKFILLING THE PIPE (ABOVE THE AREA IDENTIFIED ABOVE AS THE HAUNCH), BORROW MATERIAL OR MATERIAL FROM THE ROADWAY EXCAVATION WILL BE USED TO BACKFILL THE PIPE. IF SUITABLE MATERIAL IS NOT AVAILABLE, THE ENGINEER MAY AUTHORIZE THE USE OF "SELECTED PIPE BACKFILL."

**MINIMUM HEIGHT OF FILL "H" OVER CIRCULAR R.C. PIPE CULVERTS**

INSTALLATION TYPE	CLASS OF PIPE			
	CLASS III	CLASS IV	CLASS V	CLASS V
PIPE ID (IN.)	FEET			
12-15	2	2.5	2	1
18-24	2.5	3	2	1
27-33	3	4	2	1
36-42	3.5	5	2	1
48	4.5	5.5	2	1
54-60	5	7	2	1
66-78	6	8	2	1
84-108	7.5	8	2	1

NOTE: FOR MINIMUM COVER VALUES, "H" SHALL INCLUDE A MINIMUM OF 12" OF PAVEMENT AND/OR BASE.

**MAXIMUM HEIGHT OF FILL "H" OVER CIRCULAR R.C. PIPE CULVERTS**

INSTALLATION TYPE	CLASS OF PIPE		
	CLASS III	CLASS IV	CLASS V
TYPE 1	21	32	50
TYPE 2	16	25	39
TYPE 3	12	20	30

NOTE: IF FILL HEIGHT EXCEEDS 50 FEET, A SPECIAL DESIGN CONCRETE PIPE WILL BE REQUIRED USING TYPE 1 INSTALLATION.

**MINIMUM HEIGHT OF FILL "H" OVER R.C. ARCH & HORIZONTAL ELLIPTICAL PIPE CULVERTS**

INSTALLATION TYPE	CLASS OF PIPE	
	CLASS III	CLASS IV
TYPE 2 OR TYPE 3	FEET	
	2.5	1.5

NOTE: TYPE 1 INSTALLATION WILL NOT BE ALLOWED FOR ARCH & HORIZONTAL ELLIPTICAL PIPE CULVERTS.

NOTE: FOR MINIMUM COVER VALUES, "H" SHALL INCLUDE A MINIMUM OF 12" OF PAVEMENT AND/OR BASE.

**MAXIMUM HEIGHT OF FILL "H" OVER R.C. ARCH & HORIZONTAL ELLIPTICAL PIPE CULVERTS**

INSTALLATION TYPE	CLASS OF PIPE	
	CLASS III	CLASS IV
TYPE 2	13	21
TYPE 3	10	16

NOTE: TYPE 1 INSTALLATION WILL NOT BE ALLOWED FOR ARCH & HORIZONTAL ELLIPTICAL PIPE CULVERTS.

DATE	REVISION	DATE FILMED
2-27-14	REVISED GENERAL NOTE 1.	
12-15-11	REVISED FOR LRFD DESIGN SPECIFICATIONS	
5-18-00	REVISED TYPE 3 BEDDING & ADDED NOTE	
3-30-00	REVISED INSTALLATIONS	
11-06-97	ISSUED	

**ARKANSAS STATE HIGHWAY COMMISSION**

**CONCRETE PIPE CULVERT FILL HEIGHTS & BEDDING**

STANDARD DRAWING PCC-1



**CORRUGATED STEEL PIPE (ROUND)**

PIPE DIAMETER (INCHES)	① MINIMUM COVER TOP OF PIPE TO TOP OF GROUND "H" (FEET)	MAX. FILL HEIGHT "H" ABOVE TOP OF PIPE (FEET)				
		METAL THICKNESS (INCHES)				
		0.064	0.079	0.109	0.138	0.168
2 3/8 INCH BY 1/2 INCH CORRUGATION RIVETED, WELDED, OR HELICAL LOCK-SEAM						
12	1	84	91			
15	1	67	73			
18	1	56	61			
24	1	42	46	59		
30	2	34	36	47		
36	2		30	39	41	73
42	2		43	67	70	
48	2		37	58	61	64
3 INCH BY 1 INCH OR 5 INCH BY 1 INCH CORRUGATION RIVETED, WELDED, BOLTED, OR HELICAL LOCK-SEAM						
36	1	48	60	88	111	118
42	1	41	51	72	90	102
48	1	36	45	64	77	85
54	2	32	40	59	71	79
60	2	29	36	53	64	71
66	2	26	33	47	58	64
72	2	24	30	44	53	59
78	2		28	41	49	54
84	2		26	38	45	51
90	2		24	35	43	45
96	2		22	33	40	44
102	2			31	38	42
108	2			30	35	39
114	2			28	34	37
120	2			27	32	35

**CONSTRUCTION SEQUENCE**

1. PLACE STRUCTURAL BEDDING MATERIAL TO GRADE. DO NOT COMPACT.
2. INSTALL PIPE TO GRADE.
3. COMPACT STRUCTURAL BEDDING OUTSIDE THE MIDDLE THIRD OF THE PIPE.
4. COMPLETE STRUCTURAL BACKFILL OPERATION BY WORKING FROM SIDE TO SIDE OF THE PIPE. THE SIDE TO SIDE STRUCTURAL BACKFILL DIFFERENTIAL SHALL NOT EXCEED 24 INCHES OR 1/3 THE SIZE OF THE PIPE, WHICHEVER IS LESS.

NOTE: STRUCTURAL BACKFILL AND STRUCTURAL BEDDING MATERIAL WILL NOT BE PAID FOR SEPARATELY, BUT COMPENSATION WILL BE CONSIDERED TO BE INCLUDED IN THE PRICE BID PER LINEAR FOOT OF METAL PIPE.


INSTALLATION TYPE	MATERIAL REQUIREMENTS FOR STRUCTURAL BACKFILL AND STRUCTURAL BEDDING
TYPE 1	AGGREGATE BASE COURSE (CLASS 4, 5, 6, OR 7)
TYPE 2	SELECTED MATERIALS (CLASS SM-1, SM-2, OR SM-4) OR TYPE 1 INSTALLATION MATERIAL ③

③ SM-3 WILL NOT BE ALLOWED.

**- LEGEND -**

- D<sub>o</sub> = OUTSIDE DIAMETER OF PIPE
- MAX. = MAXIMUM
- MIN. = MINIMUM
- [Symbol] = STRUCTURAL BACKFILL MATERIAL
- [Symbol] = UNDISTURBED SOIL
- EQUIV. DIA. = EQUIVALENT DIAMETER
- H = FILL COVER HEIGHT OVER PIPE (FEET)

IN SOIL - MIN. EQUALS TWICE CORRUGATION DEPTH  
IN ROCK - MIN. EQUALS GREATER OF:  
1/2" PER FOOT OF FILL OVER PIPE (24" MAX.)  
TWICE CORRUGATION DEPTH



**EMBANKMENT AND TRENCH INSTALLATIONS**

1. STRUCTURAL BACKFILL, EMBANKMENT, AND OUTER STRUCTURAL BEDDING MATERIAL SHALL BE COMPACTED TO 95% OF THE MAXIMUM DENSITY ACCORDING TO THE TYPE OR CLASS OF MATERIAL USED.
2. INSTALLATION TYPE 1 OR 2 MAY BE USED FOR CORRUGATED STEEL OR ALUMINUM PIPE (ROUND).
3. INSTALLATION TYPE 1 SHALL BE USED FOR CORRUGATED STEEL OR ALUMINUM PIPE ARCHES WITH 2 3/8" X 1/2" CORRUGATION.
4. INSTALLATION TYPE 1 OR 2 MAY BE USED FOR CORRUGATED STEEL OR ALUMINUM PIPE ARCHES WITH 3" X 1" OR 5" X 1" CORRUGATION.

**GENERAL NOTES**

1. METAL PIPE CULVERT CONSTRUCTION SHALL CONFORM TO ARKANSAS DEPARTMENT OF TRANSPORTATION STANDARD SPECIFICATIONS FOR HIGHWAY CONSTRUCTION (CURRENT EDITION), WITH APPLICABLE SUPPLEMENTAL SPECIFICATIONS AND SPECIAL PROVISIONS. UNLESS OTHERWISE NOTED IN THE PLANS, SECTION AND SUBSECTION REFER TO THE STANDARD CONSTRUCTION SPECIFICATIONS.
2. METAL PIPE CULVERT DESIGN SHALL CONFORM TO AASHTO LRFD BRIDGE DESIGN SPECIFICATIONS, FIFTH EDITION (2010) WITH 2010 INTERIMS.
3. METAL PIPE CULVERT MATERIALS AND INSTALLATIONS SHALL CONFORM TO SECTION 606 AND JOB SPECIAL PROVISION "METAL PIPE".
4. ALL PIPE SHALL BE PROTECTED DURING CONSTRUCTION BY A COVER SUFFICIENT TO PREVENT DAMAGE FROM PASSAGE OF EQUIPMENT.
5. THE MINIMUM TRENCH WIDTH SHALL BE THE OUTSIDE DIAMETER OF THE PIPE PLUS 24 INCHES. THE MAXIMUM ALLOWABLE TRENCH WIDTH SHALL BE THE MINIMUM WIDTH PRACTICABLE FOR WORKING CONDITIONS.
6. MULTIPLE PIPE CULVERTS SHALL BE INSTALLED WITH A MINIMUM CLEARANCE OF 24 INCHES BETWEEN STRINGS OF PIPE. REFER TO STD. DWG. FES-2 FOR MINIMUM CLEARANCE WHERE FLARED END SECTIONS ARE USED.
7. IMPERVIOUS MATERIAL SHOULD BE PLACED AS DIRECTED BY THE ENGINEER AT THE ENDS OF THE CULVERT TO PREVENT LOSS OF STRUCTURAL BEDDING WHEN PERVIOUS MATERIAL IS USED FOR STRUCTURAL BEDDING AND/OR BACKFILL.
8. WHEN DIRECTED BY THE ENGINEER, UNSUITABLE MATERIAL THAT IS ENCOUNTERED AT THE BOTTOM OF THE EXCAVATED TRENCH (BELOW THE AREA IDENTIFIED AS "STRUCTURAL BEDDING" ABOVE) WILL BE EXCAVATED AND REPLACED WITH SELECTED PIPE BEDDING. THE QUANTITY OF MATERIAL REQUIRED TO BACKFILL THE UNDERCUT AREA UP TO THE SELECTED PIPE BEDDING PAY LIMIT DESIGNATED ABOVE WILL BE MEASURED AND PAID FOR AS "SELECTED PIPE BEDDING."
9. WHEN THE EXISTING MATERIAL EXCAVATED FOR THE PIPE TRENCH IS DETERMINED BY THE ENGINEER TO BE UNSUITABLE FOR BACKFILLING THE PIPE (ABOVE THE AREA IDENTIFIED AS STRUCTURAL BACKFILL), BORROW MATERIAL OR MATERIAL FROM THE ROADWAY EXCAVATION WILL BE USED TO BACKFILL THE PIPE. IF SUITABLE MATERIAL IS NOT AVAILABLE, THE ENGINEER MAY AUTHORIZE THE USE OF "SELECTED PIPE BACKFILL."

**CORRUGATED ALUMINUM PIPE (ROUND)**

PIPE DIAMETER (INCHES)	① MINIMUM COVER TOP OF PIPE TO TOP OF GROUND "H" (FEET)	MAX. FILL HEIGHT "H" ABOVE TOP OF PIPE (FEET)				
		METAL THICKNESS IN INCHES				
		0.060	0.075	0.105	0.135	0.164
2 3/8 INCH BY 1/2 INCH CORRUGATION RIVETED OR HELICAL LOCK-SEAM						
12	1	45	45			
18	2	30	30	52		
24	2	22	22	39	41	34
30	2		18	31	32	
36	2.5		15	26	27	28
42	2			43	43	44
48	2			40	41	43
54	2			35	37	38
60	2				33	34
66	2					31
72	2					29

**EQUIVALENT METAL THICKNESSES AND GAUGES**

METAL THICKNESS IN INCHES			GAUGE NUMBER
STEEL			
ZINC COATED	UNCOATED	ALUMINUM	
0.064	0.0598	0.060	16
0.079	0.0747	0.075	14
0.109	0.1046	0.105	12
0.138	0.1345	0.135	10
0.168	0.1644	0.164	8

**CORRUGATED METAL PIPE ARCHES**

EQUIV. DIA. (INCHES)	PIPE DIMENSION SPAN X RISE (INCHES)	MINIMUM CORNER RADIUS (INCHES)	STEEL				ALUMINUM			
			MIN. THICKNESS REQUIRED (INCHES)	① MIN. HEIGHT OF FILL, "H" (FT.)		MIN. THICKNESS REQUIRED (INCHES)	① MIN. HEIGHT OF FILL, "H" (FT.)			
				INSTALLATION			INSTALLATION			
				TYPE 1	TYPE 1		TYPE 1	TYPE 1		
2 3/8 INCH BY 1/2 INCH CORRUGATION RIVETED, WELDED, OR HELICAL LOCK-SEAM										
15	17x13	3	0.064	2	15	0.060	2	15		
18	21x15	3	0.064	2	15	0.060	2	15		
21	24x18	3	0.064	2,25	15	0.060	2,25	15		
24	28x20	3	0.064	2,5	15	0.075	2,5	15		
30	35x24	3	0.079	3	12	0.075	3	12		
36	42x29	3 1/2	0.079	3	12	0.105	3	12		
42	49x33	4	0.079	3	12	0.105	3	12		
48	57x38	5	0.109	3	13	0.135	3	13		
54	64x43	6	0.109	3	14	0.135	3	14		
60	71x47	7	0.138	3	15	0.135	3	14		
66	77x52	8	0.168	3	15	0.164	3	15		
72	83x57	9	0.168	3	15					
② 3 INCH BY 1 INCH OR 5 INCH BY 1 INCH CORRUGATION RIVETED, WELDED, OR HELICAL LOCK-SEAM										
			INSTALLATION				INSTALLATION			
			TYPE 2		TYPE 1		TYPE 2		TYPE 1	
36	40x31	5	0.079	3	2	12	15			
42	46x36	6	0.079	3	2	13	15			
48	53x41	7	0.079	3	2	13	15			
54	60x46	8	0.079	3	2	13	15			
60	66x51	9	0.079	3	2	13	15			
66	73x55	12	0.079	3	2	15	15			
72	81x59	14	0.079	3	2	15	15			
78	87x63	14	0.079	3	2	15	15			
84	95x67	16	0.109	3	2	15	15			
90	103x71	16	0.109	3	2	15	15			
96	112x75	18	0.109	3	2	15	15			
102	117x79	18	0.109	3	2	15	15			
108	128x83	18	0.138	3	2	15	15			

① FOR MINIMUM COVER VALUES, "H" SHALL INCLUDE A MINIMUM 12" OF PAVEMENT AND/OR BASE.


② WHERE THE STANDARD 2 2/3" X 1/2" CORRUGATION AND GAUGE IS SPECIFIED FOR A GIVEN DIAMETER, A PIPE OF THE SAME DIAMETER WITH A 3" X 1" OR 5" X 1" CORRUGATION MAY BE SUBSTITUTED, PROVIDING IT IS GAUGED FOR A FILL HEIGHT CONDITION EQUAL TO OR GREATER THAN THE MAXIMUM FILL HEIGHT CONDITION FOR THE SPECIFIED GAUGE AND CORRUGATION.

DATE	REVISION	DATE FILMED
2-27-14	REVISED GENERAL NOTE 1	
12-15-11	REVISED FOR LRFD DESIGN SPECS	
3-30-00	REVISED INSTALLATIONS	
11-06-97	ISSUED	


ARKANSAS STATE HIGHWAY COMMISSION

**METAL PIPE CULVERT  
FILL HEIGHTS & BEDDING**

STANDARD DRAWING PCM-1




CONCRETE PAVEMENT




ASPHALT PAVEMENT


**BROKEN LINE STRIPING**




**SOLID LINE STRIPING ON CONCRETE PAVEMENT**



**SOLID LINE STRIPING ON ASPHALT PAVEMENT**




ASPHALT PAVEMENT




CONCRETE PAVEMENT

**STRIPING AT ADJACENT NO PASSING LANES**



**YIELD LINE DETAIL**




**CROSSWALK AND STOP LINE DETAILS**

**NOTES:**

1. REFER TO THE STRIPING DETAILS FOR PAVEMENT MARKING LINE WIDTHS.
2. THIS DRAWING SHALL BE USED IN CONJUNCTION WITH THE LATEST REVISED ADDITION OF THE "MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES."
3. RAISED PAVEMENT MARKERS SHALL BE PLACED ON AN 80 FEET SPACING UNLESS OTHERWISE SHOWN IN THE PLANS.


2" FOR ASPHALT OR CONCRETE PAVEMENT  
6" FOR BITUMINOUS SURFACE TREATMENT



**PAVEMENT EDGE LINE MARKING**


NOTE:  
THE RED LENS OF THE TYPE II R.P.M. SHALL FACE THE INCORRECT TRAFFIC MOVEMENT.

TYPE II RED/CLEAR OR YELLOW/YELLOW



PRISMATIC REFLECTOR

NOTE:  
DIMENSIONS SHOWN FOR RAISED PAVEMENT MARKERS ARE TYPICAL. THE CONTRACTOR MAY SUBSTITUTE SIMILAR MARKERS WITH THE APPROVAL OF THE ENGINEER. REQUESTING APPROVAL FOR SIMILAR MARKERS MAY BE MADE BY REFERRING TO THE ARDOT QUALIFIED PRODUCTS LIST.



**DETAIL OF STANDARD RAISED PAVEMENT MARKERS**

DATE	REVISION	FILMED
2-27-20	REVISED STOP LINE DETAILS	
6-1-17	ADDED YIELD LINE DETAIL	
5-12-16	REVISED LINE WIDTHS, SPACING, & NOTES	
9-12-13	REVISED DETAIL OF STANDARD RAISED PAVEMENT MARKERS	
11-17-10	REVISED GENERAL NOTES & REMOVED PLOWABLE PVMT MRKRS	
11-18-04	REVISED NOTE 2 & GENERAL NOTES	
8-22-02	ADDED CROSSWALK & STOPBAR DTL.	
7-02-98	ADDED DETAILS OF STD. RAISED PAV'T. MARKERS	
4-26-96	REV. NOTES 3&4; ADDED R.P.M.	
9-30-80	DRAWN	1-9-30-80


ARKANSAS STATE HIGHWAY COMMISSION

**PAVEMENT MARKING DETAILS**


STANDARD DRAWING PM-1




NOTE:  
 1. UNLESS OTHERWISE SPECIFIED ON THE PLANS, THE UNDERDRAIN COVER SHALL BE THOROUGHLY COMPACTED EARTH AND SHALL BE SUBSIDIARY TO PIPE UNDERDRAIN.  
 2. GRANULAR MATERIAL SHALL BE WRAPPED WITH GEOTEXTILE FABRIC, LAP FABRIC 12" OR THE WIDTH OF THE TRENCH AT THE TOP.



PLAN VIEW




SIDE VIEW




DETAIL OF HOLE FOR 4" PIPE

1/4" STAINLESS STEEL BOLT WITH ANCHOR & 1" STAINLESS STEEL WASHER IN APPROX. CENTER OF SCREEN



FRONT VIEW (DETAIL OF RODENT SCREEN)




DETAILS OF PIPE UNDERDRAIN

FERNCO 1056-44 (4" CI/PLASTIC) OR FERNCO 1051-44 (4" AC/DI OR 4" CI/PLASTIC) COUPLING OR EQUAL WITH 2 CLAMPS (TYPICAL)

UNDERDRAIN OUTLET PROTECTORS

FERNCO 1056-44 (4" CI/PLASTIC) OR FERNCO 1051-44 (4" AC/DI OR 4" CI/PLASTIC) COUPLING OR EQUAL WITH 2 CLAMPS (TYPICAL)



NOTE: LATERALS SHALL BE INSTALLED AT ALL SAGS AND AT 250' INTERVALS ON GRADES. THE 250' DISTANCE MAY BE EXCEEDED ONLY WHERE NECESSARY FOR AN ACCEPTABLE OUTLET.

DETAIL OF PIPE UNDERDRAIN LATERALS WHEN PLACED ALONG PAVEMENT EDGE

NOTE: PVC PIPE FOR LATERALS SHALL MEET THE REQUIREMENTS OF ASTM D 1785 (LATEST REVISION) FOR SCHEDULE 40 PIPE.

NOTES FOR PIPE UNDERDRAINS

- GEOTEXTILE FABRIC SHALL MEET THE REQUIREMENTS OF SECTION 625 FOR TYPE I. PAYMENT FOR GEOTEXTILE FABRIC AND GRANULAR FILTER MATERIAL SHALL BE INCLUDED IN THE PRICE BID PER LIN. FT. FOR "4" PIPE UNDERDRAINS" IN ACCORDANCE WITH SECTION 611 OF THE STANDARD SPECIFICATIONS.
- 4" NON-PERFORATED SCHEDULE 40 PVC PIPE LATERALS WITH OUTLET PROTECTORS SHALL BE INSTALLED AS SHOWN HEREON. LATERALS WILL BE MEASURED AND PAID FOR AS "4" PIPE UNDERDRAINS." UNDERDRAIN OUTLET PROTECTORS WILL BE MEASURED AND PAID FOR BY THE UNIT IN ACCORDANCE WITH SECTION 611 OF THE STANDARD SPECIFICATIONS.
- EXISTING 4" PIPE UNDERDRAINS MAY BE CONNECTED TO PROPOSED DROP INLETS OR EXTENDED WHERE DIRECTED BY THE ENGINEER. PAYMENT FOR CONNECTING TO DROP INLETS SHALL BE CONSIDERED INCLUDED IN THE PRICE BID FOR "4" PIPE UNDERDRAINS."
- THE LOCATION OF ALL LATERALS SHALL BE MARKED WITH 4" X 12" PERMANENT PAVEMENT MARKING TAPE (TYPE III WHITE) AT THE OUTSIDE EDGE OF THE SHOULDER, PLACED TRANSVERSE TO TRAFFIC. PAYMENT FOR THIS WORK SHALL BE INCLUDED IN THE PRICE BID FOR THE VARIOUS CONTRACT ITEMS.
- PAYMENT FOR THE RODENT SCREEN SHALL BE INCLUDED IN THE PRICE BID PER EACH FOR "UNDERDRAIN OUTLET PROTECTORS."
- ANY EXISTING UNDERDRAINS THAT INTERFERE WITH INSTALLATION OF THE NEW UNDERDRAIN SYSTEM SHALL BE REMOVED AND DISPOSED OF AS DIRECTED BY THE ENGINEER. PAYMENT WILL BE CONSIDERED INCLUDED IN THE PRICE BID FOR THE VARIOUS CONTRACT ITEMS. EXISTING UNDERDRAIN OUTLET PROTECTORS SHALL BE REMOVED UNDER THE ITEM "REMOVAL AND DISPOSAL OF UNDERDRAIN OUTLET PROTECTORS."
- AT LOCATIONS WHERE A SINGLE LATERAL IS USED THE CONTRACTOR SHALL HAVE THE FOLLOWING OPTIONS: 1. INSTALL OUTLET PROTECTOR AS SHOWN ON STANDARD DRAWING PU-1 AND GROUT THE UNUSED HOLE OR 2. INSTALL AN OUTLET PROTECTOR WITH A SINGLE HOLE.


12-8-16	ADDED NOTES FOR PIPE UNDERDRAINS, REVISED RODENT SCREEN DETAIL AND NOTES, REMOVED NOTE 1 FOR GRANULAR MATERIAL, ADDED NOTE FOR GEOTEXTILE FABRIC	
4-10-03	REVISED NOTE 3	
1-12-00	REVISED DETAIL OF UNDERDRAIN LATERALS	
11-18-98	REVISED NOTE	
10-18-96	REVISED MIN. DEPTH & GEOTEXTILE FABRIC	
4-26-96	ADDED LATERAL NOTE: 5 1/2" TO 5"	
11-22-95	REVISED LATERALS	
7-20-95	REVISED LATERALS & ADDED NOTE	
11-3-94	REVISED FOR DUAL LATERALS	11-3-94
10-1-92	SUBSTITUTED GEOTEXTILE	10-1-92
8-15-91	ADDED POLYETHYLENE PIPE	8-15-91
11-8-90	DELETED ALTERNATE NOTE	11-8-90
1-25-90	ADDED 4" SNAP ADAPTER	1-25-90
11-30-89	DEL. (SUBGRADE); ADDED (WHERE REQUIRED)	11-30-89
7-15-88	ISSUED P.L.M.	647-7-15-88
DATE	REVISION	DATE FILMED

ARKANSAS STATE HIGHWAY COMMISSION


DETAILS OF PIPE UNDERDRAIN

STANDARD DRAWING PU-1


### CONDUIT ENTRY TO EXISTING POLE BASE



### ANCHOR BASE





### CONDUIT ENTRY TO EXISTING CONTROLLER CABINET




NOTE: ENTRY TO CABINET SHALL BE THROUGH A CUT IN THE BASE SUFFICIENT TO PROVIDE ADEQUATE CONDUIT RADIUS FOR ITEM.

### TYPE "HD" CONCRETE PULL BOX DETAIL



NOTE: ALL REINFORCING BARS TO BE GRADE 60


TOP



ELEVATION


NOTE: ALL TYPE 1 AND TYPE 2 HD CONCRETE PULL BOXES ARE INSTALLED WITH AN APRON OF CONCRETE 12" WIDE AND 7" IN DEPTH. ALL PAYMENT SHALL BE INCLUDED IN THE PRICE OF THE TYPE HD CONCRETE PULL BOX. THE CONCRETE PULL BOX SHALL BE INSTALLED FLUSH TO SURROUNDING GRADE UNLESS OTHERWISE INSTRUCTED BY THE ENGINEER. THE CONCRETE SHALL BE CLASS "S". THREE #6 REINFORCING BARS IN THE APRON ON ALL SIDES OF THE CONCRETE PULL BOX IS REQUIRED IN CONCRETE.

DATE	REVISION	FILMED	
11-16-17	REVISED NOTES		
09-02-15	REVISED PULL BOX DEPTH		
09-12-13	ISSUED AS STANDARD DRAWING		
05-21-09	REVISED GROUNDING		
07-31-08	ADDED & REVISED CONDUIT ENTRY		
06-23-04	REVISED CLEARANCE AT CURB ENTRY		
01-04-02	ADDED REINFORCING TO BOX APRON		
07-02-01	REVISED		
12-27-99	REVISED NOTES		
11-18-98	ISSUED		
			ARKANSAS STATE HIGHWAY COMMISSION
			HEAVY DUTY PULL BOX
			STANDARD DRAWING SD-6



NOTE: MAX FILL HEIGHT ABOVE TOP OF BOX = 13'-0".


STEEL SCHEDULE			
BARS	NUMBER	LENGTH	SPACING
"A"	12	6'-0"	10"
"B"	20	5'-0"	10 1/2"
"C"	16	5'-0"	12"




QUANTITIES  
 "A" BARS 5'-0"  
 CONCRETE 3.31 CU. YDS.  
 REINFORCING STEEL 168 LB.

GENERAL NOTE:  
 THE PAY ITEMS FOR REINFORCED CONCRETE SPRING BOXES SHALL BE FOR THE QUANTITIES OF CONCRETE OF THE CLASS SPECIFIED, REINFORCING STEEL, EXCAVATION FOR STRUCTURES AND 18" R.C. PIPE CULVERT.

**REINFORCED CONCRETE SPRING BOX**




PAVEMENT REPAIR OVER CULVERTS (CONCRETE)



PAVEMENT REPAIR OVER CULVERTS (ASPHALT)

**DETAIL SHOWING REPAIR OF EXISTING PAVEMENT AT CULVERT INSTALLATIONS**




DETAIL OF HAND RAILING SET IN CONCRETE


POST CONNECTION TO WALL

BASE PLATE

**POST CONNECTION DETAILS**



HAND RAILING SHALL CONFORM TO SECTION 633.




POST CONNECTION TO WALL

BASE PLATE

**DETAILS OF ALTERNATE POST ANCHOR SYSTEM (EPOXY ADHESIVE ANCHORS)**

**HAND RAILING DETAILS**



**DETAILS OF CONCRETE STEPS & WALKS**














































GENERAL NOTES  
 1. RISE AND TREAD DIMENSIONS OF STEPS MAY BE VARIED AS DIRECTED BY THE ENGINEER, HOWEVER, TREAD WIDTHS SHALL BE 11" MIN. ALL STEPS IN A FLIGHT SHALL HAVE CONSISTENT TREAD & RISER DIMENSIONS.  
 2. 1" TRANSVERSE EXPANSION JOINTS SHALL BE PLACED IN CONCRETE WALKS AT 45' INTERVALS.

DATE	REVISION	DATE FILMED
10-25-18	REVISED DETAIL SHOWING REPAIR OF EXISTING PAVEMENT AT CULVERT INSTALLATIONS	
9-12-13	REVISED REINFORCED CONCRETE SPRING BOX	
7-26-12	REMOVED RETAINING WALL DETAILS & REVISED HAND RAILING DETAILS	
4-17-08	REV. JOINT & FOOTING STEP DETAILS	
11-29-07	REVISED RETAINING WALL DRAINAGE	
5-25-06	REVISED PVMT REPAIR OVER CULVERTS (CONC); REVISED REINFORCED CONG SPRING BOX	
10-9-03	REVISED PIPE RAILING DETAILS TO HAND RAILING DETAILS	
4-10-03	REVISED RETAINING WALL DRAWING	
8-22-02	ADDED HAND RAILING DETAIL	
11-16-01	REVISED PVMT REPAIR OVER CULVERTS (CONC); CORRECTED SPELLING IN GENERAL NOTES	
11-18-98	ADDED GENERAL NOTES TO CONCRETE STEPS & WALKS	
7-02-98	ENLARGED PIPE	
4-03-97	ADDED NOTE TO STEEL BAR SCHED.	
10-18-96	CORRECTED SPELLING	
4-26-96	ADD WEEP HOLE; REV. JOINT SPACING IN RET. WALL	
6-2-94	CHANGED CONST. TO CONTRACTION JOINT	
10-1-92	CHANGED MESH FABRIC TO WIRE MESH	10-1-92
8-15-91	DELETED HDWL MODIFICATION DETAIL	8-15-91
11-8-90	DELETED COLD MIX FROM CULV'T. REPAIR	11-8-90
11-30-89	REV. RETAINING WALL STEEL SCHEDULE	11-30-89
11-17-88	V. BARS BEHIND ARROW	665-11-17-88
7-15-88	REV. PAVEMENT REPAIR	649-7-15-88
11-1-84	ADDED HDWL. MODS, DEL. PIPE UNDERDRAINS	
1-4-83	REV. TRENCH FOR PIPE UNDERDRAIN	510-11-1-84
	ELIMINATED CONG. CLASS & ADDED CHAMFER NOTE	682-1-4-83
3-2-81	SPELLING OF "UNDERDRAIN"	721-3-2-81
4-20-79	REV. UNDERDRAIN DET & PAVEMENT REPAIR	674-4-20-79
2-2-76	12" MIN. GRAN. MAT'L. OVER PIPE	919-2-2-76
4-10-75	REM. SPECS. FOR GRAN. MAT'L.	568-4-10-75-853
5-22-74	GRANULAR MAT'L. TO BE SB-3	567-5-22-74-740
10-2-72	REVISED AND REDRAWN	564-10-16-72

ARKANSAS STATE HIGHWAY COMMISSION

**DETAILS OF SPECIAL ITEMS**

STANDARD DRAWING SI - 1

<p>RI-1</p>  <p>STANDARD 30"x30" EXPRESSWAY 36"x36" SPECIAL 48"x48"</p>	<p>RI-2</p>  <p>STD. 36"x36"x36" EXPWY. 48"x48"x48" FWY. 60"x60"x60"</p>	<p>R2-1</p>  <p>STD. 24"x30" EXPWY. 36"x48" FWY. 48"x60"</p>	<p>W3-5</p>  <p>STD. 36"x36" EXPWY. 48"x48" FWY. 48"x48"</p>	<p>W3-5a</p>  <p>STD. 36"x36" EXPWY. 48"x48" FWY. 48"x48"</p>	<p>R4-1</p>  <p>STD. 24"x30" EXPWY. 36"x48" FWY. 48"x60"</p>	<p>R4-2</p>  <p>STD. 24"x30" EXPWY. 36"x48" FWY. 48"x60"</p>	
<p>R5-1</p>  <p>STD. 30"x30" EXPWY. 36"x36" SPECIAL 48"x48"</p>	<p>R11-2</p>  <p>48"x30"</p>	<p>R11-3A</p>  <p>60"x30"</p>	<p>R11-4</p>  <p>60"x30"</p>	<p>W21-5a</p>  <p>STD. 36"x36" FWY. 48"x48"</p>	<p>WI-1</p>  <p>STD. 36"x36" FWY. 48"x48"</p>	<p>WI-2</p>  <p>STD. 36"x36" FWY. 48"x48"</p>	
<p>WI-3</p>  <p>STD. 48"x48"</p>	<p>WI-4</p>  <p>STD. 48"x48"</p>	<p>WI-6</p>  <p>STD. 48"x24" SPECIAL 60"x30"</p>	<p>WI-8</p>  <p>STD. 18"x24" SPECIAL 24"x30" EXPWY. 30"x36" FWY. 36"x48"</p>	<p>W3-1</p>  <p>STD. 36"x36" SPECIAL 48"x48"</p>	<p>W3-2</p>  <p>STD. 36"x36" SPECIAL 48"x48"</p>	<p>W4-2</p>  <p>STD. 36"x36" FWY. 48"x48"</p>	
<p>W5-1</p>  <p>STD. 36"x36" SPECIAL 48"x48"</p>	<p>W6-3</p>  <p>EXPWY. 36"x36" SPECIAL 48"x48"</p>	<p>W8-7</p>  <p>EXPWY. 36"x36" FWY. 48"x48"</p>	<p>W9-2</p>  <p>STD. 36"x36" FWY. 48"x48"</p>	<p>W13-1</p>  <p>STD. 24"x24"</p>	<p>W20-1</p>  <p>STD. 48"x48"</p>	<p>W20-2</p>  <p>STD. 48"x48"</p>	<p>W20-3</p>  <p>STD. 48"x48"</p>
<p>W20-4</p>  <p>STD. 48"x48"</p>	<p>W20-5</p>  <p>STD. 48"x48"</p>	<p>W20-7a</p>  <p>18" 500 FEET 24" W16-2</p> <p>STD. 36"x36" FWY. 48"x48"</p>	<p>W21-2</p>  <p>STD. 30"x30" SPECIAL 36"x36"</p>	<p>W21-5</p>  <p>STD. 30"x30" SPECIAL 36"x36"</p>	<p>W24-1</p>  <p>STD. 36"x36"</p>	<p>WI-4b</p>  <p>STD. 48"x48"</p>	<p>R56-1</p>  <p>STD. 18"x18"</p>
<p>W8-11</p>  <p>STD. 36"x36" FWY. 48"x48"</p>	<p>W8-9</p>  <p>STD. 36"x36" FWY. 48"x48"</p>	<p>G20-1</p>  <p>60"x24"</p>	<p>G20-2</p>  <p>48"x24"</p>	<p>OM-3L OM-3R</p>  <p>12"x36"</p>	<p>M4-9</p>  <p>STD. 30"x24" SPECIAL 48"x36" SPECIAL 60"x48"</p>	<p>M4-10</p>  <p>48"x18"</p>	<p>R55-1</p>  <p>36"x60"</p> <p>• USE 6" C LETTERS •• USE 4" D LETTERS</p>

ADVANCE DISTANCES  
(XXXX)

500 FT	1/2 MILE
1000 FT	3/4 MILE
1500 FT	1 MILE AHEAD


GENERAL NOTES:

- ALL TRAFFIC CONTROL DEVICES USED ON ROAD CONSTRUCTION SHALL CONFORM TO THE MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES, LATEST EDITION, AND TO THE STANDARD HIGHWAY SIGNS, LATEST EDITION, OR AS APPROVED BY THE FEDERAL HIGHWAY ADMINISTRATION.
- TRAFFIC CONTROL DEVICES SHALL BE SET UP JUST BEFORE THE START OF CONSTRUCTION OPERATIONS AND SHALL BE PROPERLY MAINTAINED DURING THE TIME SUCH CONDITIONS EXIST. THEY SHALL REMAIN IN PLACE ONLY AS LONG AS NEEDED AND REMOVED THEREAFTER.
- EXISTING SIGNS AND CONSTRUCTION SIGNS SHALL BE KEPT IN PROPER POSITION, AND BE CLEAN AND LEGIBLE AT ALL TIMES. SIGNS THAT DO NOT APPLY TO EXISTING CONDITIONS SHALL BE REMOVED. SIGNS THAT ARE DAMAGED, DEFACED, OR THAT ACCUMULATE DIRT DURING CONSTRUCTION SHALL BE CLEANED, REPAIRED, OR REPLACED.
- SIGNS ARE USUALLY MOUNTED ON A SINGLE POST, ALTHOUGH THOSE WIDER THAN 36" OR LARGER THAN 10 SQ. FT. SHALL BE MOUNTED ON TWO POSTS OR ABOVE A TYPE III BARRICADE.
- SIGN POSTS DIRECT BURIED IN SOIL SHALL BE 2 LB. MINIMUM CHANNEL POST OR 4"x4" WOOD POSTS. CHANNEL POSTS SHALL BE PAINTED GREEN. WOOD POSTS SHALL BE PAINTED WHITE. ALL POSTS SHALL BE NEATLY CONSTRUCTED, AND SHALL BE REPLUMBED, CLEANED, OR REPAIRED AS NEEDED FOR THE DURATION OF THE JOB. THERE SHALL NOT BE MORE THAN 2 POSTS IN A 7' PATH FOR WOOD OR CHANNEL POSTS. ANY CHANNEL POST SPLICE SHALL BE IN ACCORDANCE WITH STANDARD DRAWING TC-3.
- POST MOUNTED SIGNS IN RURAL AREAS SHALL BE CONSTRUCTED WITH THE NEAR EDGE OF THE SIGN FROM 6 TO 12 FEET FROM THE PAVEMENT EDGE. SIGNS IN URBAN AREAS AND BARRICADE MOUNTED SIGNS SHALL BE MOUNTED A MINIMUM OF 2 FEET FROM THE PAVEMENT EDGE.
- ALL POST AND BARRICADE MOUNTED SIGNS MOUNTED IN URBAN AREAS SHALL BE MOUNTED A MINIMUM DISTANCE OF 7' FROM THE BOTTOM OF THE SIGN TO THE ROADWAY SURFACE. ALL POST AND BARRICADE MOUNTED SIGNS MOUNTED IN RURAL AREAS SHALL BE MOUNTED A MINIMUM DISTANCE OF 7' FROM THE BOTTOM OF THE SIGN TO THE ROADWAY SURFACE, EXCEPT A MINIMUM OF 6' SHALL BE USED WHEN MOUNTING AN ADVISORY SIGN BELOW A WARNING SIGN. TEMPORARY SIGNS MAY BE MOUNTED ON PORTABLE SUPPORTS FOR INTERMEDIATE TERM STATIONARY WORK CONDITIONS. THE SIGNS MINIMUM MOUNTING HEIGHT SHALL BE 5'. RETROREFLECTIVE DEVICES SHALL BE USED. TEMPORARY SIGNS MAY BE MOUNTED ON PORTABLE SUPPORTS FOR SHORT-TERM, SHORT DURATION, AND MOBILE CONDITIONS. THEY SHALL BE NO LESS THAN ONE (1) FOOT ABOVE THE TRAVELED WAY. LONG-TERM STATIONARY SIGNS SHALL BE DIRECT BURIED IN SOIL, UNLESS CONDITIONS NECESSITATE THE USE OF PORTABLE SIGNS, OR AS APPROVED BY THE ENGINEER. CONCRETE PADS, CONCRETE OR ROCK BALLAST, OR OTHER SOLID MATERIALS SHALL NOT BE UTILIZED WITH PORTABLE SIGN SUPPORTS.
- FLAGGERS SHALL USE REFLECTORIZED STOP-SLOW PADDLES. FLAGS MAY BE USED ONLY FOR EMERGENCY SITUATIONS.
- MOST OF THE SIGNS SHOWN ARE ORIENTED TO THE RIGHT. HOWEVER, THIS DOES NOT PRECLUDE THE USE OF MIRROR IMAGES OF THESE SIGNS WHERE THE REVERSE ORIENTATION MIGHT BETTER CONVEY TO MOTORISTS THE PROPER DIRECTION OF MOVEMENT.
- R55-1 SIGNS SHALL BE PLACED AT LEAST 1500' BUT NOT MORE THAN 1 MILE IN ADVANCE OF THE WORK ZONE. IF A SPEED LIMIT REDUCTION IS IN EFFECT, THE SIGN SHALL BE PLACED A MINIMUM OF 500' IN ADVANCE OF THE "REDUCED SPEED AHEAD" SIGN.


• NOTE: SUPPORTS FOR SIGNS, BARRICADES, AND VERTICAL PANELS THAT ARE DIFFERENT FROM THE REQUIREMENTS SHOWN IN NOTES 4 & 5, BUT MEET THE REQUIREMENTS OF MANUAL FOR ASSESSING SAFETY HARDWARE (MASH), WILL BE ACCEPTED. COMPLIANCE WITH THE REQUIREMENTS OF MANUAL FOR ASSESSING SAFETY HARDWARE (MASH) IS REQUIRED FOR ALL PROJECTS.

DATE	REVISION	FILMED
11-07-19	REVISED FOR MASH	
4-13-17	DELETED RSP-1 & ADDED W21-5a	
9-2-15	REVISED REDUCED SPEED LIMIT AHEAD SIGNS REVISED ROAD WORK NEXT XX MILES	
12-15-11	REVISED W24-1	
11-17-10	DELETED W8-9a & ADDED W8-9	
10-15-09	ADDED REFERENCE TO MASH & ADDED SIGN W24-1	
4-17-08	REVISED SIGN DESIGNATIONS	
11-18-04	REVISED NOTES	
10-9-03	REVISED NOTE 1	
11-16-01	REVISED NOTE 7	
9-28-00	REVISED NOTE	
11-18-98	ADDED NOTE	
6-26-97	REVISED NOTE 5	
4-03-97	REVISED NOTE 5	
10-18-96	ADDED CONTROLLED ACCESS HWY. SIGN & TO NOTE 7	
10-12-95	ADDED R55-1	
6-8-95	REVISED TO CORRECT SIGN ILLUSTRATIONS	6-8-95
2-2-95	REVISED PER PART VI, MUTCD SEPT. 3, 1993	
8-15-91	DRAWN AND PLACED IN USE	


ARKANSAS STATE HIGHWAY COMMISSION  
STANDARD TRAFFIC CONTROLS  
FOR HIGHWAY CONSTRUCTION  
STANDARD DRAWING TC-1




(A) TYPICAL APPLICATION OF TRAFFIC CONTROL DEVICES ON A 2-LANE HIGHWAY WHERE THE ENTIRE ROADWAY IS CLOSED AND A BYPASS DETOUR IS PROVIDED.



(B) TYPICAL APPLICATION - 4-LANE DIVIDED ROADWAY WHERE ONE ROADWAY IS CLOSED.




(C) TYPICAL APPLICATION - 4-LANE UNDIVIDED ROADWAY WHERE HALF OF THE ROADWAY IS CLOSED.




NOTES:  
 1. REGULATORY TRAFFIC CONTROL DEVICES TO BE MODIFIED AS NEEDED FOR THE DURATION OF THE DETOUR.  
 2. STREET NAMES MAY BE USED WHEN DESIRABLE FOR DIRECTING DETOURED TRAFFIC.

(D) TYPICAL APPLICATION - ROADWAY CLOSED BEYOND DETOUR POINT.




NOTES:  
 1. FLOOD LIGHTS SHOULD BE PROVIDED TO MARK FLAGGER STATIONS AT NIGHT AS NEEDED.  
 2. IF ENTIRE WORK AREA IS VISIBLE FROM ONE STATION, A SINGLE FLAGGER MAY BE USED.  
 3. CHANNELIZING DEVICES ARE TO BE EXTENDED TO A POINT WHERE THEY ARE VISIBLE TO APPROACHING TRAFFIC.  
 4. AUTOMATED FLAGGER ASSISTANCE DEVICE (AFAD) OPTIONAL. REFER TO MUTCD.

(E) TYPICAL APPLICATION OF TRAFFIC CONTROL DEVICES ON 2-LANE HIGHWAY WHERE ONE LANE IS CLOSED AND FLAGGING IS PROVIDED.



(F) TYPICAL APPLICATION - 4-LANE UNDIVIDED ROADWAY WITH INSIDE LANE CLOSED.

- KEY:
- FLAGGER
  - ▬ POSITIVE BARRIER
  - ∞ ARROW PANEL (IF REQUIRED)
  - ▬ TYPE III BARRICADE
  - CHANNELIZING DEVICE
  - TRAFFIC DRUM
  - RAISED PAVEMENT MARKER



TYPICAL ADVANCE WARNING SIGN PLACEMENT

TAPER FORMULAE:

$L = S \times W$  FOR SPEEDS OF 45MPH OR MORE.

$L = \frac{W \times S^2}{60}$  FOR SPEEDS OF 40MPH OR LESS.


WHERE:  
 L = MINIMUM LENGTH OF TAPER.

S = NUMERICAL VALUE OF POSTED SPEED LIMIT PRIOR TO WORK OR 85TH PERCENTILE SPEED.


W = WIDTH OF OFFSET.

- GENERAL NOTES:
1. THE MAINTENANCE DIVISION SHALL CONDUCT A BALL BANK STUDY TO DETERMINE THE ADVISORY SPEED LIMIT PRIOR TO OPENING TO TRAFFIC. THE ADVISORY SPEED WILL BE POSTED ON W1-3 OR W1-4 CURVE WARNING SIGNS. USE W1-4 WHEN SPEED IS GREATER THAN 30MPH AND W1-3 WHEN 30MPH OR LESS.
  2. WHEN THE EXISTING SPEED LIMIT IS 55MPH AND THE PLANS REQUIRE A SPEED LIMIT OF 45MPH, THE R2-1(55) SHALL BE OMITTED AND THE W3-5 SHALL BE INSTALLED AT THAT LOCATION. ADDITIONAL R2-1(45) SPEED LIMIT SIGNS SHALL BE INSTALLED AT A MAXIMUM OF 1/2 MILE INTERVALS. AT THE END OF THE WORK AREA A R2-1(XX) SHALL BE INSTALLED TO MATCH ORIGINAL SPEED LIMIT.
  3. WHEN THE EXISTING SPEED LIMIT IS 65MPH AND THE PLANS REQUIRE A SPEED LIMIT OF 55MPH, THE R2-1(65) SHALL BE OMITTED. ADDITIONAL R2-1(55) SPEED LIMIT SIGNS SHALL BE INSTALLED AT A MAXIMUM OF 1/2 MILE INTERVALS. AT THE END OF THE WORK AREA A R2-1(XX) SHALL BE INSTALLED TO MATCH ORIGINAL SPEED LIMIT.
  4. THE MAXIMUM SPACING BETWEEN CHANNELIZING DEVICES IN A TAPER SHOULD BE APPROXIMATELY EQUAL IN FEET TO THE SPEED LIMIT. BEYOND THE TAPER, MAXIMUM SPACING SHALL BE TWO TIMES THE SPEED LIMIT, OR AS DIRECTED BY THE ENGINEER.
  5. WARNING LIGHTS AND/OR FLAGS MAY BE MOUNTED TO SIGNS OR CHANNELIZING DEVICES AT NIGHT AS NEEDED.
  6. PAVEMENT MARKINGS NO LONGER APPLICABLE WHICH MIGHT CREATE CONFUSION IN THE MINDS OF VEHICLE OPERATORS SHALL BE REMOVED OR OBLITERATED AS SOON AS PRACTICABLE.
  7. TRAILER MOUNTED DEVICES SUCH AS ARROW PANELS AND PORTABLE CHANGEABLE MESSAGE SIGNS SHALL BE DELINEATED BY AFFIXING CONSPICUITY MATERIAL IN A CONTINUOUS LINE ON THE FACE OF THE TRAILER. WHEN PLACED ON OR ADJACENT TO THE SHOULDER AND NOT BEHIND A POSITIVE BARRIER, THESE DEVICES SHALL BE DELINEATED BY PLACING FIVE (5) TRAFFIC DRUMS, EQUALLY SPACED ALONG THE TRAFFIC SIDE OF THE DEVICE.
  8. DIMENSIONS SHOWN FOR RAISED PAVEMENT MARKERS ARE TYPICAL. THE CONTRACTOR MAY SUBSTITUTE SIMILAR MARKERS WITH THE APPROVAL OF THE ENGINEER. REQUESTING APPROVAL FOR SIMILAR MARKERS MAY BE MADE BY REFERRING TO THE ADOT QUALIFIED PRODUCTS LIST.
  9. ALL TRAILER MOUNTED DEVICES SUCH AS ARROW PANELS AND PORTABLE CHANGEABLE MESSAGE SIGNS SHALL MEET THE REQUIREMENTS OF THE MANUAL FOR ASSESSING SAFETY HARDWARE (MASH).

DATE	REVISION	FILED
11-07-19	REVISED NOTE 1, ADDED NOTE 9	
9-2-15	REVISED NOTE 2, ADDED NOTE 8, REVISED DRAWING (A) & REPLACED R2-5A WITH W3-5	
9-12-13	REVISED DETAIL OF RAISED PAVEMENT MARKERS	
3-11-10	ADDED (AFAD)	
11-20-08	REVISED SIGN DESIGNATIONS	
11-18-04	ADDED GENERAL NOTE	
10-18-96	ADDED R55-1	
4-26-96	CORRECTED (a) BEHIND G20-2	
6-8-95	CORRECTED SIGN IDENT. ON W1-4A	6-8-95
2-2-95	REVISED PER PART VI, MUTCD, SEPT. 3, 1993	
8-15-91	DRAWN AND PLACED IN USE	





(A) TYPICAL APPLICATION - DAYTIME MAINTENANCE OPERATIONS OF SHORT DURATION ON A 4-LANE DIVIDED ROADWAY WHERE HALF OF THE ROADWAY IS CLOSED.





(B) TYPICAL APPLICATION - 3-LANE ONEWAY ROADWAY WHERE CENTER LANE IS CLOSED.

CHANNELIZING DEVICES



NOTE: FOR ALL ROAD CLOSURES, THE TYPE III BARRICADES SHALL BE OF SUFFICIENT LENGTH TO EXTEND ACROSS ENTIRE ROADWAY.

VERTICAL PANEL PLACEMENT




TRAFFIC CONTROL DEVICES			
NON-INTERSTATE			
VERTICAL DIFFERENTIAL	LOCATION	TRAFFIC CONTROL	
		≤ 45 MPH	> 45 MPH
≤ 2"	CENTERLINE	W8-11 AND LANE STRIPING	W8-11 AND LANE STRIPING
> 2"	CENTERLINE	STANDARD LANE CLOSURE	STANDARD LANE CLOSURE
≤ 3"	EDGE OF TRAVELED LANE OR EDGE OF SHOULDER	W8-9, EDGE LINE STRIPING, AND VERTICAL PANELS	W8-9, EDGE LINE STRIPING, AND VERTICAL PANELS
> 3"	EDGE OF TRAVELED LANE OR EDGE OF SHOULDER	W8-17, EDGE LINE STRIPING, AND VERTICAL PANELS	W8-17, EDGE LINE STRIPING, AND VERTICAL PANELS
≤ 6"	EDGE OF TRAVELED LANE OR EDGE OF SHOULDER	W8-17, EDGE LINE STRIPING, AND TRAFFIC DRUMS <sup>(1)</sup>	W8-17, EDGE LINE STRIPING, AND TRAFFIC DRUMS <sup>(2)</sup>
> 6"	EDGE OF TRAVELED LANE OR EDGE OF SHOULDER	W8-17, EDGE LINE STRIPING, AND TRAFFIC DRUMS <sup>(1)</sup>	A STABILIZED WEDGE, W8-17, EDGE LINE STRIPING AND TRAFFIC DRUMS <sup>(3)</sup>
> 24"	EDGE OF TRAVELED LANE OR EDGE OF SHOULDER	PRECAST CONCRETE BARRIER <sup>(4)</sup> & EDGE LINES	PRECAST CONCRETE BARRIER <sup>(4)</sup> & EDGE LINES

INTERSTATE		
VERTICAL DIFFERENTIAL	LOCATION	TRAFFIC CONTROL
≤ 2"	CENTERLINE	W8-11 AND LANE STRIPING
≤ 2"	EDGE OF TRAVELED LANE OR EDGE OF SHOULDER	W8-9, EDGE LINE STRIPING, AND TRAFFIC DRUMS <sup>(2)</sup>
> 2"	EDGE OF TRAVELED LANE OR EDGE OF SHOULDER	W8-17, EDGE LINE STRIPING, AND TRAFFIC DRUMS <sup>(2)</sup>
> 6"	EDGE OF TRAVELED LANE OR EDGE OF SHOULDER	PRECAST CONCRETE BARRIER & EDGE LINES

INTERSTATE AND NON-INTERSTATE		
FORESLOPE	HEIGHT	TRAFFIC CONTROL
1:1	> 2 FT	PRECAST CONCRETE BARRIER
2:1	≤ 5 FT	TRAFFIC DRUMS
2:1	> 5 FT	PRECAST CONCRETE BARRIER
Flatter than 2:1	N/A	TRAFFIC DRUMS

- GENERAL NOTES:
- WHEN THE SHOULDER AREA IS USED AS PART OF THE TRAVELED LANE AND THERE IS INSUFFICIENT WIDTH TO PLACE TRAFFIC DRUMS ON THE REMAINING SHOULDER WIDTH, THEN VERTICAL PANELS SHALL BE USED.
  - WHEN THERE IS INSUFFICIENT WIDTH TO PLACE TRAFFIC DRUMS ON THE REMAINING SHOULDER WIDTH, A STABILIZED WEDGE SHALL BE USED. PRECAST CONCRETE BARRIER WALL CAN BE USED IN LIEU OF A STABILIZED WEDGE, W8-17 SIGN, EDGE LINE STRIPING, AND TRAFFIC DRUMS.
  - IF AND WHERE DIRECTED BY THE ENGINEER, A STABILIZED WEDGE, W8-17 SIGN, EDGE LINE STRIPING, AND TRAFFIC DRUMS CAN BE USED IN LIEU OF PRECAST CONCRETE BARRIER WALL.
  - IF AND WHERE DIRECTED BY THE ENGINEER, W21-5, W21-5a, AND/OR W21-5b SIGNS SHALL BE USED WHERE THE ROADWAY IS UNOBSTRUCTED IF AND WHERE DIRECTED BY THE ENGINEER.




NOTE: MATERIALS FOR THE STABILIZED WEDGE SHALL MEET THE REQUIREMENTS PROVIDED IN SECTION 603.02 OF THE STANDARD SPECIFICATIONS.

KEY:


- ○ ○ ARROW PANEL (IF REQUIRED)
- CHANNELIZING DEVICE
- TRAFFIC DRUM

GENERAL NOTES:

- A SPEED LIMIT REDUCTION MAY BE IMPLEMENTED ONLY WHEN DESIGNATED IN THE PLAN OR WHEN RECOMMENDED BY THE ROADWAY DESIGN DIVISION.
- WHEN THE EXISTING SPEED LIMIT IS 55MPH AND THE PLANS REQUIRE A SPEED LIMIT OF 45MPH, THE R2-1(55) SHALL BE OMITTED AND THE W3-5 SHALL BE INSTALLED AT THAT LOCATION. ADDITIONAL R2-1(45) SPEED LIMIT SIGNS SHALL BE INSTALLED AT A MAXIMUM OF 1/2 MILE INTERVALS. AT THE END OF THE WORK AREA A R2-1(XX) SHALL BE INSTALLED TO MATCH ORIGINAL SPEED LIMIT.
- WHEN THE EXISTING SPEED LIMIT IS 65MPH AND THE PLANS REQUIRE A SPEED LIMIT OF 55MPH, THE R2-1(65) SHALL BE OMITTED. ADDITIONAL R2-1(55) SPEED LIMIT SIGNS SHALL BE INSTALLED AT A MAXIMUM OF 1/2 MILE INTERVALS. AT THE END OF THE WORK AREA A R2-1(XX) SHALL BE INSTALLED TO MATCH ORIGINAL SPEED LIMIT.
- THE MAXIMUM SPACING BETWEEN CHANNELIZING DEVICES IN A TAPER SHOULD BE APPROXIMATELY EQUAL IN FEET TO THE SPEED LIMIT. BEYOND THE TAPER, MAXIMUM SPACING SHALL BE TWO TIMES THE SPEED LIMIT OR AS DIRECTED BY THE ENGINEER.
- WARNING LIGHTS AND/OR FLAGS MAY BE MOUNTED TO SIGNS OR CHANNELIZING DEVICES AT NIGHT AS NEEDED.
- PAVEMENT MARKINGS NO LONGER APPLICABLE WHICH MIGHT CREATE CONFUSION IN THE MINDS OF VEHICLE OPERATORS SHALL BE REMOVED OR OBLITERATED AS SOON AS PRACTICABLE.
- THE G20-1 SIGN WILL BE REQUIRED ON JOBS OF OVER TWO MILES IN LENGTH. WHEN THE LANE CLOSURE IS NOT AT THE BEGINNING OF THE PROJECT, THE G20-1 SIGN SHALL BE ERECTED 125' IN ADVANCE OF THE JOB LIMIT. ADDITIONAL W20-1(1/2 MILE) SIGNS ARE NOT REQUIRED IN ADVANCE OF LANE CLOSURES THAT BEGIN INSIDE THE PROJECT LIMITS.
- FLAGGERS SHALL USE STOP/SLOW PADDLES FOR CONTROLLING TRAFFIC THROUGH WORK ZONES. FLAGS MAY BE USED ONLY FOR EMERGENCY SITUATIONS.
- ALL PLASTIC DRUMS AND CONES SHALL MEET THE REQUIREMENTS OF MANUAL FOR ASSESSING SAFETY HARDWARE (MASH).
- TRAILER MOUNTED DEVICES SUCH AS ARROW PANELS AND PORTABLE CHANGEABLE MESSAGE SIGNS SHALL BE DELINEATED BY AFFIXING CONSPICUITY MATERIAL IN A CONTINUOUS LINE ON THE FACE OF THE TRAILER, WHEN PLACED ON OR ADJACENT TO THE SHOULDER AND NOT BEHIND A POSITIVE BARRIER, THESE DEVICES SHALL BE DELINEATED BY PLACING FIVE (5) TRAFFIC DRUMS, EQUALLY SPACED ALONG THE TRAFFIC SIDE OF THE DEVICE.
- ALL TRAILER MOUNTED DEVICES SUCH AS ARROW PANELS AND PORTABLE CHANGEABLE MESSAGE SIGNS SHALL MEET THE REQUIREMENTS OF THE MANUAL FOR ASSESSING SAFETY HARDWARE (MASH).




(C) TYPICAL APPLICATION - CONSTRUCTION OPERATIONS OF INTERMEDIATE TO LONG TERM DURATION ON A 4-LANE DIVIDED ROADWAY WHERE HALF OF THE ROADWAY IS CLOSED.



(D) TYPICAL APPLICATION - CLOSING MULTIPLE LANES OF A MULTILANE HIGHWAY.


- NOTES:
- USE SPLICES ONLY WHEN NECESSARY FOR INSTALLATION. TYPICAL INSTALLATION SHOULD HAVE NO SPLICES (SEE STD. DRAWING NO. SHS-2)
  - NORMAL INSTALLATIONS WILL REQUIRE 1/4" DIA. BOLTS TO MOUNT SIGNS TO POST AND 5/16" DIA. BOLTS TO ASSEMBLE THE VARIOUS POST SUPPORTS. EACH OF THESE BOLTS SHALL BE CARRIAGE BOLTS.
  - SIGN POSTS SHALL BE PAINTED GREEN; SIGNS SHALL NOT BE PAINTED, AND ALL SIGN POSTS SHALL BE PLUMB.



DATE	REVISION	FILMED
2-27-20	REVISED TRAFFIC CONTROL DEVICES DETAILS	
11-07-19	REVISED NOTE 9, ADDED NOTE II	
7-25-19	REVISED TRAFFIC CONTROL DEVICES DETAILS	
9-2-15	REVISED NOTE 2 & REPLACED R2-5A WITH W3-5	
10-15-09	ADDED REFERENCE TO MASH	
11-20-08	REVISED SIGN DESIGNATIONS	
11-18-04	ADDED NOTE	
10-1-98	ADDED NOTE	
4-03-97	ADDED (SP) TO W6-18 & REVISED TRAFFIC CONTROL DEVICES NOTE	
10-18-96	ADDED R55-1	
10-12-95	MOVED UPPER SPLICE	
6-8-95	REVISED SPLICE DETAIL, TEXT	6-8-95
2-2-95	REVISED PER PART VI, MUTCD, SEPT. 3, 1993	
8-15-91	DRAWN AND PLACED IN USE	


**GENERAL NOTES**

INSTALL A MINIMUM OF 2 UPSLOPE STAKES AND 4 DOWNSLOPE STAKES AT AN ANGLE TO WEDGE WATTLE TO BOTTOM OF DITCH.




**WATTLE DITCH CHECK (E-1)**

NUMBER OF SAND BAGS AND ARRANGEMENT VARIABLE WITH ON-SITE CONDITIONS. PLACE SAND BAGS AT BASE OF DITCH CHECK IN AREA OF OVERFLOW.




**SAND BAG DITCH CHECK (E-5)**




**ROCK DITCH CHECK (E-6)**


**GENERAL NOTES**  
 GEOTEXTILE FABRIC (TYPE 4) IN ACCORDANCE WITH SECTION 625  
 GEOTEXTILE FABRIC SHALL BE SPLICED TOGETHER WITH A SEWN SEAM ONLY AT A SUPPORT POST OR TWO SECTIONS OF FENCE MAY BE OVERLAPPED INSTEAD. PAYMENT OF ADDITIONAL MATERIAL FOR OVERLAP WILL NOT BE MADE.



**SILTS FENCE (E-11)**




**DROP INLET SILTS FENCE (E-7)**




**SILTS FENCE ON R/W FENCE (E-4)**

**GENERAL NOTES**  
 1. STRAW BALES SHALL BE INSTALLED SO THAT THE BINDINGS ARE ORIENTED AROUND THE SIDES RATHER THAN ALONG THE TOPS AND BOTTOMS OF THE BALES. THE BALES SHALL BE A MINIMUM OF 30 INCHES IN LENGTH.  
 2. NO GAPS SHALL BE LEFT BETWEEN BALES.  
 3. BALED STRAW FILTER BARRIERS COMPLETED AND ACCEPTED WILL BE MEASURED BY THE BALE IN PLACE AS AUTHORIZED BY THE ENGINEER AND WILL BE PAID FOR AT THE CONTRACT UNIT PRICE BID PER BALE FOR BALED STRAW DITCH CHECKS.




**BALED STRAW FILTER BARRIER (E-2)**



**PLAN VIEW N.T.S.**

**FILTER SOCK ALONG SLOPE (E-3)**

**NOTES:**  
 1. FILTER SOCKS CAN BE PLACED AT THE TOP, ON THE FACE, AND AT THE TOE OF SLOPES AS SEDIMENT-TRAPPING DEVICES FOR SHEET FLOW RUNOFF.  
 2. FILTER SOCKS ARE TYPICALLY SUPPLIED AND INSTALLED WITH 18 INCH DIAMETERS. DIAMETER TOLERANCE IS 2 INCHES, AS FILTER SOCKS TEND TO FLATTEN OUT WHEN PLACED.  
 3. STEEL POSTS MAY BE USED AND SHALL BE ROLLED FROM HIGH CARBON STEEL AND HAVE A MINIMUM OF 1.25 LB./FT. POSTS SHALL BE HOT-DIPPED GALVANIZED OR PAINTED WITH HIGH-GRADE WEATHER RESISTANT BROWN OR BLACK STEEL PAINT. STEEL POSTS SHALL BE EQUIPPED WITH ANCHOR PLATE HAVING A MINIMUM AREA OF 14 SQUARE INCHES. POSTS SHALL BE STUDDED, EMBOSSED, OR PUNCHED. POSTS AND ANCHOR PLATES SHALL CONFORM TO THE REQUIREMENTS OF ASTM A702. NO ADDITIONAL PAYMENT WILL BE PROVIDED FOR STEEL POSTS, BUT PRICE WILL BE CONSIDERED SUBSIDIARY TO "FILTER SOCK (18\"/>



**DROP INLET PLAN VIEW N.T.S.**

**DROP INLET PERSPECTIVE VIEW N.T.S.**

**COMPOST FILTER SOCK DROP INLET PROTECTION (E-13)**

**NOTES:**  
 1. OVERLAP ENDS OF SOCK (1' MIN. 3' MAX.).  
 2. USE 18" DIA. SOCK IN NON-TRAFFIC AREAS OR AREAS WHERE SAFETY IS NOT A CONCERN.

DATE	REVISION
11-16-17	ADDED FILTER SOCK E-3 AND E-13
12-15-11	DELETED BALED STRAW DITCH CHECK & ADDED WATTLE DITCH CHECK
11-18-98	ADDED NOTES
07-02-98	ADDED BALED STRAW FILTER BARRIER (E-2)
07-20-95	REVISED SILTS FENCE E-4 AND E-11
07-15-94	REV. E-4 & E-11 MIN. 13" BURIED END OF FABRIC
06-02-94	REVISED E-1, 4, 7 & 11; DELETED E-2 & 3
04-01-93	REDRAWN
10-01-92	REDRAWN
08-02-76	ISSUED R.D.M.


ARKANSAS STATE HIGHWAY COMMISSION  
 TEMPORARY EROSION CONTROL DEVICES  
 STANDARD DRAWING TEC-1

## CLEARING AND GRUBBING

### CONSTRUCTION SEQUENCE

1. PLACE PERIMETER CONTROLS (I.E. SILT FENCES, DIVERSION DITCHES, SEDIMENT BASINS, ETC.)
2. PERFORM CLEARING AND GRUBBING OPERATION.

## EXCAVATION



NOTE:  
NUMBER OF PHASES WILL VARY.  
THREE PHASES SHOWN FOR  
ILLUSTRATION.


### GENERAL NOTE

ALL CUT SLOPES SHALL BE DRESSED, PREPARED, SEEDED, AND MULCHED AS THE WORK PROGRESSES. SLOPES SHALL BE EXCAVATED AND STABILIZED IN EQUAL INCREMENTS NOT TO EXCEED 25 FEET, MEASURED VERTICALLY.

### CONSTRUCTION SEQUENCE

1. EXCAVATE AND STABILIZE INTERCEPTOR AND/OR DIVERSION DITCHES.
2. PERFORM PHASE 1 EXCAVATION. PLACE PERMANENT OR TEMPORARY SEEDING.
3. PERFORM PHASE 2 EXCAVATION. PLACE PERMANENT OR TEMPORARY SEEDING.
4. PERFORM FINAL PHASE OF EXCAVATION. PLACE PERMANENT OR TEMPORARY SEEDING. STABILIZE DITCHES. CONSTRUCT DITCH CHECKS, DIVERSION DITCHES, SEDIMENT BASINS, OR OTHER EROSION CONTROL DEVICES AS REQUIRED.

## EMBANKMENT



NOTE:  
NUMBER OF PHASES WILL VARY.  
THREE PHASES SHOWN FOR  
ILLUSTRATION.

### GENERAL NOTE




ALL EMBANKMENT SLOPES SHALL BE DRESSED, PREPARED, SEEDED, AND MULCHED AS THE WORK PROGRESSES. SLOPES SHALL BE CONSTRUCTED AND STABILIZED IN EQUAL INCREMENTS NOT TO EXCEED 25 FEET, MEASURED VERTICALLY.

### CONSTRUCTION SEQUENCE

1. CONSTRUCT DIVERSION DITCHES, DITCH CHECKS, SEDIMENT BASINS, SILT FENCES, OR OTHER EROSION CONTROL DEVICES AS SPECIFIED.
2. PLACE PHASE 1 EMBANKMENT WITH PERMANENT OR TEMPORARY SEEDING. PROVIDE DIVERSION DITCHES AND SLOPE DRAINS IF EMBANKMENT CONSTRUCTION IS TO BE TEMPORARILY ABANDONED FOR A PERIOD OF GREATER THAN 21 DAYS.
3. PLACE PHASE 2 EMBANKMENT WITH PERMANENT OR TEMPORARY SEEDING. PROVIDE DIVERSION DITCHES AND SLOPE DRAINS IF EMBANKMENT CONSTRUCTION IS TO BE TEMPORARILY ABANDONED FOR A PERIOD OF GREATER THAN 21 DAYS.
4. PLACE FINAL PHASE OF EMBANKMENT WITH PERMANENT OR TEMPORARY SEEDING. PLACE DIVERSION DITCHES AND SLOPE DRAINS AND MAINTAIN UNTIL ENTIRE SLOPE IS STABILIZED.

			ARKANSAS STATE HIGHWAY COMMISSION
			TEMPORARY EROSION CONTROL DEVICES
11-03-94	CORRECTED SPELLING		
6-2-94	Drawn & Issued		6-2-94
DATE	REVISION		FILMED
			STANDARD DRAWING TEC-3





- GENERAL NOTES:**
- (C) CHAIN LINK FENCE BEING PLACED ON PRIVATE PROPERTY SHALL INCLUDE A TOP RAIL. ALL LABOR, MATERIALS, EQUIPMENT, TOOLS, AND INCIDENTALS NECESSARY TO COMPLETE THE WORK WILL BE PAID FOR AT THE CONTRACT UNIT PRICE BID PER LIN. FT. OF CHAIN LINK FENCE.
  - (D) TENSION WIRE: SHALL BE SECURED TO ALL TERMINAL, PULL, BRACE OR CORNER POSTS WITH TENSION BAR BANDS.
  - (J) BRACE RAIL: BRACE RAILS SHALL BE PROVIDED AT ALL TERMINAL, PULL, BRACE OR CORNER POSTS HALFWAY BETWEEN THE TOP RAIL AND GROUND LEVEL WHEN TOPRAIL IS SPECIFIED AND TWELVE INCHES (12") DOWN FROM TOP OF FABRIC WHEN TOP TENSION WIRE IS SPECIFIED. BRACE RAIL SHALL EXTEND FROM SUCH POST TO THE FIRST ADJACENT LINE POST.
  - (L) FABRIC: SHALL CONFORM TO THE SPECIFICATIONS.

HEIGHT OF FENCE FABRIC	(A)	(B)		(C)			(D)		(E)		(F)			(G)	
	END, PULL CORNER OR BRACE POST	SIZE	TIE SPACING	SIZE	TIE SPACING	MIN. LENGTH	SIZE	TIE SPACING	SIZE	LENGTH	SIZE	BOLT SIZE	SPACING	SIZE	BOLT SIZE
6' AND LESS	2 1/2" O.D.	2" O.D.	1 TIE EVERY 1'-2"	1 5/8" O.D.	1 TIE EVERY 2'-0"	10'-0"	7 GAUGE COIL SPRING WIRE	1 TIE EVERY 1'-0"	MIN. OF 3/8" x 3/4"	MIN. OF 2" LESS THAN FABRIC HEIGHT	MIN. OF 3/4" x 5/8"	1/4" x 1 1/4"	1 BAND AT TOP AND BOTTOM 15" MAX. INTERVAL BETWEEN BANDS	MIN. OF 3/4" x 3/8"	5/8" x 1/4"
OVER 6' TO 12' INCL.	3" O.D.	2 1/2" O.D.	1 TIE EVERY 1'-2" OF FABRIC HEIGHT	1 5/8" O.D.	1 TIE EVERY 2'-0"	10'-0"	7 GAUGE COIL SPRING WIRE	1 TIE EVERY 1'-0"	3/8" x 3/4"	MIN. OF 2" LESS THAN FABRIC HEIGHT	MIN. OF 3/4" x 5/8"	1/4" x 1 1/4"	1 BAND AT TOP AND BOTTOM 15" MAX. INTERVAL BETWEEN BANDS	MIN. OF 3/4" x 3/8"	5/8" x 1/4"

HEIGHT OF FENCE FABRIC	(H)	(I)	(J)		(K)	(L)			(M)		(N)	(O)	(T)		
	TIE WIRE	HOG RING	SIZE	TIE SPACING	TRUSS ROD	SIZE	MESH	SERVAGE	SIZE	TIE SPACING	SIZE	TIE SPACING	HINGE TPE	GATE WIDTH	GATE WIDTH OVER
6' AND LESS	MIN. OF 12 GA. STEEL OR 9 GA. ALUM.	SAME GAUGE AS FABRIC	1 5/8" O.D.	1 TIE EVERY 2'-0"	MIN. OF 3/8" ROUND WITH TIGHTENERS AND FITTINGS	9 GA.	2"	KNUCKLING AND/OR TWISTING	2" O.D.	1 TIE EVERY 1'-0"	2" O.D.	1 TIE EVERY 1'-0"	180° SWING	3' O.D.	12' AND LESS
OVER 6' TO 12' INCL.	MIN. OF 12 GA. STEEL OR 9 GA. ALUM.	SAME GAUGE AS FABRIC	1 5/8" O.D.	1 TIE EVERY 2'-0"	MIN. OF 3/8" ROUND WITH TIGHTENERS AND FITTINGS	9 GA.	2"	KNUCKLING AND/OR TWISTING	2" O.D.	1 TIE EVERY 1'-0"	2" O.D.	1 TIE EVERY 1'-0"	180° SWING	3' O.D.	12' AND LESS

NOTE: POST SIZES SHOWN ARE FOR STEEL. WHERE ALUMINUM IS PROVIDED, LINE POSTS SHALL HAVE AN OUT SIDE DIAMETER OF 2 1/2" FOR FENCE HEIGHT OF 6' AND LESS, AN OUTSIDE DIAMETER OF 3" FOR FENCE HEIGHT OF 6' TO 12'. END, PULL, CORNER OR BRACE POSTS SHALL HAVE AN OUTSIDE DIAMETER OF 3" FOR FENCE HEIGHT OF 6' AND LESS; AN OUTSIDE DIAMETER OF 3 1/2" FOR FENCE HEIGHTS OF 6' TO 12'. GATE POSTS WHERE GATE WIDTH IS 12' AND LESS SHALL HAVE AN OUTSIDE DIAMETER OF 3 1/2" FOR FENCE HEIGHT OF 6' AND LESS. ALUMINUM TENSION WIRE SHALL BE 0.192" IN DIAMETER. MINIMUM THICKNESS OF MATERIAL FROM WHICH EXPANSION SLEEVES SHALL BE MADE WILL BE 0.078". POSTS AND RAILS MAY HAVE ANY CROSS-SECTIONAL SHAPE THAT WILL MEET THE SPECIFICATIONS.

OTHER DETAILS APPLY TO BOTH STEEL AND ALUMINUM FENCE.

ALL MISCELLANEOUS FITTINGS AND HARDWARE SHALL MEET THE REQUIREMENTS AND PRODUCTION TOLERANCES AS SET FORTH IN THE SPECIFICATIONS. 9 GAUGE ALUMINUM WIRE SHALL BE ACCEPTABLE FOR TIEING FABRIC TO TUBULAR AND ROLL FORMED MEMBERS OF STEEL FENCE.

- (M) GATE FRAMES: SHALL BE CONSTRUCTED OF TUBULAR MEMBERS ASSEMBLED BY USE OF HEAVY PRESSED STEEL, MALLEABLE FITTINGS OR BY WELDING. ALL GATES SHALL HAVE ONE HORIZONTAL SUPPORT EXTENDING THE WIDTH OF THE GATE AT THE MIDPOINTS OF VERTICAL FRAME MEMBERS. THE COMPLETE FRAME SHALL BE RIGID AND HAVE AMPLE STRENGTH TO BE FREE FROM SAG AND TWIST.
- (O) HINGES: SHALL BE OF HEAVY PATTERN, OF ADEQUATE STRENGTH FOR GATE, AND WITH LARGE BEARING SURFACES FOR CLAMPING IN POSITION. THE HINGE SHALL BE OF THE PROPER TYPE TO ALLOW FOR THE DESIGNATED DEGREE OF SWING. THE HINGE SHALL NOT TWIST OR TURN UNDER THE ACTION OF THE GATE. THE GATES SHALL BE CAPABLE OF BEING OPENED AND CLOSED EASILY BY ONE PERSON.
- (P) LATCHES AND STOPS: SHALL BE PROVIDED FOR ALL GATES. GATES SHALL HAVE A DROP BAR LATCH. LATCHES SHALL BE ARRANGED FOR LOCKING. THE STOP FOR DROP BAR LATCHES SHALL BE SET IN CONCRETE AND ENGAGE THE PLUNGER OF THE BAR LATCH.
- (S) CAPS: ALL POSTS, EXCEPT ROLL FORMED POSTS AND "T" POSTS SHALL BE CAPPED OVER THE EXTERIOR OF THE POST, AND SHALL CONFORM TO ASTM F626.

CONCRETE REQUIRED FOR THE EMBEDMENT OF ALL POSTS SHALL NOT BE PAID FOR DIRECTLY BUT SHALL BE INCLUDED IN THE CONTRACT UNIT PRICE BID FOR CHAIN LINK FENCE.

POSTS SHALL BE SPACED EQUIDISTANT ON A MAXIMUM OF 10' CENTERS.


EXCAVATION FOR POSTS: IN OTHER THAN ROCK SHALL BE OF THE DIMENSIONS INDICATED. IF ROCK IS ENCOUNTERED BEFORE REACHING THE REQUIRED DEPTH, THE EXCAVATION SHALL BE CONTINUED TO THE DEPTH INDICATED OR 1'-6" INTO THE ROCK, WHICHEVER IS LESS, AND SHALL BE A MINIMUM OF 8 INCHES IN DIAMETER.

POSTS AND RAILS

SIZE O.D.	GRADE 1 AND ALUMINUM ALLOY				GRADE 2		
	O.D. INCHES	WALL THICKNESS	LBS. PER LINEAR FT.		O.D. INCHES	WALL THICKNESS	LBS. PER LINEAR FT.
			STEEL	ALUMINUM			
1 5/8"	1.660	0.140	2.27	0.786	1.660	0.111	1.84
2	1.900	0.145	2.72	0.940	1.900	0.120	2.28
2 1/2	2.375	0.154	3.65	1.264	2.375	0.130	3.11
3	2.875	0.203	5.79	2.004	2.875	0.160	4.64
3 1/2	3.500	0.216	7.58	2.621	3.500	0.160	5.71
4	4.000	0.226	9.11	3.151	4.000	0.160	6.56

TOLERANCES ON DIMENSIONS AND WEIGHTS ACCORDING TO AASHTO M 181

DATE	REVISION	FILMED
11-17-10	REVISED TRUSS ROD	
12-10-09	REVISED POSTS & RAILS TABLE	
5-21-09	ADDED TABLE & GEN. NOTE (C)	
8-22-02	REVISED NOTES, REMOVED TABLE, & REMOVED FENCE ALTERNATE	
4-3-97	REVISED BRACE RAIL NOTE	
10-18-96	REVISED AASHTO & ASTM REF.	
11-3-94	REVISED NOTE (L)	
10-1-92	DELETED ALTERNATE POST	10-1-92
8-15-91	DELETED ROLL FORMED POST DETAIL & ADDED NOTE	8-15-91
11-30-89	DELETED CLASS CONCRETE	11-30-89
11-17-88	REVISED O.D. SIZES	668-11-17-88
10-30-87	GENERAL REVISIONS	548-10-30-87
4-20-79	REVISED TOP RAIL & TENSION WIRE	695-4-20-79
10-2-72	REVISED AND REDRAWN	530-10-2-72





INSTALLATION MAY BE MODIFIED AS SHOWN IN THE PLANS

**ARKANSAS STATE HIGHWAY COMMISSION**

**CHAIN LINK FENCE**

**STANDARD DRAWING WF-3**




**TYPE 1 RAMP DIMENSIONS AND QUANTITIES**




RADIUS "R"	DISTANCE "X"	DISTANCE "Y"	LENGTH "L"	RAMP AREA "A"
FEET	FEET	FEET	FEET	SQ. YD.
15	11.67	18.82	32.18	26.21
20	11.52	22.28	35.46	30.07
25	11.43	26.60	38.77	33.80
30	11.37	30.26	40.93	36.90
35	11.33	33.51	43.11	39.77
40	11.30	36.45	45.26	42.45
45	11.27	39.16	47.34	44.97
50	11.25	41.69	49.36	47.35
55	11.24	44.07	51.31	49.63
60	11.22	46.33	53.21	51.80

**GENERAL NOTES FOR DETECTABLE WARNING DEVICES**





THE DETECTABLE WARNING DEVICE SHALL BE LOCATED SO THAT THE NEAREST EDGE OF THE DEVICE IS 6 TO 8 INCHES FROM THE FACE OF THE CURB. TRUNCATED DOMES IN THE DETECTABLE WARNING SURFACE SHALL MEET THE REQUIREMENTS OF THE GEOMETRIC CONFIGURATION SHOWN. DOMES SHALL BE ALIGNED ON A SQUARE GRID IN THE PREDOMINANT DIRECTION OF TRAVEL TO PERMIT WHEELS TO ROLL BETWEEN DOMES. DETECTABLE WARNING DEVICE SHALL BE 24 INCHES IN THE DIRECTION OF TRAVEL AND EXTEND THE FULL WIDTH OF THE CURB RAMP OR FLUSH SURFACE. DETECTABLE WARNING DEVICE SHALL BE ON THE ADOT QUALIFIED PRODUCTS LIST FOR CAST-IN-PLACE TACTILE PANELS (ADA DETECTABLE WARNING).



**DETECTABLE WARNING DEVICE DETAIL**



**NOTE:** THE CROSS SLOPE OF THE RAMPS, LEVEL LANDINGS, AND SIDEWALKS SHALL NOT EXCEED 2.0% UNLESS REQUIRED TO MATCH STREET LONGITUDINAL GRADE.



**GENERAL NOTES:**

IN NEW CONSTRUCTION, UNLESS OTHERWISE INDICATED ON THE PLANS, WHEELCHAIR RAMPS ARE TO BE PROVIDED AT ALL CORNERS OF CURBED STREET INTERSECTIONS AND MID-BLOCK CROSSWALK LOCATIONS. IN ALTERATIONS WHEELCHAIR RAMPS ARE TO BE PROVIDED AT CURBED STREET INTERSECTIONS WITH PEDESTRIAN TRAFFIC AND MID-BLOCK CROSSWALK LOCATIONS. THE LENGTH OF THE RAMP SHALL BE SUCH THAT THE SLOPE DOES NOT EXCEED 12:1. THE SURFACE TEXTURE OF THE RAMP SHALL CONFORM TO A CLASS 6 FINISH ACCORDING TO SECTION 802.19. THE NORMAL GUTTER GRADE SHALL BE MAINTAINED THROUGH THE AREA OF THE RAMP. ALL PAYEMENT MARKINGS SHALL BE IN ACCORDANCE WITH THE LATEST EDITION OF THE MANUAL OF UNIFORM TRAFFIC CONTROL DEVICES PUBLISHED BY THE FEDERAL HIGHWAY ADMINISTRATION. THE MINIMUM THICKNESS OF THE RAMP, WALK, & LANDING SHALL BE 4". THE MINIMUM WIDTH OF THE RAMPS SHALL BE THE WALK WIDTH OR 36", WHICHEVER IS GREATER. RAMPS SHALL BE MODIFIED AS NECESSARY TO INSURE THAT THEY ARE PARALLEL TO A LINE DRAWN FROM THE CENTER OF ONE RAMP TO THE CENTER OF THE RAMP ON THE OPPOSITE SIDE OF THE INTERSECTION. THE DIMENSIONS AND QUANTITIES SHOWN ON THIS DRAWING ARE FOR A 90° INTERSECTION ONLY. DIMENSIONS AND QUANTITIES FOR SKEWED INTERSECTIONS WILL VARY, AND ARE TO BE DETERMINED BY THE ENGINEER.

**RAMP SELECTION CRITERIA**

CHOICE	TYPE	DESCRIPTION
FIRST CHOICE	TYPE 1	CORNER LOCATIONS WITH THE WALK ADJACENT TO THE CURB (BOTH NEW CONSTRUCTION AND ALTERATIONS).
	TYPE 2	CORNER LOCATIONS WITH THE WALK OFFSET FROM THE CURB A DISTANCE INSUFFICIENT TO ALLOW THE REQUIRED RAMP SLOPE (BOTH NEW CONSTRUCTION AND ALTERATIONS).
	TYPE 3	CORNER LOCATIONS WITH THE WALK OFFSET FROM THE CURB A DISTANCE SUFFICIENT TO ALLOW THE REQUIRED RAMP SLOPE (BOTH NEW CONSTRUCTION AND ALTERATIONS).
SECOND CHOICE	TYPE 4	TANGENT LOCATIONS (BOTH NEW CONSTRUCTION AND ALTERATIONS).
	TYPE 5	TANGENT LOCATIONS (ALTERATIONS ONLY).
THIRD CHOICE	TYPE 6	CORNER LOCATIONS (ALTERATIONS ONLY), THIS RAMP MAY BE USED ONLY IF THE TYPE 5 RAMPS CANNOT BE PLACED AT THE ENDS OF THE RADIUS.
FOURTH CHOICE		IF SITE CONSTRAINTS PREVENT THE CONSTRUCTION OF ANY OF THE TYPES LISTED, THEN AND ONLY THEN CAN THE 12:1 MAX. SLOPE ON THE RAMP BE EXCEEDED TO PROVIDE ACCESS TO THE STREET LEVEL (ALTERATIONS ONLY). THE SLOPE CAN BE STEEPENED TO A 10:1 MAX. FOR A MAX. LENGTH OF 5' OR A 8:1 MAX. FOR A MAX. LENGTH OF 2'. SLOPES STEEPER THAN 8:1 ARE NOT ALLOWED UNDER ANY CIRCUMSTANCES.

**NOTE:** IN ALTERATIONS, THE SELECTION OF THE TYPE OF WHEELCHAIR RAMP TO BE CONSTRUCTED SHALL BE BASED ON THE AMOUNT OF RIGHT-OF-WAY AVAILABLE, AND ON THE PRESENCE OF OTHER SITE CONSTRAINTS (UTILITIES, BUILDINGS, ETC.). THE TABLE ABOVE LISTS THE ORDER IN WHICH THE RAMPS ARE TO BE CONSIDERED. AN ALTERATION IS DEFINED AS A PROJECT THAT CHANGES OR AFFECTS THE USE OF A PEDESTRIAN PATHWAY (OVERLAYS, SIGNALIZATION PROJECTS, ETC.) BUT DOES NOT REQUIRE THE PURCHASE OF ADDITIONAL RIGHT-OF-WAY. ALL PROJECTS THAT REQUIRE THE PURCHASE OF ADDITIONAL RIGHT-OF-WAY WILL USUALLY BE CONSIDERED NEW CONSTRUCTION FOR THE PURPOSES OF THE CHART ABOVE.

DATE	REVISION	DATE FILM
11-10-05	REVISED TO NEW SIDEWALK POLICY	
10-9-03	REVISED GEN. NOTES & ADDED NOTE	
4-10-03	REV. DETECTABLE WARNING DEVICES	
8-22-02	ADD DETECTABLE WARNING DEVICES	
3-30-00	ADD SLOPE, TRANS. & REV. ISL. DIMS.	
11-8-98	REVISED NOTES	
8-12-98	REVISED TEXTURE	
7-02-98	REDRAWN & REISSUED	
10-18-96	CORRECTED DIMENSIONS	10-18-96
5-24-90	FROM 10:1 MAX. SLOPES	5-24-90
7-15-88	ADJUSTED MAX. SLOPE	652-7-15-88
7-14-88	INCLUD. "CONC. ISLD." IN PAY ITEM	-----
6-02-76	ISSUED-P.H.D.	299-7-28-76

**ARKANSAS STATE HIGHWAY COMMISSION**

**WHEELCHAIR RAMPS  
NEW CONSTRUCTION  
AND ALTERATIONS**

**STANDARD DRAWING WR-1**