

Retarding Admixture For Use in Portland Cement Concrete

Supplier	Brand	Dosage Rate
GCP Applied Technologies Inc. Cambridge MA	Recover	2 - 6 oz. per 100# cement
	WRDA-79	7.5 - 15 oz. per 100# cement
Master Builders Souolutions Admixtures US, LLC. Cleveland OH	MasterPozzolith 200	Up to 6 oz per 100# cement
	MasterPozzolith 80	3 - 10 oz per 100# cement
	MasterSet DELVO	4 ± 1 oz per 100# cement
	MasterSet R 100	3 ± 1 oz per 100# cement
	MasterSet R 300	4 ± 1 oz per 100# cement
	MasterSet R 961	4 ± 1 oz per 100# cement
Sika Corporation Lyndhurst NJ	Sika Plastiment	*2 - 6 oz. per 100# cement
	Sika Plastocrete-250	5 - 9 oz. per 100# cement
	SikaTard-440	*2 - 8 oz. per 100# cement

* Classed as a type D at this dosage rate

Method of Documentation of Acceptance:

By brand and source.

Method of Approval:

THE FOLLOWING PROCEDURE IS TO BE USED IN ACQUIRING APPROVAL OF RETARDING AGENTS:

- The manufacturer/supplier shall provide the Materials Division with a test report from a recognized laboratory indicating compliance with AASHTO M 194, Standard Specification for Chemical Admixtures for Concrete. A recognized laboratory is any State Highway Agency, Federal Highway Administration or independent laboratory regularly inspected by AASHTO re:source, Cement and Concrete Reference Laboratory(CCRL) or other Department approved accreditation/inspection agency. All test reports shall include the manufacturer's name, brand name of the material, and date of testing.
- In addition to the requirements of the AASHTO Specification, the manufacturer/supplier shall include:

Retarding Admixture For Use in Portland Cement Concrete

- **The type material, B or D – (B: Retarding admixture, or D: Water-reducing and retarding admixture).**
- **The constituents of the retarder (Example – This material is a solution of calcium salt of lignosulphonic acid).**
- **The chloride content of the admixture and whether or not chloride was added during its manufacture.**
- **Recommended dosage rate.**
- **Uniformity and equivalence tests according to AASHTO M 194 to provide results against which later comparison can be made. Where the nature of the admixture or the Department's testing capabilities may make some or all of the procedures unsuitable, other requirements may be established by agreement between the Department and the manufacturer.**
- **A sample of the retarding agent will be supplied to the Materials Division at the following address. Product information and Safety Data Sheets (SDS) must be included.**
- **If the product meets material requirements, the product will be approved for inclusion after receipt of a signed QPL certification.**
- **Destination samples will be taken as deemed necessary to assure compliance with specifications. Material failures either in the laboratory or in field applications may be considered sufficient cause to reject the material. The Materials Engineer will determine if the failures warrant discontinuing acceptance and removal from this QPL.**

No information contained in these lists is to be used for promotional purposes.

The manufacturer of privately labeled products must be disclosed.